



KE-910 Limited Slip Booster

Product Segment: Lubricants
Product Category: Automotive, Racing
Product Sub-Category: Differential
Description: Top-treat booster for limited slip differentials.

Features:

- This booster can be mixed with existing axle lubricants to improve differential performance.
- **Performance improvements include:**
 1. Reduced axle chatter and noise.
 2. Reduced operating temperature of the gear oil.
 3. Mitigates corrosion inside of the differential.
 4. Extends gear life.

Applications:

- Designed exclusively for limited slip differentials/axles.
- Not for use in automatic transmissions.

Technical Information:

Test Method	Test Description	
	Product Color	Red
D445	Kinematic Viscosity, 40°C (cSt)	
D445	Kinematic Viscosity, 100°C (cSt)	7.1
D2270	Viscosity Index	
D92	Flash Point (°C)	125 (minimum)
D97	Pour Point (°C)	
D4052	Specific Gravity @ 15.6°C (g/mL)	0.91



KE-910 Limited Slip Booster

Directions for Use:

Drain the limited slip differential while the gear oil is at its operating temperature. Pour the contents of the Klotz bottle into the differential. Fill the differential to the proper level with an appropriate gear oil.

Dosage:

One bottle will treat one to two quarts of axle oil. Two bottles will treat three to five quarts of axle oil.

Ordering Options:

Part No.	Bottle Volume	Bottles Per Package
KE-910	4 fluid ounces	1 Bottle

Klotz Synthetic Lubricants

7424 Freedom Way

Fort Wayne, IN 46818

Website: www.klotzlube.com

Technical Support Line: 260-490-0489

Order Line: 800-242-0489

Order Email: salesteam@klotzlube.com