



# Snowmobile Techniplate

**Product Segment:** Lubricants

**Product Category:** Snowmobile

**Product Sub-Category:** 2-Stroke Engine Oil

**Description:** High-performance lubricant for two-stroke snowmobile engines.

## Klotz Techniplate has the Following Features:

- Mitigates high-temperature oxidation, deposit formation, and spark plug fouling.
- Contains dispersants to reduce smoke generation.
- Delivers outstanding cold flow characteristics and resists low-temperature gelling.
- Protects against piston scuffing during cold start-ups.
- Remains in suspension when mixed with gasoline.
- Meets API TC and ISO-EDG performance requirements.
- Carries the signature Klotz scent.

## Applications:

- Compatible with direct fuel injection (DFI), air-cooled, and exhaust power valve configurations.
- Can be used with Arctic Cat, Ski-Doo, Polaris, and Yamaha engines (including C-TEC and E-TEC).

## Technical Information:

Test Method	Test Description					
	Product Color	Red				
D445	Kinematic Viscosity, 40°C (cSt)	30.84				
D445	Kinematic Viscosity, 100°C (cSt)	6.11				
D2270	Viscosity Index	150				
D92	Flash Point (°C)	93				
D97	Pour Point (°C)	-51				
D4052	Density at 15.56°C (g/mL)	0.8587				



# Snowmobile Techniplate

**Directions for Use:**

- **PRE-MIX:** Blend with gasoline per engine manufacturer’s recommendation or pre-mix at ratios between 32:1 and 50:1.
- **OIL INJECTION:** Pour directly into oil injection tank.

**Certifications and Credentials:**

- NMMA TC-W3
- JASO FD

**Ordering Options:**

Part No.	Bottle Volume	Bottles Per Package
KL-215	1-Quart	10 Bottles / Package
KL-216	1-Gallon	4 Bottles / Package
KL-215 5 PL	5-Gallon Pail	1 Bottle / Package
	30-Gallon Drum	
	55-Gallon Drum	

**Klotz Synthetic Lubricants**

7424 Freedom Way

Fort Wayne, IN 46818

**Website:** [www.klotzlube.com](http://www.klotzlube.com)

**Technical Support Line:** 260-490-0489

**Order Line:** 800-242-0489

**Order Email:** [salesteam@klotzlube.com](mailto:salesteam@klotzlube.com)