



KL-302 Motorcycle Techniplate

Product Segment: Lubricants
Product Category: Motorcycle
Product Sub-Category: 2-Stroke Engine Oil
Description: High-performance lubricant for two-stroke motorcycle engines.

Klotz Techniplate has the Following Features:

- Mitigates high-temperature oxidation, deposit formation, and spark plug fouling.
- Contains dispersants to reduce smoke generation.
- Corrosion inhibitors and anti-oxidants prevent rust and corrosion.
- Protects against bearing and piston ring wear.
- Remains in suspension when mixed with gasoline.
- Meets API TC and ISO L-EGD performance requirements.
- Carries the signature Klotz scent.

Applications:

- Compatible with direct fuel injection (DFI), two-stroke engines.
- Can be used with street, offroad, and track bikes.
- Will blend with gasoline at ratios of 15:1 or greater.

Technical Information:

Test Method	Test Description					
	Product Color	Red				
D445	Kinematic Viscosity, 40°C (cSt)	30.84				
D445	Kinematic Viscosity, 100°C (cSt)	6.11				
D2270	Viscosity Index	150				
D92	Flash Point (°C)	93				
D97	Pour Point (°C)	-51				
D4052	Density at 15.56°C (g/mL)	0.8587				



KL-302 Motorcycle Techniplate

Directions for Use:

- **PRE-MIX:** Blend with gasoline per engine manufacturer’s recommendation.
- **OIL INJECTION:** Pour directly into oil injection tank.

Certifications and Credentials:

- NMMA TC-W3
- JASO FD

Ordering Options:

Part No.	Bottle Volume	Bottles Per Package
KE-302	1-Quart	10 Bottles / Package
KE-302 30 GL	30-Gallon Drum	
KE-302 55 GL	55-Gallon Drum	

Klotz Synthetic Lubricants

7424 Freedom Way

Fort Wayne, IN 46818

Website: www.klotzlube.com

Technical Support Line: 260-490-0489

Order Line: 800-242-0489

Order Email: salesteam@klotzlube.com