



Motorcycle Techniplate

Product Segment: Lubricants
Product Category: Motorcycle
Product Sub-Category: 4-Stroke Engine Oil
Description: High-performance lubricant for 4-stroke motorcycle engines.

Klotz Techniplate has the Following Features:

- Provides outstanding wear and oxidation protection, detergency, and shear stability.
- Improves piston ring sealing for increased power and efficiency.
- Protects against gear pitting.
- Promotes smoother and quieter operation of clutch and transmission.
- Meets performance requirements for JASO MA2 (friction category for improved clutch performance) and API SN (quality category).
- Carries the signature Klotz scent.

Applications:

- Designed for motorcycle, ATV, and UTV 4-stroke engines.
- Suitable for use with air-cooled or liquid-cooled engines.
- Can be used in conjunction with wet clutches and integrated transmissions.

Technical Information:

Test Method	Test Description	10W-30	10W-40	15W-50	20W-50	
	Product Color	Red	Red	Red	Red	
D445	Kinematic Viscosity, 40°C (cSt)	72.75	110.42	142.01		
D445	Kinematic Viscosity, 100°C (cSt)	11.57	16.11	17.84		
D2270	Viscosity Index	153	156	139		
D92	Flash Point (°C)	231	231	231		
D97	Pour Point (°C)	-21	-39	-36		
D4052	Density (g/mL)	0.8572	0.8607	0.8674		



Motorcycle Techniplate

Directions for Use:

- Fill crankcase to manufacturer’s recommended level.
- Change lubricant according to manufacturer guidelines.

Ordering Options:

Part No.	Bottle Volume	Bottles Per Package
KL-815 (15W-50)	1-Quart	10 Bottles / Package
KL-830 (10W-30)	1-Quart	10 Bottles / Package
KL-840 (10W-40)	1-Quart	10 Bottles / Package
KL-850 (20W-50)	1-Quart	10 Bottles / Package
	30-Gallon Drum	
	55-Gallon Drum	

Klotz Synthetic Lubricants

7424 Freedom Way

Fort Wayne, IN 46818

Website: www.klotzlube.com

Technical Support Line: 260-490-0489

Order Line: 800-242-0489

Order Email: salesteam@klotzlube.com