








New and Upgraded

FY-5000GT



Print width of 5.1M at 288 sqm/hr, Sturdy with ease of use

PRINthead	
	With 4 pcs of Alpha printhead, the latest technology from SPT, particularly designed for signage printing, featuring high performance and low affordability, 30Khz fire frequency, 25pl droplet size, duo colors per head. A perfect combo of speed and resolution.
FEATURES	
	Negative pressure ink supply and heatable sub tanks, to supply stable and steady ink flow under all conditions.
	High intensive cross-beam of 15cmx20cm steel, plus machine finished aluminium bar and double silent linear guide.
	Sturdy frame structure to assure mechanic precision and printing resolution after long life of use.
	Motor driven media spread roll: Media spread roll at front of the platform to accommodate all types PVC material of different thickness.
	Pneumatic electric press handle: pneumatic electric controlled press handle of pinch rollers and grid rollers ease of stable operation.
	3 individually controlled heaters from left to right under the platform with digital displayed temperature.

● Technical Specifications

Model	FY-5000GT	
Printhead	Drop-on-demand piezo α102HG-L	Drop-on-demand piezo α102HG-L 58 nozzles
Number of Printhead	4	8
Print width	5100mm	
Print Speed *	2PASS 288m ² /h	3 PASS 80m ² /h
	3PASS 192m ² /h	4PASS 144m ² /h
	4PASS 144m ² /h	6PASS 90m ² /h
Media Width	5150mm	
Media Type	Vinyl, Flex, Polyester, Back-lit Film, Window Film, etc.	
Ink	Solvent Ink	
Color Configuration	4 Color (C, M, Y, K)	
RIP Software	United Fancy / Maintop / Photoprint	
Print Interface	RJ45	
Printhead Height	Above Media Adjustable 28mm	
Media Transmit	Media Feeding System	
Heating & Drying System	Equipped (Infrared Ray + Fan Drying)	
Operation Environment	Temperature 15-32°C Humidity 35-80%	
Air Pressure Requirement	Positive 8kg	
Power Specification	Printer	AC220V 50HZ 3A 600W
	Dryer	AC220V 50HZ 32A 7100W
	Platform heating	AC220V 50HZ 14A 3100W
Printer Dimension	L7230mm×W1150mm×H1600mm 1200G	
Package Size	L7400mm×W1330mm×H1860mm 1350G	

1. The speed data are taken from the printer at high speed, a difference of 10% may occur when running with different computers.
2. Product specifications are subject to change without notice in advance. Color and shape in picture are for reference, computer and monitor not included. All rights reserved!