

# AUTOMATIC SOFTENERS

Model No.	Softwise 200 (200 Ltr Resin)	Softwise 250 (250 Ltr Resin)
Water Flow	7000 Ltr/Hr	9000 Ltr/Hr
Area Required	4*5 Ft	4*5 Ft
Inlet Water Pressure	3 Kg Max	3 Kg Max
Inlet Max Hardness	800 PPM	800 PPM
Treated Water Hardness	<50 PPM	<50 PPM
Inlet/Outlet Connection	2.00 Inch	2.00 Inch
Drain Line	0.5 Inch	0.5 Inch
Electric Supply	230 V/6 Amp 3 Point Electric	230 V/6 Amp 3 Point Electric
Treated Water Output At 400 ppm	20000 Lt/Regeneration	25000 Lt/Regeneration
Salt Capacity	100 Kg	100 Kg
Process Valve	Fully Automatic	Fully Automatic
Regeneration Pump	Self Priming Pump	Self Priming Pump
Salt Per Recharge	32 Kg	40 Kg
Resin Quantity	200 Kg	250 Kg
Vessel Diameter	16*65 Inch	21*62 Inch
Multi Port Valve	Side Mounted	Side Mounted
Softener Vessel	Included	Included
Salt Tank	Included	Included
Self Priming Motor	Included	Included

Model No.	Softwise 300 (300 Ltr Resin)	Softwise 400 (400 Ltr Resin)
Water Flow	9000 Ltr/Hr	10000 Ltr/Hr
Area Required	4*5 Ft	4*5 Ft
Inlet Water Pressure	3 Kg Max	3 Kg Max
Inlet Max Hardness	800 PPM	800 PPM
Treated Water Hardness	<50 PPM	<50 PPM
Inlet/Outlet Connection	2.00 Inch	2.00 Inch
Drain Line	0.5 Inch	0.5 Inch
Electric Supply	230 V/6 Amp 3 Point Electric	230 V/6 Amp 3 Point Electric
Treated Water Output At 400 ppm	30000 Lt/Regeneration	40000 Lt/Regeneration
Salt Capacity	100 Kg	100 Kg
Process Valve	Fully Automatic	Fully Automatic
Regeneration Pump	Self Priming Pump	Self Priming Pump
Salt Per Recharge	48 Kg	56 Kg
Resin Quantity	300 Kg	400 Kg
Vessel Diameter	21*62 Inch	24*72 Inch
Multi Port Valve	Side Mounted	Side Mounted
Softener Vessel	Included	Included
Salt Tank	Included	Included
Self Priming Motor	Included	Included

## Contact Us