

Professional Water Solution For Every Need



SOFTWISE™
Live Wise - Water Wise



- **ENHANCED SKIN AND HAIR HEALTH:** BY ELIMINATING HARSH MINERALS, HELPS PREVENT DRYNESS AND IRRITATION, RESULTING IN SMOOTHER SKIN AND HEALTHIER HAIR.
- **PROLONGED APPLIANCE DURABILITY:** PREVENTS SCALE ACCUMULATION IN APPLIANCES LIKE WASHING MACHINES AND WATER HEATERS, THEREBY IMPROVING EFFICIENCY AND EXTENDING LIFESPAN.
- **SUPERIOR WATER QUALITY:** IMPROVES THE QUALITY OF WATER, MAKING IT MORE SUITABLE FOR EVERYDAY USE.
- **ECONOMIC BENEFITS:** REDUCES MAINTENANCE EXPENSES AND ENERGY CONSUMPTION BY AVERTING SCALE-RELATED DAMAGES.



AUTOMATIC SOFTENERS

Model No.	Softwise 50 (50 Ltr Resin)	Softwise 100 (100 Ltr Resin)	Softwise 150 (150 Ltr Resin)
Water Flow	2500 L/Hr	4000 L/Hr	6000 L/Hr
Area Required	4*5 Ft	4*5 Ft	4*5 Ft
Inlet Water Pressure	3 Kg Max	3 Kg Max	3 Kg Max
Inlet Max Hardness	800 PPM	800 PPM	800 PPM
Treated Water Hardness	<50 PPM	<50 PPM	<50 PPM
Inlet/Outlet Connection	1.25 Inch	1.25 Inch	1.25 Inch
Drain Line	0.5 Inch	0.5 Inch	0.5 Inch
Electric Supply	230 V/6 Amp = 3 Point Electric	230 V/6 Amp = 3 Point Electric	230 V/6 Amp = 3 Point Electric
Treated Water Output At 400 ppm	5000 Lt/Regeneration	10000 Lt/Regeneration	15000 Lt/Regeneration
Salt Capacity	100 Kg	100 Kg	100 Kg
Process Valve	Fully Automatic Programmable	Fully Automatic Programmable	Fully Automatic Programmable
Regeneration Pump	Self Priming Pump	Self Priming Pump	Self Priming Pump
Salt Per Recharge	8	15	24 Kg
Resin Quantity	50 Kg	100 Kg	150 Kg
Softener Vessel	Included	Included	Included
Salt Tank	Included	Included	Included
Self Priming Motor	Included	Included	Included

AUTOMATIC SAND FILTER

Model No.	Sand Soft 2A	Sand Soft 3A	Sand Soft 6A	Sand Soft 9A
Vessel Diameter (inch)	12	13	16	21
Vessel Height (inch)	48	54	65	62
Silex Media (Kgs)	25	25	50	75
Coarse Sand Media (Kgs)	-	25	50	75
Fine Sand Media (in Kgs)	25	25	50	75
Activation Media	Only Backwash	Only Backwash	Only Backwash	Only Backwash
Maximum Flow	2000 LPH	3000 LPH	6000 LPH	9000 LPH
Multiport Valve Type	Automatic	Automatic	Automatic	Automatic
Multiport valve Size & Mounting	20 NB Top Mount	25 NB Top Mount	50 NB Side Mount	50 NB Side Mount
Maximum Operating Pressure	3.5 Bar	3.5 Bar	3.5 Bar	3.5 Bar



AUTOMATIC CARBON FILTER

Model No.	Carbon Soft 2A	Carbon Soft 3A	CarbonSoft 6A	Carbon Soft 9A
Vessel Diameter (inch)	12	13	16	21
Vessel Height (inch)	48	54	65	62
Silex Media (Kgs)	25	25	50	75
Carbon Media (in Kgs.)	25	50	70	100
Activation Media	Only Backwash	Only Backwash	Only Backwash	Only Backwash
Maximum Flow	2000 LPH	3000 LPH	6000 LPH	9000 LPH
Multiport Valve Type	Automatic	Automatic	Automatic	Automatic
Multiport valve Size & Mounting	20 NB Top Mount	25 NB Top Mount	50 NB Side Mount	50 NB Side Mount
Maximum Operating Pressure	3.5 Bar	3.5 Bar	3.5 Bar	3.5 Bar



SOFTWISE R.O.

Model No.	RO SOFT 100	RO SOFT 250	RO SOFT 500	RO SOFT 1000
Purification Capacity (LPH)	100 LPH	250	500	1000
Precision of purification (Micron)	0.0001	0.0001	0.0001	0.0001
Max Duty Cycle time	5-6 hours	5-6 Hrs	5-6 Hrs	5-6 Hrs
Product Dimension (inch.)	43.9" (H) x 24" (W) x 20" (L)	73(H)x45(W)x26(L)	73(H)x45(W)x26(L)	77(H)x46.9(W)x32(L)
TDS Reduction %	90-95%	90-95%	90-95%	90-95%
Membrane Type	Thin Film Composite	Spiral Wound 40 40x1	Spiral Wound 40 40x2	Spiral Wound 4080
Input Voltage	100-300 Watt AC	100-300 Watt AC	100-300 Watt AC	100-300 Watt AC
Operating Voltage	24V DC	220V AC	220V AC	220V AC
Installation	Floor top	Floor Top	Floor Top	Floor Top
Filter's Life	12 months	12 Months	12 Months	12 Months
Min. Inlet Pressure/Temp.	0.3 Kg/Cm ²	1Kg/Cm ²	1Kg/Cm ²	1Kg/Cm ²
Max. Inlet Pressure/Temp	3.5 Kg/Cm ²	5Kg/Cm ²	5Kg/Cm ²	5Kg/Cm ²
Filter	Sediment, Activated Carbon RO Membrane, Alkaline	Sand Filter, Activated Carbon filter Micron Filter, RO Membrane	Sand Filter, Activated Carbon filter, Micron Filter, RO Membrane	Sand Filter, Activated Carbon filter, Micron Filter, RO Membrane

Contact Us



208, Akashdeep Complex, 21, Snehnagar
 Indore, Madhya Pradesh 452001
 +918602403338

Email wwlivewise@gmail.com
www.waterwisesolutions.in
 Follow Us :