LOADRITE S1100 ON-BOARD SCALE

The Trimble® LOADRITE® S1100 is an on-board scale that provides an accurate in-cab payload measurement for tractors, and skid steers.

The compact design reduces required cab space, which is ideal for smaller machines; while the fourkey user interface enables quick and easy operation.

The system is IP67 rated which means that it is suitable for use in open cabs and exposed conditions where the display could be exposed to moisture or dust.

System Components	
Trigger components	Manually triggered pressure transducer
Pressure transducer	1 X LC 965C
Remote button inputs	N/A
Printer	N/A

Weighing Functions	
Dynamic/static	weighing Static
Multiple implement presets	9 (individually named)
Bucket overload warning	Yes
Zero function	Yes
Recall/subtract function	Yes

Data Functions		
Product short total	1	
Product long total	1	
Bucket/Fork load count	Yes	

Key Features

- Accurate, consistent and reliable weighing
- Easy to use four button interface
- Use up to nine individual attachments (e.g. bucket, forks, hay squeezer)





LOADRITE S1100 ON-BOARD SCALE



Power Requirements		
Supply voltage	12-28.8 VDC	
Current consumption	300 mA	
Power supply protection	3 A fuse	

Physical Specification		
Display	82.2 mm (3.2 inches) backlit LCD	
Weight	190 grams (6.7 oz)	
Dimensions	107.9 x 89.9 x 39.9 mm (4.2 x 3.5 x 1.5 inches)	



Environmental Specification		
-25 °C ~ 85 °C (-13 °F ~ 185 °F)		
-50 °C ~ 85 °C (-58 °F ~ 185 °F)		
IP67		
ISO 16750-5 EP 455 5.8.2		

Other Information		
Supported languages	English	
Warranty	1 year on parts	

YOUR TRIMBLE LOADRITE PROVIDER Loadrite Central Shipping: 20346 Range Line Road Brighton, IL 62012 Mailing: PO Box 668 Valley, NE 68064

888.435.4020 Phone & Fax sales@loadritecentral.com www.loadritecentral.com



Trimble Loadrite Auckland Ltd. 45 Patiki Road, Avondale, Auckland 1026 PO Box 19623, Avondale, Auckland 1746 New Zealand

Tel: +64 9 820 7720 Fax: +64 9 820 7721 info@loadritescales.com www.loadritescales.com

