

Micro Server Level 1—MS1

The Micro Server Level 1 provides a cost effective, easy to use, solution for Modbus, BACnet and SNMP protocol transformation with multiple mounting options.

Description:


MS1 provides a quick, simple and cost-effective way to add data transformation and data monitoring products for Network Management and Building Management Systems. The MS1 provides multiple protocol support for a maximum of 16 devices.

The MS1 supports devices over TCP/IP as well as the serial communication ports available on the unit. Devices connected over multiple ports are supported simultaneously. Multiple devices are also supported through daisy-chaining (multi-drop) at the serial ports. Users must adhere to protocol and electrical standards for proper operation. Converter kits are also available for 2 / 4-wire devices to USB when connecting to the MS1.

Assembly Overview



Dimensions



Assembly

Micro Server Level 1

Power Adapter / US Power Cord

Quick Reference Guide

Features

Supports up to 16 connected devices standard (when DM software is included—support for 64, 128 and 247 devices is also available, please call)

Provides serial and network connectivity

Provides 2 x GbE Ethernet ports for network capable devices. Support simultaneous connection of differing protocols

Wide temperature ranges available

Low Power Design

100% Solid state device

Specification

| | |
|-----------------------------------|---|
| Standard Color | Black |
| Construction | Die Cast Aluminum |
| Processor / Memory | Intel Atom / Celeron (or greater), 4GB DDR3L-1866 (min) |
| System I/O | 2 x GbE RJ-45 Lan Connection 2 x USB 3.0, 2 x USB 2.0, 1 x RS-232 via mini serial connector 1 x HDMI up to 3840 x 2160 @ 30Hz, 1 x DisplayPort 1.2 up to 4096 x 2160 @ 60Hz via Mini DP connector |
| Protection | Processor fan speed control, Voltage and Temperature sensing, Fan sensor inputs, ACPI-complaint power management control |
| Storage | Solid State HDD |
| System Indicator | HDD LED, Power LED |
| Power Supply | 7–20VDC input (power supply included) 15watts max |
| Operating Temperatures / Humidity | 0C–45C (standard), -20C–70C (extended available), -40C– 85C (industrial available) / 5% - 90% non-condensing |
| Storage Temperature | -20C- +70C |
| Dimensions | 4.4" (112mm) x 3.3" (84mm) x 1.3" (34mm) |
| Weight | - .75lb / 350g |
| | |
| | |

Ordering

| | |
|-----------|---|
| MS1 | Micro Server Level 1 and power supply (server only, no software included translation) |
| MS1-DM-xx | Micro Server Level 1 and power supply with DM application |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



PYTHIA TECHNOLOGIES
data transformation solutions

175 S. Sandusky Street, Suite 321 Delaware OH 43015 Tel. 740-363.2272

Sales@pythiatech.com

© 2020 Pythia Technologies, Inc.

All rights reserved throughout the world.

Specification may change at anytime without notice.

Document #: SPEC_MS1_004_0520