

Countertop Template Checklist



- ✓ All entryways to the property or home must be cleared. This includes driveways, walkways and stairs.
- ✓ There must be an authorized person on-site (at least 18 years of age) on template day to answer questions or a lock box must be installed for our technician to enter your property.
- ✓ The sink must be on-site unless your contractor is providing one. Farm and apron front sinks must be cradled and in place within the cabinetry prior to templating.
- ✓ If the sink is customer provided, please ensure it is clearly labeled with your last name. We will be picking the sink up to bring back with us for the fabrication process.
- ✓ Cabinets receiving countertops must be permanently installed and leveled.
- ✓ Cooktop must be on-site and loose from the countertop. Any special cooktop vents need to be on-site as well.
- ✓ Faucets, soap dispensers, sprayers and other accessories requiring holes should be on site. If this is not possible for templating, all relevant model information (spec sheets) should be available to the template or given to your contractor.
- ✓ Supports and end panels must be in place at time of templating. If you have a dishwasher that is not located between two cabinets, you will need a support on the open end.
- ✓ Countertops and cabinets must be cleared off for measurements.

Our templater's name is Rick McClintock. The template process is relatively fast. Depending on the size of your job, you can expect a visit to last between 10 minutes to an hour. Our templater can only answer questions pertaining to measurements. All other questions or concerns must go through your contractor.

A great countertop begins with a great template. Thank you for your help.