

Thales MissionLINK[®] on Iridium CertusSM Data Sheet

Dependable and
robust satcoms,
covering every
continent.



Thales MissionLINK®

Critical global coverage regardless of landscape or location.

- Capable up to Certus 700 services (352kbps up / 704kbps down & 256kbps streaming)
- 100% global satellite coverage and low latency for critical data and voice communications
- Satellite to Land Mobile Radio extendable network through a unique Radio Gateway
- Easily integrates terrestrial 4G with in box least cost routing switch



TERMINAL SPECIFICATIONS	
SIZE	12in x 9 in (30.5 cm x 22.9 cm x 7.6 cm)
WEIGHT	7.5 lb (3.4 kg)
POWER	10-32 VDC input, 11A max (6A avg.), includes powering external MissionLINK High Gain Antenna
IP RATING	IP31
CONNECTORS	Front: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular, VSAT and other IP connections RJ-14 POTS (2 independent phone lines) Rear: DC Power Input (10-32V) MIL-STD-1275D DC Power Input, +12 Regulated GPIO (RS-232, +12V out, Emergency, Radio Gateway, GPIO) TNC Connector, RF connection to Antenna Wi-Fi reverse SMA SIM slot
MECHANICAL VIBRATION AND SHOCK	MIL-STD-810G, Test Method 514.6, Procedure 1, Category 20, Annex D Mil-STD 810G, Test Method 516.6, Procedure IV

ANTENNA SPECIFICATIONS	
High-gain, electronic phased array antenna with no moving parts to enable the fastest upload and download speeds to cover any land communications need from safety services, tracking and location services, out-of-band management to operational reporting and data transfers.	
SIZE	14 in dia. x 4 in h (35.6 cm dia. x 10.2 cm h)
WEIGHT	6.2 lb (2.8 kg)
POWER	Directly powered by the terminal at 24 VDC
IP RATING	IP66
OPERATING TEMPERATURE	-40 to +55 degrees C
MECHANICAL VIBRATION AND SHOCK	MIL-STD-810G, Test Method 514.6, Procedure 1, Category 20, Annex D Mil-STD 810G, Test Method 516.6, Procedure IV

*Specifications are subject to change without notice.

Thales Defense & Security, Inc.

22605 Gateway Center Drive | Clarksburg, MD 20871

Toll-Free: +1.800.324.6089 | Phone: +1.240.864.7695

E-mail: satcomsolutions@thalesdsi.com | www.thalesgroup.com/LINKsatcom