

LockJaw®

SYNTHETIC WINCH LINES, EXTENSIONS & ANCHORS

- Integrated lockable synthetic shackle for secure handling (lines & extensions)
- Stronger & safer than steel winch cables
- Flexible synthetic fibers allow pulling at full load from different angles
- Rust-proof, freeze-proof, weather-resistant and UV-resistant finish



LockJaw® Synthetic Winch Lines and Extensions are the most advanced winch lines on the market. Crafted from high-strength synthetic fibers, our winch ropes outperform traditional wire cables in both strength and overall weight, offering a lighter and safer solution. Every LockJaw Winch Rope & Extension comes equipped with an integrated LockJaw Synthetic Shackle, designed for both convenience and safety. Our shackles feature an exclusive lock that securely holds the shackle closed during use. With LockJaw's patented design, you can effortlessly wrap it around any anchor point. To further safeguard against wear and tear, each winch line is fitted with a 2 ft. long protective sliding sleeve. Extensions feature a kevlar-sleeved tail loop for easy connection to your winch line.

LockJaw Winch Anchors add versatility to winch lines by wrapping around objects to create a variety of anchor points without harming the object or reducing the strength of the winch rope. Winch Anchors can also be paired with synthetic recovery rings to increase the pulling power or to redirect the winch line during a pull. To further safeguard against wear and tear, each Winch Anchor is fitted with a replaceable chafe sleeve. This product is available in 10' and 20' lengths as well as various diameters to match your LockJaw Synthetic Winch Line.

LockJaw winch lines, extensions, and anchors are crafted with high-strength HMPE fibers, feature a 3:1 design factor, and are made in the USA/built to last. They are UV, abrasion, and weather-resistant and will not rust or freeze. Not rated for Lifting.

Applications: Vehicle recovery, towing, transportation, off-roading, agriculture,

Manufactured by Fusion Tools, Inc. SPARTA, TN 38583

www.fusion-tools.com | 615-969-2825

AVAILABLE SIZES

LockJaw Winch Lines w/Integrated Shackle

Part #	WLL (lbs)	Breaking Strength (lbs)	Rope Diameter (in)	Available Lengths (ft) (part # - XXX = length)
20-0188XXX	1,700	5,100	3/16"	25, 40, 50, 75, 100
20-0250XXX	2,833	8,499	1/4"	25, 40, 50, 75, 100
20-0313XXX	4,400	13,200	5/16"	25, 50, 75, 85, 100, 125, 150, 175, 200
20-0375XXX	6,600	19,800	3/8"	25, 50, 75, 85, 100, 125, 150, 175, 200
20-0438XXX	7,400	22,200	7/16"	25, 50, 75, 85, 100, 125, 150, 175, 200
20-0500XXX	10,700	32,100	1/2"	25, 50, 75, 85, 100, 125, 150, 175, 200
20-0563XXX	13,166	39,498	9/16"	25, 50, 75, 85, 100, 125, 150, 175, 200
20-0625XXX	16,933	50,799	5/8"	50, 75, 85, 100, 125, 150, 175, 200

LockJaw Winch Line Extensions w/Integrated Shackle

Part #	WLL (lbs)	Breaking Strength (lbs)	Rope Diameter (in)	Available Lengths (ft) (part # - XXX = length)
21-0188XXX	1,700	5,100	3/16"	25, 50, 75, 100
21-0250XXX	2,833	8,499	1/4"	25, 50, 75, 100
21-0313XXX	4,400	13,200	5/16"	25, 50, 75, 100
21-0375XXX	6,600	19,800	3/8"	25, 50, 75, 100
21-0438XXX	7,400	22,200	7/16"	25, 50, 75, 100
21-0500XXX	10,700	32,100	1/2"	25, 50, 75, 100
21-0563XXX	13,166	39,498	9/16"	25, 50, 75, 100
21-0625XXX	16,933	50,799	5/8"	25, 50, 75, 100

LockJaw Winch Anchors

Part #	WLL (lbs)	Breaking Strength (lbs)	Rope Diameter (in)	Available Lengths (ft) (part # - XXX = length)
22-0188XX	1,700	5,100	3/16"	10, 20
22-0250XX	2,833	8,499	1/4"	10, 20
22-0313XX	4,400	13,200	5/16"	10, 20
22-0375XX	6,600	19,800	3/8"	10, 20
22-0438XX	7,400	22,200	7/16"	10, 20
22-0500XX	10,700	32,100	1/2"	10, 20
22-0563XX	13,166	39,498	9/16"	10, 20
22-0625XX	16,933	50,799	5/8"	10, 20

Manufactured by Fusion Tools, Inc. SPARTA, TN 38583