

# TECHNICAL DATA SHEET

## LUBRIKOOL Radiator Additive

Not an Antifreeze



LUBRIKOOL Radiator Additive is a super anti-rust and corrosion inhibitor, "ready to use", environmentally friendly product. Recommended for radiator cooling systems in combustible engines of passenger cars, trucks and stationary engines.

LUBRIKOOL Radiator Additive is specially formulated to maintain pH balance of the cooling system liquid and together with the corrosion inhibitors, prevent corrosion or scale build-up in the radiator system. The corrosion inhibitors protect the metals such as aluminum and solder, commonly found in engine cooling systems today. It will keep your radiator and cooling system clean and free from corrosion, electrolysis, rust and scale build-up.

**CAN BE USED ON IT'S OWN IN TROPICAL TO MILD CLIMATES or MIXED WITH ETHYLENE OR PROPYLENE GLYCOL BASED ANTIFREEZE TO REACH DESIRED ANTI-FREEZING LEVELS.**

### **LUBRIKOOL Radiator Additive USE INSTEAD OF WATER**

**BIODEGRADABLE  
NON ABRASIVE  
NO MIXING REQUIRED  
PREVENTS CORROSION**

**CHEMICALLY STABLE  
UNIFORM HEAT DISPLACEMENT  
LUBRICATES  
ECONOMICAL**

**NON FLAMMABLE  
READY TO USE  
NON FOAMING  
NO EXTRA ADDITIVES NECESSARY**

- Replenishes depleted Corrosion and Anti-Rust Additives and Water Pump Lubricant.
- Extends the life of the radiator and cooling system by replacing lost corrosion inhibitors
- Environmentally friendly and biodegradable

## Performance Results

LUBRIKOOL Radiator Additive is manufactured and quality control tested to meet corrosion test method ASTM D-1384-87 requirements ( Std test Method for corrosion )

| TEST        | SPECIFICATION                 | RUDSON Engine Coolant |
|-------------|-------------------------------|-----------------------|
| ASTM D-1384 | (wt Loss mg/coupon / 2 weeks) |                       |
| Copper      | 10 max                        | 3.6                   |
| Solder      | 30 max                        | 13.5                  |
| Brass       | 10 max                        | 5.0                   |
| Steel       | 10 max                        | 1.6                   |
| Cast Iron   | 10 max                        | 3.0                   |
| Aluminum    | 30 max                        | 12.0                  |

## PACKAGING:



Name LUBRIKOOL Radiator Additive 1 Gal  
 UPC # 7 36324 00324 2  
 Case Pack 6 / 1 Gal  
 Case Weight 52 lbs ( 23.63 kgs )  
 Pallet pack 45 cs 2,390 lbs ( 1,086 kgs )  
 Truck load 20 pallets 900cs 6/1 gal



# American Manufacturing Co.

1017 E 23 St Hialeah, Florida 33013 USA Tel ( 305 ) 696-7440 Fax ( 305 ) 696-7443  
 Email [info@AmericanMfgCo.com](mailto:info@AmericanMfgCo.com) [www.AmericanMfgCo.com](http://www.AmericanMfgCo.com)

