



S4600-SI R3 L2+ Gigabit Access Switch

Product Overview

S4600-SI R3 is L2 gigabit uplink intelligent switch designed for carrier and MAN networks. It supports comprehensive QoS, enhanced VLAN functions (Dynamic VLAN, Voice VLAN, QinQ, N:1 VLAN Translation etc), Ethernet Ring Protection Protocol (G.8032), classified bandwidth control, intelligent security control, OAM(Operations, Administration and Maintenance), manageability functions and Triple-Play services which fulfill the network requirements demanded by carrier network, MAN access. S4600-SI R3 Series switch offers green features like Fan-less design feature, which can dramatically lower power consumption, achieve green energy and save the cost for the carrier and MAN users.

S4600-SI R3 is equipped with the full GE ports and 4 SFP uplink ports, it integrates advanced management and security functions to provide performance and scalability.

Appearance	Description
 <p>S4600-28P-SI R3.0</p>	<ul style="list-style-type: none"> ● 24x10/100/1000Base-T+4x100/1000Base-X (SFP) ● 1 Console, 1 Reset, 1 USB port ● AC power supply ● Switching capacity: 56Gbps ● Forwarding rate: 41.7Mpps
 <p>S4600-28P-P-SI R3.0</p>	<ul style="list-style-type: none"> ● 24x10/100/1000Base-T PoE+4x100/1000Base-X (SFP) ● 1 Console, 1 Reset, 1 USB port ● PoE+, up to 370w ● AC power supply ● Switching capacity: 56Gbps ● Forwarding rate: 41.7Mpps

Main Features

L3 Forwarding

S4600-SI R3 supports L3 forwarding allowing you to segment your network into workgroups and communicate across VLANs without degrading application performance.

VSF (Virtual Switch Framework)

Virtual Switch Framework can virtualize multiple DCN switches into one logical device, achieving the sharing of information and data tables between different switches. The performance and ports density of the virtualized device is greatly enlarged by times under VSF. VSF also simplifies management work for the network administrator and provides more reliability.

Enhanced Security

IEEE **802.1X** port-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based RADIUS server.

Access Control Lists (**ACLs**) can be used to restrict access to sensitive network resources by denying packets and forward by different policies. User-defined ACL provides more flexible access control for users.

S4600-SI R3 supports **DHCP snooping**, which prevents DHCP attacks and illegal DHCP SERVER by setting trust ports and untrust ports. With DHCP Snooping binding and option82 enabled, it can combine modules like dot1x and ARP, or implement user-access-control independently.

S4600-SI R3 supports abundant L2 security features such as **ARP guard**, **Anti-ARP scanning**, and other ARP and **MAC Security** technology to protect network security and reliability.

High Reliability

S4600-SI R3 supports 4 1G uplink ports, which could be designed to offer redundant uplinks with various ring protection applications, effectively raised the expansibility and performance of the network.

G.8032 provides sub-50ms protection and recovery switching for Ethernet traffic in a carrier ring topology. S4600-SI R3 supports G.8032 v2 and can be deployed in a variety of complex network topologies including single ring, tangent ring, intersecting rings, double rings, and other home networking.

Abundant Multicast Features

S4600-SI R3 also supports **MVR** (Multicast VLAN Register), selectively allows traffic to cross between different VLANs for bandwidth and security reasons. With the MVR Trunk function, which could associate multicast VLAN to trunk port, S4600-SI R3 combines the VLAN data into the same link, saving lots of resources for users.

S4600-SI R3 could prevent multicast traffic from flooding via IGMP Snooping, while multicast traffic is only forwarded to ports associated with multicast devices.

Specifications

Item	S4600-28P-SI(R3.0)	S4600-28P-P-SI(R3.0)
Ports	24x10/100/1000Base-T + 4x100/1000Base-X (SFP) Auto-MIDX	24x10/100/1000Base-T PoE + 4x100/1000Base-X (SFP) Auto-MIDX
Management port	1x Console port	1x Console port
	1x USB2.0 interface	1x USB2.0 interface
Performance		
Switching Capacity	56Gbps	56Gbps
Forwarding Rate	41.7Mpps	41.7Mpps
MAC ADDRESS	16K	16K
Jumbo Frame	10K bytes	10K bytes
Packet Buffer	12Mbits	12Mbits
ACL Table	512	512
Queues per port	8	8
VLAN TABLE	4K	4K
Physical		


Item		S4600-28P-SI(R3.0)	S4600-28P-P-SI(R3.0)
Dimension(W×H×D)		440mm x 43.6mm x 160mm	440mm x 43.6mm x 260mm
Power Input		100~240VAC, 50~60Hz	100~240VAC, 50~60Hz
Max. Power Consumption		<20W	<450W with full PoE output
Cooling		Passive	Active
Temperature		Working 0°C~50°C, Storage -40°C~70°C	Working 0°C~50°C, Storage -40°C~70°C
Relative Humidity		5%~95%, non-condensing	5%~95%, non-condensing
EMC Safety		CE, RoHS	CE, RoHS
PoE		NA	IEEE 802.3af POE (15.4W) IEEE 802.3at POE+ (30W) PoE output 370w
Main Features			
Forwarding		Storage and Forwarding	
VLAN		Port-based VLAN, IEEE802.1Q, private VLAN, Protocol VLAN, Voice VLAN, MAC VLAN Normal QinQ, Flexible QinQ VLAN Translation, N:1 VLAN Translation	
L3 Features		Static Routing, PBR	
DHCP		IPv4/IPv6 DHCP Client, IPv4/IPv6 DHCP Relay Option 82, Option 37/38 IPv4/IPv6 DHCP Snooping, IPv4/IPv6 DHCP Server	
Reliability	Spanning Tree	802.1D STP, 802.1W RSTP, 802.1S MSTP Root Guard, BPDU Guard, BPDU Forwarding, TCN filtering	
	LACP	64 groups / 8 ports	
	L2 Ring Protection	MRPP ERPS (G.8032) Loopback Detection Fast Link	
Security		IP ACL, MAC ACL, MAC-IP ACL, User-Defined ACL Time Range ACL ACL rules can be configured to port, VLAN Storm Control based on packets Port Security, MAC Limit based on VLAN and Port Anti-ARP-Spoofing, Anti-ARP-Scan, ARP Binding ND Snooping DAI IEEE 802.1x Authentication, Authorization, Accounting Radius, TACACS+	
Multicast		IGMP v1/v2/v3 snooping, IGMP Proxy, IGMP v3 MLD v1/v2 snooping	
QoS		8 Queues Per Port Bandwidth Control Flow Redirect Classification based on ACL, VLAN ID, COS, TOS, DSCP, Policing Based on Port and VLAN Single Rate single barrel double color for Policing SP DWRR SDWRR, SP+DWRR for Scheduling Match the IP fragmentation of a message	
Maintenance and Operation Management		TFTP/FTP CLI, Telnet, Console Web/SSL (IPv4/IPv6) SSH (IPv4/IPv6) SNMPv1/v2c/v3	

Item	S4600-28P-SI(R3.0)	S4600-28P-P-SI(R3.0)
	SNMP Trap Public & Private MIB interface RMON 1,2,3,9 Ping, Trace Route Radius Authentication Syslog (IPv4/IPv6) Sntp/NTP (IPv4/IPv6) Dual IMG, Multiple Configuration Files Port Mirror, RSPAN sFlow OAM EFM VCT, DDM ULDP (like Cisco UDLD) LLDP/LLDP MED	
Green Energy	Fanless	Auto-speed fan

Application

S4600 Series switch is deployed as Gigabit access in a Campus / ISP network

S4600 Series POE switch supports Access points, cameras and other PE devices



Order Information

Product	Description
S4600-28P-SI R3	L2+ Full Gigabit Access Switch with 24x10/100/1000Base-T and 4x100/1000Base-X (SFP) ports, static routing, 1 fixed AC power
S4600-28P-P-SI R3	L2+ Full Gigabit Access Switch with 24x10/100/1000Base-T PoE and 4x100/1000Base-X (SFP) ports, static routing, 1 fixed AC power, 802.3af/at Supported, PoE output 370w