



Bone Stock Compacts

www.ultimatederby.com

Chris Williams (402) 890-5513

General Driver Rules & Expectations:

Only Fresh Cars May Be Used

1. ALL RULES MUST BE FOLLOWED OR YOU WILL NOT RUN
2. Drivers must wear seat belt, helmet, fire suit jacket and long pants while participating.
3. ALL drivers must attend the drivers meeting.
4. During event you are given 1 minute to make an aggressive hit or will be disqualified.
5. You MUST run a roof sign.
6. Drivers are not allowed to drink alcohol before they participate. If found with alcohol in system you will not run, no exceptions. **ZERO TOLERANCE RULE!!!**

THIS IS NOT A SET OF RULES BUT A SET OF GUIDELINES OF HOW TO BUILD YOUR CAR. IF IT DOESN'T SAY YOU SPECIFICALLY CAN DO SOMETHING THEN YOU CAN'T!

Car Building Rules:

DO NOT PAINT ANYWHERE ON SUSPENSION OR FRAME; WE WILL NOT EVEN INSPECT YOUR CAR.

1. May be any 1980's and newer front-wheel drive car (Wheelbase up to 112") with a V4 or V6 engine and **must be the original engine** for that car. No modifications or carb conversions of any kind.
2. Remove all glass, mirrors, plastic, outside body chrome & turn signals. Vehicles must be swept clean of all debris. Also, must remove ALL carpet, dash, headliner, rear seats, and any other flammable materials.
3. ZERO crease enhancement, ZERO sheet metal or frame shaping, forming or folding.
4. Hoods must be 100% in stock location and open for inspection. Must have a minimum 12" opening on hood in case of a fire.
5. Hoods may be fastened in 4 places. 2 places with the core support all thread and 2 places with 2 strands of #9 wire. Trunks may be fastened in 4 places with 2 strands of #9 wire only, no all thread. You may weld doors 6 inches total on each vertical seam only 2"x1/8" Strap. Drivers door may be welded 12 inches total on vertical seams only 2" x 1/8" strap. Do not weld hood or trunk!
6. Body mounts and spacers to remain stock and in place. If they are broken or rusted out, a single piece #9 wire may be substituted. No body bolt changing allowed.

DO NOT EVEN TOUCH THEM!!! Exception: You may replace two front body mounts with two 5/8" threaded rod with eight 3-inch washers and 4 nuts, Bottom nut and washer must be inside frame and may extend through hood. ZERO welding allowed to mount this rod.

7. #9 wire or chain **required** in front windshield.
8. Battery **must** be relocated to the interior of the vehicle and properly secured and covered.
9. Must disable airbags.
10. Gas tanks **MUST** be moved behind the seat in the center. All fuel lines running inside the car must be covered. Original gas tanks are not allowed, must be an aftermarket metal or aluminum fuel cell. Gas tanks must be mounted 8-inches off the floor and all sheet metal. A gas tank protector is allowed by must be centered in the car, 24" wide, and 4" away from all sheet metal
11. 4-point square cage only 60" max in length with one 2x3 down tube to sheet metal only per side. Max 60-inch side bars 6-inch max. **Halo bar is mandatory** and must be attached to the back-seat bar and floor sheet metal. No gas tank protector.
12. **Mandatory:** Drivers door must be padded and have a bar or plate on driver's door that is at least

3/16-inch-thick but no more than ONE inch thick- on the inside, outside or both for safety. Plate or Bar must cover the door, not less than 6 inches and not more than 10 inches past each front and rear seams. (NO grader blades, channel iron or I-beams allowed)

13. Must use factory pedals & brakes.

- You are allowed an aftermarket shifter; it may not be mounted in any way that strengthens the car.
- You are allowed an aftermarket steering column.

Everything else must be factory for the year, make and model of the car you are running.

14. You may weld any loaded (loaded on the inside only, nothing on the outside) factory OEM car bumper and you may weld the stock bumper bracket for the car or the bumper to the frame 4 inches from the back of the bumper, single pass only. In addition, you may weld (4) one-inch welds on the back side of the bumper. All bumper material longer than 4" back must be removed.

- Shocks may be collapsed and welded. All shocks and brackets in stock location only and extended one inch in front of frame. No suspension may tie to the body or frame outside of what it was stock.

- **Or** you may shorten to one inch in front of the core support space and hard nose with no shocks or brackets on car

- **Or** you may chain, one piece of chain per side BOLTED from the mount to mount to hold on the bumper.

Instead of a loaded factory bumper you may use a piece of 4"x4"x1/4" flat tubing in its place with original bumper shocks for the car you are running. NO POINT.

15. Any tires are fine, including solid rear forklift tires. You may weld in full centers, all bracing must be inside the lip of the wheel and may not extend past the lip of the wheel.

Only welding allowed is doors, bumper & cage.

**THIS IS NOT A SET OF RULES BUT A SET OF GUIDELINES OF HOW TO BUILD YOUR CAR. IF IT DOESN'T SAY YOU CAN SPECIFICALLY DO SOMETHING THEN YOU CANT.
JUDGES DECISION IS FINAL!!!**

**This is a simple build, keep it that way!
If you call me on these the answer is likely NO! Do not get creative or read into the rules, this is a back to the basics build.**