

Closed Coupled System & Split System Specifications

Horizontal Model (Closed Profile)	PSHOG-200GL-125	PSHOG-300GL-220		PSHOG-300GL-125
Tank Storage Capacity	200L	300L		300L
Number of Solar Collectors	1	2		1
Tank Dimensions (Height/ Diameter)	1495/540mm	1594/648mm		
Collector Dimensions (L/W/D)	2000/1250/80mm	2000/1000/80mm		2000/1250/80mm
Vertical Model (Split System)	PSE2-25-270GL	PSE2-25-340GL	PSE2-25-450GL	PSE3-20-450GL
Tank Storage Capacity	200L	270L	340L	450L
Number of Solar Collectors	1	2	2	3
Booster	3.6kw			
Collector Dimensions (L/W/D)	2000/1250/80mm			2000/1000/80mm
Tank Dimensions (Height/ Diameter)	1503/540mm	1398/648mm	1700/648mm	1721/730mm
Cold Water Inlet Height	82mm	82mm	82mm	82mm
Solar Return Height	625mm	579mm	664mm	711mm
Hot Water Outlet and PTR Valve Height	1300mm	1169mm	1472mm	1472mm
Electrical Booster Height (If applicable)	817mm	748mm	913mm	923mm
Weight KG (Dry)	81	92	105	137
Maximum Water Supply Pressure	680kPa			
Maximum Working Pressure	850KPa			
TPR Valve Pressure	850KPa			
Warranty, Tank and Collectors	7 years			
Warranty, Parts and Labor	1 year			