

Product Family	Power Required	Recommended Supply	Line Voltage
SCM5B	5VDC ±5%	SCMXPRT-001Order Info	105-125VAC 47-63Hz
SCMD (5VDC units)		SCMXPRT-001DOrder Info	105-124VAC 47-63Hz
isoLynx		SCMXPRT-003Order Info	104-132VAC 47-63Hz
		- OR -	200-240VAC 47-63Hz
		SCMXPRE-001Order Info	200-240VAC 47-63Hz
		SCMXPRE-001DOrder Info	207-265VAC 47-63Hz
		SCMXPRE-003Order Info	85-264VAC 47-63Hz
		PWR-4505Order Info	
8B	5VDC ±5%	8BPWR-2Order Info	7-34VDC dc-dc
SCM7B	18 to 35VDC (see model)	PWR-PS5R7WOrder Info PWR-PS5R15WOrder Info PWR-PS5R30WOrder Info PWR-PS5R60WOrder Info PWR-PS5R120WOrder Info	100-120VAC or 200-240VAC
SCM9B	10 to 35VDC		100-120VAC or 200-240VAC
SCMD (24VDC units)	24VDC ±5%		100-120VAC or 200-240VAC
DCP485	10 to 30VDC		100-120VAC or 200-240VAC
DSCA	15 to 30VDC (see model)		100-120VAC or 200-240VAC
DSCL	Loop powered		100-120VAC or 200-240VAC
DSCT	Loop powered		100-120VAC or 200-240VAC
SCTP	Loop powered		100-120VAC or 200-240VAC
DSCP	See model		Loop or Universal 24 to 60VDC/AC or 85 to 230VDC/AC
LDM30	12VAC	U.S. Wall-mount Transformer	120VAC 60Hz 230VAC 50Hz
LDM70		Model PT3Order Info	
LDM85		- OR -	
LDM422		European Style Transformer	
LDM485		Model PT3EOrder Info	
MAQ20	7-34 VDC	Use 24VDC Nominal Supply	
	5VDC at 3A Output	MAQ20-PWR3 Boost Power Supply Module	