



FIG 100 Imported Standard Frac Tank Couplings

Part #	Description - Butt Weld
4" FTS124	3-Piece Coupling (Thread or Weld)
4" FTS 1	Male Sub
4" FTS 2	Wing Nut
4" FTS 3	Blind (Cap) - External Thread
4" FTS 4	Hose End (Thread or Weld)
4" FTS 5	Cap - Internal Thread w/ Gasket
	Description - Thread or Slip-on
6" FTS123	3-Piece Coupling
6" FTS1-W	Male Sub x Slip-on
6" FTS1-T	Male Sub x NPT Thread
6" FTS2	Wing Nut
6" FTS3	Blind (Cap)
6" FTS4	Hose End
6" FTS4-W	Female Sub X Slip-on
6" FTS4-T	Female Sub X NPT Thread
6" FTS124	Male Sub x Wing Nut x Female Sub (Thread or Weld)
6" FTS5	Cap
	Description - Thread or Slip-on
8" FTS123-OR	3-Piece Coupling w/ O-Ring
8" FTS123	3-Piece Coupling
8" FTS1-W	Male Sub x Slip-on
8" FTS1-T	Male Sub x NPT Thread



- GUARANTEED -

FRAC TANK
SUPPLY COMPANY

- . QUALITY . -



8" FTS2	Wing Nut
8" FTS3	Blind (Cap)
8" FTS4	Hose End
8" FTS4-W	Female Sub X Slip-on
8" FTS4-T	Female Sub X NPT Thread
8" FTS124	Male Sub x Wing Nut x Female Sub (Thread or Weld)
8" FTS5	Internal Thread w/ Gasket
Domestic Standard Frac Tank Couplings	
Part #	Description
8" HH123	Domestic 3-Piece Coupling (Thread or Weld)
8" HH1-OR	Domestic Male 'O' Ring Sub x weld-on
8" HH123-OR	Domestic 3-Piece (Thread or Weld) w/ O-Ring
8" O-RING	O-Ring Buna Gasket
8" HH1-T	Domestic Male Sub x Female NPT Thread
8" HH1-W	Domestic Male Sub x Weld-on
8" HH2	Domestic Wing Nut
8" HH3	Domestic Blind (Cap)
8" HH3-T	Teflon Cap
8" HH4	Domestic Hose End
8" HH4-T	Domestic Female Sub X Female NPT Thread
8" HH4-W	Domestic Female Sub X Weld-on
8: HH124 T or W	Domestic Complete Coupling (Thread or Weld)
6" HH1	Domestic Male Sub x Weld-on or Thread

Hose End Coating Available



- GUARANTEED -

FRAC TANK
SUPPLY COMPANY

- . QUALITY . -



6" HH2	Domestic Wing Nut
6" HH3	Domestic Blind (Cap)
6" HH123	Domestic 3-Piece Coupling (Thread or Weld)
6" HH4	Domestic Hose End
6" HH4-W	Domestic Femal Sub x Weld on
6" HH124-W	Domestic Complete Coupling
Infield Repair Nuts	
Part #	Description - Heavy Duty (HD) - Have Double Bolted Key-ways to Insure Thread Alignment and Quality
8" IFR NUT	Infield Repair Nut Half Ring
8" HD IFR	Heavy Duty Infield Repair Nut
6" IFR NUT	Iinfield Repair Nut Full Ring
6" HD IFR	Heavy Duty Infield Repair Nut
Part #	Description - West Texas Frac Tank Couplings
8" WT1-T	West Texas Double Seal Male Sub x Female NPT Thread
8" WT1-W	West Texas Double Seal Male Sub x Weld-on
8" WT2	West Texas Double Seal Wing Nut
8" WT3	West Texas Blind (Cap) with Cast Handle
8" WT3-P	West Texas Blind (Cap) with Pipe Handle
8" WT4-T or W	West Texas Double Seal Female Sub X Female NPT Thread
8" WT4	West Texas Double Seal Hose End
8" WT123-T or W	West Texas Frac Coupling
8" WT124-T or W	Complete Coupling Thread or Weld
8" WTGBN	Buna-N Replacement Gasket (other materials for acid available)



Crimped

Crimped or Banded Frac Hoses Water or Tank Truck Hose
6" & 8" x 21", 36", 43", 51", 63" Overall Length
Domestic or Import ends Available
Rebuild your hoses!!!





KIH COMPOSITE 250

Application: Suction and Discharge of Water, Gasoline, Diesel fuel, Paraffin, Kerosene, Lubricating Oils, 100% aromatics, black oils and heavy lubricants and solvents.

Carcass: Multiple layers of polypropylene fabric, film and polyester barrier layers

Reinforcement: High tensile strength galvanized inner and outer wire

Temperature: -22°F to +176°F (-30°C to +80°C)

Cover: Abrasion resistant PVC impregnated fabric



Part #		ID	Max WP	Burst	Bend Radius	Weight	Max Length
10'	20'	in	psi	psi	in	lb/ft	ft
C040-250B-10-4040SFL	C040-250B-20-4040SFL	4	250	850	16	3.5	65
C060-250B-10-6060SFL	C060-250B-20-6060SFL	6	250	850	23	7.7	65
C080-250B-10-8080SFL	C080-250B-20-8080SFL	8	250	850	32	12.0	65
C0100-250B-10-100100SFL	C0100-250B-20-100100SFL	10	250	850	40	16.9	40
C0120-250B-10-120120SFL	C0120-250B-20-120120SFL	12	250	850	47	19.8	40

Size	Length	Weight	Length	Weight
in	ft	lbs	ft	lbs
4	10	70.55	20	99.20
6	10	160.94	20	233.69
8	10	264.56	20	381.40
10	10	363.76	20	507.06
12	10	551.25	20	760.01

Size	Length	Weight	Length	Weight
in	ft	lbs	ft	lbs
4	10	52.91	20	85.98
6	10	136.69	20	209.44
8	10	227.08	20	343.92
10	10	319.67	20	462.97
12	10	396.43	20	696.16



Large Bore Hose



Orange and Clear w/ Aluminum Cam and Groove

Size	Part #	Description	List
4"	OC04-20-CE	20' Orange and Clear w/ Alum C & E	
6"	OC06-20-CE	20' Orange and Clear w/ Alum C & E	
8"	OC08-20-CE	20' Orange and Clear w/ Alum C & E	

Orange and Clear w/ Bauer-type fittings

Size	Part #	Description	List
4"	OC04-20-B	20' Orange and Clear w/ Bauer-type ends	
6"	OC06-20-B	20' Orange and Clear w/ Bauer-type ends	
8"	OC08-20-B	20' Orange and Clear w/ Bauer-type ends	

Black Nitrile Discharge w/ Aluminum Cam & Groove

Size	Part #	Description	List
4"	BN04-50-CE	50' Black Nitrile discharge w/ Alum C & E	
6"	BN06-50-CE	50' Black Nitrile discharge w/ Alum C & E	
8"	BN08-50-CE	50' Black Nitrile discharge w/ Alum C & E	

Black Nitrile w/ Bauer-type fittings

Size	Part #	Description	List
4"	BN04-20-B	50' Nitrile w/ Bauer-type ends	
6"	BN06-20-B	50' Nitrile w/ Bauer-type ends	
8"	BN08-20-B	50' Nitrile w/ Bauer-type ends	





Metal Hose Assemblies

Construction: SS316L Corrugated flexible hose with 304 double wire braiding

Couplings: TIG welded with 150# SS 316 Swivel flanges at each end. 316 Sch. 40 stub ends



Quality Certifications & Testing

- * Hydrostatic & pneumatically tested
- * ISO 14001:2004
- * PED Certified

Part #		ID (In)	Nom ID (In)	Nom OD (In)	Static Bend Radius (In)	Dynamic Bend Radius (In)	Max WP (PSI)	Weight (lbs)	
10'	20'							10'	20'
BH20-870SS-10-2020SSFL	BH20-870SS-20-2020SSFL	2	1.98	2.77	5	15	867	44	76
BH30-526SS-10-3030SSFL	BH30-526SS-20-3030SSFL	3	3.15	3.99	9	22	526	61	103
BH40-464SS-10-4040SSFL	BH40-464SS-20-4040SSFL	4	4.36	5.06	10	24	455	98	163
BH60-319SS-10-6060SSFL	BH60-319SS-20-6060SSFL	6	5.93	7.12	18	31	312	163	277
BH80-275SS-10-8080SSFL	BH80-275SS-20-8080SSFL	8	7.76	9.29	19	37	270	251	421
BH100-174SS-10-100100SSFL	BH100-174SS-20-100100SSFL	10	9.86	11.45	25	51	174	267	423
BH120-151SS-10-120120SSFL	BH120-151SS-20-120120SSFL	12	11.82	13.50	31	61	151	353	553





Manifold Extender



8" 90 MxF

Manifold Adapters & Extenders	
Part #	Description
WTFXF100	West Texas Double Seal to Standard Frac Coupling Adapter
F100XWT	Standard Frac Coupling to West Texas Double Seal Adapter
MEX12	12" Standard Frac Coupling Manifold Extender
MEX24	24" Standard Frac Coupling Manifold Extender
MEX36	36" Standard Frac Coupling Manifold Extender
WTFX12	12" West Texas Double Seal Frac Coupling Manifold Extender
WTFX24	24" West Texas Double Seal Frac Coupling Manifold Extender
WTFX36	36" West Texas Double Seal Frac Coupling Manifold Extender
8" F100CC	Standard Frac Coupler for Joining Hose Assemblies
8" WTCC	West Texas Frac Coupler for Joining Hose Assemblies
8" 90 MXF	8" 90 Elbow Male X Female
Slip-on /Threaded Flanges	
Part #	Description - Carbon Steel
2-150	2" Slip-on or threaded 150# Flange
3-150	3" Slip-on or threaded 150# Flange
4-150	4" Slip-on or threaded 150# Flange
6-150	6" Slip-on or threaded 150# Flange
8-150	8" Slip-on or threaded 150# Flange
10-150	10" Slip-on or threaded 150# Flange
12-150	12" Slip-on or threaded 150# Flange
Description - Stainless Steel	
2-150	2" Slip-on or threaded 150# Flange





8" TFMM



SPV8

Splitter Valves & "Tees"	
Part #	Description - WOG and Acid
SPV10	8" Male Female Coupling w/ 10" Valve
SPV8	8" Male Female Coupling w/ 8" Valve
8"TFMM	8"Female X Male X Male "Tee"
8"TFMM/SPV	8"Female X Male X Male "Tee" w/ 8" Butterfly Valve in Stem
8" WTSPV	8" West Texas Splitter Valve
Splitters and Tees can be customized as well as coated for acid.	





4-LWM-F

3-150	3" Slip-on or threaded 150# Flange
4-150	4" Slip-on or threaded 150# Flange
6-150	6" Slip-on or threaded 150# Flange
8-150	8" Slip-on or threaded 150# Flange
10-150	10" Slip-on or threaded 150# Flange
12-150	12" Slip-on or threaded 150# Flange
Lightweight Flanges	
Part #	Description - Carbon Steel
2-LW FF	2" Light Weight Female Flange
2-LW MF	2" Light Weight Male Flange
2-LWM-F	2" Light Weight Male X Female Flange Set w/ Bolts
2-LW	2" Light Weight Socket Weld Thread
3-LW	3" Light Weight Socket Weld Flange
3-LWM	3" Light Weight Male Flange
3-LWF	3" Light Weight Female Flang
3-LWM-F	Set of 2 w/ 4 BOLTS
2-3BLW	Bolts for 2 & 3" Flanges (3/8" x 6")
4-LW	4" LW Socket Weld Flange (8 Hole)
4-LWM	4" Light Weight Male Flange
4-LWF	4" Light Weight Female Flange
4-LWM-F	4" Male x Female set (8 hole) w/ bolts
4-6BLW	Bolts for 4 & 6" Flanges (1/2" x 4")





8-LW

6-LWM	6" LW Male Flange (8 Hole)
6-LWF	6" LW Female Flange
6-LWM-F	6" LW Male X Female Flange Set
5-LW	5" LW Socket Weld (6 and 8 Hole)
6-LW	6" LW Socket Weld
8-LW	8" LW Socket Weld
10-LW	10" LW Socket Weld
12-LW	12" LW Socket Weld
STUDS	Studs w/ Nuts (5/8" x 6", 3/4" x 7", 7/8" x 8")
4" 6-Hole Light Flanges	
Part #	Description - Carbon Steel
4-LW6	4" Socket-Weld 6-hole flange
4-LW6F	4" Female Thread 6-hole Flange
4-LW6M	4" Male Thread 6-hole Flange
4-LNM-F	4" Male X Female Set (6 Hole) w/ Bolts
TTMA Flanges	
Part #	Description - Aluminum
TTMA3F	3" Female Flange
TTMA4F	4" Female Flange
TTMA4S	4" Slip on Flange





4 P-L

**Ductile Iron Body / Stainless Steel Stem
Valves Specifically Designed for Frac Tank Supply**

Part #	Description
2 P-L	2" Buna-N Seat / Nylon Coated Disc
3 P-L	3" Buna-N Seat / Nylon Coated Disc
4 P-L	4" Buna-N Seat / Nylon Coated Disc
6 P-L	6" Buna-N Seat / Nylon Coated Disc
8 P-L	8" Buna-N Seat / Nylon Coated Disc
10 P-L	10" Buna-N Seat / Nylon Coated Disc
12 P-L	12" Buna-N Seat / Nylon Coated Disc
3PLBAB	3" Buna-N Seat / Aluminum Bronze Disc
4PLBAB	4" Buna-N Seat / Aluminum Bronze Disc
6PLBAB	6" Buna-N Seat / Aluminum Bronze Disc
8PLBAB	8" Buna-N Seat / Aluminum Bronze Disc
10PLBAB	10" Buna-N Seat / Aluminum Bronze Disc





Hose w/ WT-4



8" Manifold



Hose w/ FTS-4

MANWAYSEA	Manway Buna Gasket
MANSEALVIT	Manway Viton Gasket
MWD21	Manway Door
MANIFOLDS	
PART #	DESCRIPTION
MIU-6	6" Manifold w/ Import Unions
MDU-6	6" Manifold w/ Domestic Unions
MIU-8	8" Manifold w/ Import Unions
MDU-8	8" Manifold w/ Domestic Unions
8" Switcher Hoses – 100 PSI	
PART #	DESCRIPTION - West Texas / Domestic Couplings
WT4/HH4 – 43	
WT4/HH4 – 51	
WT4/HH4 – 63	
WT4/HH4 – 75	
<p>(These come banded using 100 PSI) Crimped ends also available. 150 PSI Hose can be substituted.</p>	
Frac Hoses (Fig100)	
PART #	DESCRIPTION - Banded or Crimped Good-Year Hose 150 PSI in 6" or 8" w/ Standard or Domestic Ends
GYFTS4 – 43-6	6" Hose/ 6" standard ends (overall length in inches, including ends- 43)
GYFTS4 – 51-6	6" Hose/ 6" standard ends





MW21-6



BP-4S



Iron-4 (Square)



Iron-4 (Bar)



MWBS

Description
21" Manway w/ 6" or 12" Neck
Eyebolt Assemblies for Manways
Buna Gasket for 21" Manway
Viton Gasket for 21" Manway
Manway Lids & Hardware



6T x W

Description
6" and 8" Custom cut and threaded nipples
2", 3" & 4" Pipe Caps, Pipe Plugs, & Bull Plugs
3" & 4" Bar (Cross-head) Plugs
3" and 4" half and full collars
Reducing nipples * Not to be used as swages
Eccentric & Concentric 10" x 8" Reducing Nipples
Standard Black Sch 40 Weld & Threaded Elbows
Standard Black Sch 40 Steel Ells
Standard Black Sch 40 Nipples all sizes and lengths
Standard Black Sch 40 Weld and Thread Tees
Plated KC Nipples & Hose Menders



B-10 x 8E