

GAF shingles and roof accessories are made to work together. They provide a system that's built to protect homes—so the people who live inside them can enjoy what matters most.



	LRS	Page			
Technology Index		3			
GAF Lifetime [†] Roofing System LR	S	4-5			
GAF Shingles		6-19			
Timberline® Lifetime† Shingles	Collect	ion LR			
Timberline HDZ®	•	8			
Timberline® UHDZ™	•	9			
Timberline® NS	•	10			
Timberline® CS	•	11			
Designer Lifetime [†] Shingles [®] C	ollectio	on LRS			
Grand Canyon®		13			
Camelot® II		14			
Grand Sequoia®		14			
Woodland®		15			
Slateline®		15			
SBS Modified IR Shingles Colle	ction L	.RS			
Timberline® AS II	•	16-1			
Grand Sequoia® AS	•	16-1			
3-Tab Shingle Collection (Exclu	uded fr	om LR			
Royal Sovereign®		18–19			
Shingle Specifications Chart		20-2			
GAF Roofing Accessories LRS		22-2			
Leak Barriers	•	23			
Roof Deck Protection	•	24			
Starter Strip Shingles		25			
Cobra® Attic Ventilation	•	26			
Ridge Cap Shingles	•	27			
Other Products		28-3			
Master Flow® Ventilation Products					
WeatherSide™ Fiber-Cement S	iding	29			
ThermaCal® Building Envelope Insulation Panels	9	30			
LIBERTY™ Self-Adhering Roofing System		31			



Trust the diamonds



Install any GAF Lifetime[†] Shingle and get a **Lifetime**[†] **Limited Warranty** on your qualifying shingle. Install any GAF Lifetime[†]
Shingle and at least 3 qualifying GAF Accessories, and get a **Lifetime**[†] **Limited Warranty** on your qualifying GAF products.



GAF Advanced Protection® Shingle Technology uses highly advanced design and manufacturing techniques to produce cutting-edge roofing products.

Whether it's warranty coverage that gives homeowners peace of mind or technology that makes their roof look and perform its best. there's a **GAF** diamond badge behind it.



Dura Grip™ Adhesive helps protect your roof investment from winds and wind-driven rain.



Comes with a **25-year StainGuard Plus™** or **30-year StainGuard Plus PRO™** (as indicated) **Algae Protection Limited Warranty¹** against blue-green algae discoloration and GAF Time-Release Algae-Fighting Technology, which releases copper over time for long-lasting algae-fighting power.



StainGuard® Algae Protection² is a 10-year limited warranty against blue-green algae discoloration.



LayerLock® Technology is a proprietary technology which mechanically fuses the common bond between overlapping shingle layers.



WindProven™ Limited Wind Warranty³ is a 15-year limited wind warranty with no maximum wind speed limitation — available when you install the LayerLock®-labeled Shingles as well as GAF starter strips, roof deck protection, ridge cap shingles, and leak barrier or attic ventilation.



25-Year Limited Warranty Term⁴ gives homeowners protection they can trust.



Patent-pending **Dual Shadow Line** for sunset shadows all day long.

[†] Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime Shingles only. See the GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products.

¹The 25-year StainGuard Plus[™] or the 30-year StainGuard Plus PRO[™] Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the appropriate StainGuard Plus[™] or StainGuard Plus Pro[™] logos. See *GAF Shingle & Accessory Limited Warranty* for complete coverage and restrictions, and qualifying products.

²10-year StainGuard® Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the StainGuard® logo. See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions, and qualifying products.

³ 15-year WindProven[™] limited wind warranty on GAF Shingles with LayerLock[®] Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty.

⁴ See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions.

Trust the system that's built to protect


A roof is so much more than shingles. It's layers of protection, working together to help keep your home safe from wind, rain, snow, and even sun.

Install any GAF Lifetime[†] Shingle and at least 3 qualifying GAF Accessories and get a Lifetime[†] limited warranty on your qualifying GAF products plus nonprorated coverage for the first 10 years. For even stronger coverage, ask your GAF factory-certified contractor about enhanced GAF warranties.

Visit gaf.com/LRS for a list of qualifying GAF products.



LIFETIME




^{*}Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime Shingles only. See the GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. Lifetime coverage on shingles and accessories requires the use of any GAF Lifetime Shingle and at least 3 qualifying GAF Accessories. See the GAF Roofing System Limited Warranty for complete coverage and restrictions. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty. Visit gaf.com/LRS for qualifying GAF products.

¹ Contractors enrolled in GAF certification programs are not employees or agents of GAF, and GAF does not control or otherwise supervise these independent businesses. Contractors may receive benefits, such as loyalty rewards points and discounts on marketing tools from GAF for participating in the program and offering GAF enhanced warranties, which require the use of a minimum amount of GAF products.



Timberline[®] Lifetime[†] Shingles Collection

More homeowners in North America rely on Timberline® Shingles than any other brand. They offer just the right combination of beauty, performance, and reliability.



America's #1-selling **Timberline** shingle-now **HDZ®** featuring the industry's pg 7-8 widest nail zone For a highly Timberline® dimensional wood-shake UHDZ™ look in an asphalt pg 7 & 9 shingle The beauty Timberline® of natural NS wood shakes in an asphalt pg 10 shingle Timberline® Our most CS reflective shingle pg 11

For specifications see pages 20-21




For the full collection visit gaf.com/Timberline




Color Availability





Timberline® (JHDZ™		2	3	4
Barkwood		•		•	•
Charcoal		•	•	•	•
Pewter Gray		•	•	•	•
Shakewood			•	•	•
Slate		•	•	•	•
Weathered Wood		•	•	•	•




¹ Limited availability.





Now with GAF Time-Release
Algae-Fighting Technology and
LayerLock® Technology, Timberline HDZ®
offers everything you can expect from an architectural shingle roof, and more.





For more details visit gaf.com/TimberlineHDZ

¹15-year WindProven[™] limited wind warranty on GAF Shingles with LayerLock[®] Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty.



CAF
LIFETIME
LIMITED
WARRANTY TERM
CAF
STAINGUARD
PLUS PRO
ALGAE PROTECTION
TECHNOLOGY
T

Crafted for homeowners ready to go
beyond expectations, Timberline® UHDZ™
Shingles feature a Dual Shadow Line for dramatic
sunset shadows and offer a 30-year StainGuard Plus PRO™
limited warranty against blue-green algae discoloration¹.














For more details visit gaf.com/uhdz





These stylish yet practically priced architectural shingles provide value and performance with a classic shadow effect for a subtle, even-toned look.




















Highly reflective shingles that can help to reduce temperatures in your attic, and help save on air-conditioning costs.²









For more details visit gaf.com/CS

¹15-year WindProven™ limited wind warranty on GAF Shingles with LayerLock® Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation.

See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty.


² Energy cost savings are not guaranteed and the amount of savings may vary based on climate zone, utility rates, radiative properties of roofing products, insulation levels, HVAC equipment efficiency, and other factors.

NOTE: It is difficult to reproduce the color clarity and actual color blends of these products. Before selecting your color, please ask to see several full-size shingles.



Designer Lifetime[†] Shingles Collection

Sophisticated designs, custom color palettes, and high performance, GAF Lifetime[†] Designer Shingles are only a fraction of the cost of traditional slate or wood shakes.



Designer Lifetime[†] Shingles Collection

Designer Life in life	Shingles Collection		
Grand Canyon® pg 13	CONTROL OF THE PARTY OF THE PAR	STAINGUARD PLUS PROTECTION REPROTECTION TO THE PROTECTION OF THE P	Rugged sophistication with striking depth
Camelot II®	Convol	CAF STAINGUARD PLUS PLUS PROFECTION TICS MODELON	Contemporary slate-inspired elegance in an asphalt shingle
Grand Sequoia®	CONTRACTOR OF STATE O	STAINGUARD PLUS MARK POTICION INC. THE CONTROL OF T	Rustic charm meets 21st-century style
Woodland®	West of the second	STAINGUARD PROFECTION INCOME.	The beauty of natural wood shakes in an asphalt shingle
Slateline®	PARAMETERS OF THE PARAMETERS O	STAINGUARD PLUS SOURCED PROTECTION TO NO.LOST	An asphalt shingle with the dramatic look of slate

For specifications see pages 20-21









The ultimate choice for a rugged wood-shake look, offering incredible depth and dimension.









For more details visit gaf.com/GrandCanyon





Artisan-crafted shapes combined with oversized tabs result in a sophisticated beauty unmatched by typical shingles.













For more details visit gaf.com/GrandSequoia



Designed to complement your home's exterior color scheme, these shingles give your home the luxury look you want without breaking your budget.















For more details visit gaf.com/CamelotII











For more details visit gaf.com/Woodland



Bold shadow lines and tapered cut-outs create the look of slate at a fraction of the cost.












For more details visit gaf.com/Slateline



SBS Modified Impact Resistance (IR) Shingles Collection

Engineered with SBS modified asphalt to really take a punch from Mother Nature.



Timberline® AS II

pg 17









Grand Sequoia® AS

pg 17










The look of rugged wood shakes in an asphalt shingle with UL2218 Class 4 impact resistance

For specifications see pages 20-21

UL 2218 Class 4 Impact-Resistance Test

A 2" steel ball is dropped twice from a 20' height onto various target locations to evaluate the shingles' ability to withstand the impact.



	Pass
Result on a standard shingle Evidence of visible ruptures or cracks through the shingle immediately after impact	Results on a Class 4 shingle No evidence of ruptures or cracks through the shingle immediately after impact



For the full collection visit **gaf.com/ArmorShield**





Crafted to pass the UL 2218 Class 4 impact resistance test, and capture the essence of wood in a thick asphalt design.


















For more details visit gaf.com/AS



A durable designer shingle with rugged wood-shake look that passes the UL 2218 Class 4 impact resistance test.











For more details visit gaf.com/GrandSequoiaAS


¹15-year WindProven™ limited wind warranty on GAF Shingles with LayerLock® Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty.

GAF Shingle & Accessory Limited Warranty.



3-Tab Shingles

The perfect choice for first-time buyers, these shingles add beauty and performance to any roof.



Royal Sovereign®

pg 18-19







Excellent performance and a vivid design make for an exceptional investment

For specifications see pages 20-21

Color Availability

Royal Sovere		2	3	5	
Autumn Brown			•	•	•
Charcoal		•	•	•	•
Golden Cedar			•	•	•
Silver Lining			•		•
Weathered Gray			•	•	•
White ¹			•		•
Ash Brown				•	
Nickel Gray			•		
Slate			•	•	

^{3 5}





¹ Royal Sovereign® White can be used to comply with 2019 Title 24, Part 6, Cool Roof Requirements of the California Code of Regulations; is rated by the Cool Roof Rating Council (CRRC); and meets Green Building Standards Code of Los Angeles County for residential buildings.



Beautiful, Reliable, Affordable,









Shingle Specifications

Shingle	Warranty	Technology	Shingle Construction		
Timberline® Lifetime† Shingles Collec	ction				
Timberline HDZ®	t 2 4	LAVERIOCK DULK GRIP	0 0 0		
Timberline [®] UHDZ [™]	UPERMAN PLANT PLAN	DUAL SHADOW LYCHOCK BUT OF THE SHADOW PROTECTION	0 0 0		
Timberline® NS	UPERME STANCHARD	DUIN GRIP			
Timberline® CS	t 2 4	ECOLINIC LIVERIDOR STATE OF PROTECTION			
Designer Lifetime [†] Shingles Collection	on				
Grand Canyon®	UFFINE STANDARD TO THE STANDAR	DUIL GRIP			
Grand Sequoia®	Usernat Usernat Puls	DUIA GRIP			
Woodland®	UFFINE STANDARD	DUN GRP PROTECTED			
Camelot® II	UFINE USING THE PULL	DUNG CHIPT AND			
Slateline®	UFFINE STANDARD TO	DUIL GERP THE PROTECTION			
SBS Modified IR Shingles Collection					
Timberline® AS II	t 2 4	SSS NOVINE DAY DURING THE PROTECTION PROTECTION	3 0 0		
Grand Sequoia® AS	T TIME TO THE TIME	MODIFIED CONTROL OF PROTECTION			
3-Tab Shingle					
Royal Sovereign®	3 25-FAR USUMMOTORIA	DUNA CRIP ANNEXES			

^{*}Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence (or eligible second owner(s)) owns the property where the qualitying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime Shingles only. See the GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. Lifetime coverage on shingles and accessories requires the use of any GAF Lifetime Shingle and at least 3 qualifying GAF Accessories. See the GAF Roofing System Limited Warranty for complete coverage and restrictions. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty. Visit gaf.com/LRS for qualifying GAF products.

¹ See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions.

² 15-year WindProven™ limited wind warranty on GAF Shingles with LayerLock® Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty.

^{3 10-}year StainGuard® Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the StainGuard® logo. See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions, and qualifying products.

	Approximate		roximat	е		Codes											cial
	- 1	Physic	al Attrib	utes	Fire	W	ind	ı	Nationa	ıl		F	Region	ıl		Features	
Pieces/Square	Bundles/Square	Nails/Square ⁵	Exposure	Dimensions	UL Listed to ANSI/UL 790 Class A	ASTM D7158, Class H	ASTM D3161, Class F	ASTM D3018 Type 1	ASTM D3462°	Classified in accordance with ICC-ES AC438	Miami-Dade County Product Control Approved	State of Florida Approved	Texas Department of Insurance Listed	ICC-ES ESR-1475	ICC-ES ESR-3267	Passes UL 2218, Class 4 Impact Test	Cool Roof Rating Council (CRRC) Rated
Pie	Bu	N	<u> </u>	<u>D</u> ia	In	AS	AS	AS	AS	ö	ğ	Stc	Te	32	<u> </u>	Pa	8
64	3	256	5 %" (143 mm)	13 ¼" x 39 %" (337 x 1,000 mm)	•	•	•	•	•	•	7	•	•	•	•		•
64	3	256	5 %" (143 mm)	13 ¼" x 39 ¾" (337 x 1,000 mm)	•	•	•	•	•	•	7	•	•	•	•		
64	3	256	5 %" (143 mm)	13 ¼" x 39 ¾" (337 x 1,000 mm)	•	•	•	•	•	•	7	•	•	•	•		
64	3	256	5 %" (143 mm)	13 ¼" x 39 ¾" (337 x 1,000 mm)	•	•	•	•	•	•	7	•	•	•	•		•
72	6	360	5" (127 mm)	17" x 40" (432 x 1,016 mm)	•	•	•	•	•	•	•	•	•	•	•		
70	5	360	5" (127 mm)	17" x 40" (432 x 1,016 mm)	•	•	•	•	•	•	•	•	•	•	•		
56	4	280	6 ½" (165 mm)	17" x 40" (432 x 1,016 mm)	•	•	•	•	•	•	•	•	•	•	•		
56	4	280	7 ½" (191 mm)	17" x 34 ½" (432 x 876 mm)	•	•	•	•	•	•	•	•	•	•	•		
48	3	288	7 ½" (191 mm)	17" x 40" (432 x 1,016 mm)	•	•	•	•	•	•	•	•	•	•	•		
64	3	256	5 %" (143 mm)	13 ¼" x 39 ¾" (337 x 1,000 mm)	•	•	•	•	•	•		•	•	•	•	•	
72	4	360	5" (127 mm)	17" x 40" (432 x 1,016 mm)	•	•	•	•	•	•	•	•	•	•	•	•	
				1													
English 79 Metric	3	English 316	English 5" (127 mm) Metric 5 %"	English 12" x 36" (305 x 914 mm) Metric 13 ¼" x 39 ¾"	•	•	•	•	7	•	7	•	•	7	•		•

⁴25-year StainGuard Plus™ Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the StainGuard Plus™ logo. See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions, and qualifying products.

^{° 30-}year StainGuard Plus PRO™ Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the StainGuard Plus PRO™ logo. See GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions.



⁵ Steeper slopes and maximum wind warranties may require more nails.

 $^{^{6}}$ Periodically tested by independent and internal labs to ensure compliance with ASTM D3462 at time of manufacture.


 $^{^{7}\}mbox{\rm Applies}$ to some plants (that make referenced product).

⁸ Applies to White only.



Roofing Accessories

Install any GAF Lifetime[†] Shingle and at least 3 qualifying GAF Accessories and you'll get a Lifetime[†] limited warranty on your qualifying GAF products.



Visit **gaf.com/LRS** for a list of qualifying products.

Leak Barriers		GAF WINDPROVEN NINGEWING SECONOCION SECON	Help prevent leaks caused by wind-driven rain and ice dams
Roof Deck Protection	2	WINDPROVEN NINNTE WIND A SEED PROTECTION A SEED PR	Helps shield the roof deck from moisture infiltration
Starter Strip Shingles	3	WINDPROVEN NINTEWISO WES INCOCCIO	Help guard against shingle blow-offs at the eaves and rakes
Cobra® Attic Ventilation	5	WINDPROVEN NINTEWING SPES INCITICATION	Helps reduce attic moisture and heat Also available, Master Flow® Ventilation Products, see page 28
Ridge Cap Shingles	6	WINDPROVEN BERNE WAS DESCRIBED AS THE MEDICAL PROPERTY OF THE PROPERTY OF T	The finishing touch that helps defend against leaks at the hips and ridges

[†] Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not a pplicable. Lifetime coverage on shingles requires the use of GAF Lifetime Shingles only. See the GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions. Visit gar.com/LRS for qualifying GAF products. Lifetime coverage on shingles and accessories requires the use of any GAF Lifetime Shingle and at least 3 qualifying GAF Accessories. See the GAF Roofing System Limited Warranty for complete coverage and restrictions. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty. Visit gaf.com/LRS for qualifying GAF products





¹ 15-year WindProven™ limited wind warranty on GAF Shingles with LayerLock® Technology requires the use of GAF Starter Strips, Roof Deck Protection, Ridge Cap Shingles, and Leak Barrier or Attic Ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty.

Leak Barriers

Help prevent leaks caused by wind-driven rain and ice dams.





StormGuard®


WeatherWatch®

Patterned synthetic film-surfaced peel and stick underlayment for asphalt shingles and metal roofing

- Self-seals fasteners and helps protect vulnerable areas of the roof
- 250°F high-temperature design. Meets or exceeds the performance criteria of ASTM D1970.
- 2 Sq. (200 ft² [18.58 m²]) roll size excludes laps
- Mineral-surfaced peel and stick underlayment for asphalt shingles
- Self-seals fasteners and helps protect vulnerable areas of the roof
- Meets or exceeds the performance criteria of ASTM D1970
- 2 Sq. (200 ft² [18.58 m²]) & 1.5 Sq. (150 ft² [13.94 m²) roll sizes excludes laps

Leak Barrier Application Recommendations:

Strongly recommended around	Optional around	Required by code at ¹	Region ¹	
1. Penetrations				
2. Skylights	5. Hips & rake edges	7. Eaves in colder zones Recommended in	1. Colder zone	
3. Valleys & dormers	. 5: 1	warmer zones	- W	
4. Flashings & transitions	6. Ridges		2. Warmer zone	





For the full collection visit gaf.com/LeakBarriers

¹ Always check local building codes for requirements in your area.


^{*} To qualify for this coverage, must be installed with GAF Lifetime[†] Shingles and at least 3 qualifying GAF Accessories. See GAF.com/LRS for qualifying products and see GAF Roofing System Limited Warranty for complete coverage and restrictions.



Roof Deck Protection

Helps shield the roof deck from moisture infiltration.





Deck-Armor[™]



- Premium breathable synthetic underlayment for asphalt shingles and other roof systems
- Nom. 16 perms, high-traction surface, and tear-resistant construction
- 48" x 250' (1.22 m x 76.2 m); 10 Sq. (1,000 ft² [92.9 m²]) roll size excludes laps

Tiger Paw™



- Premium synthetic underlayment for asphalt shingles and other roof systems
- High-traction surface, tear-resistant construction, and deck side coating provides moisture control
- 48" x 250' (1.22 m x 76.2 m); 10 Sq. (1,000 ft2 [92.9 m2]) roll size excludes laps

FeltBuster®



- High-traction synthetic underlayment for asphalt shingles
- Value-priced, high-traction surface, and tear-resistant construction
- 48" x 250' (1.22 m x 76.2 m); 10 Sq. (1,000 ft2 [92.9 m2]) roll size excludes laps

Shingle-Mate™



- Fiberglass-reinforced underlayment for asphalt shingles
- Fiberglass reinforcement lays flat and helps prevent telegraphing through shingles
- 36" x 144' (.914 m x 43.89 m); 4 Sq. (432 ft² [40.13 m²]) roll size excludes laps

Specialty Underlayment






- Fiberglass-reinforced fire-resistant underlayment for asphalt shingles, metal, wood, and other roof systems
- Helps upgrade the UL Fire Rating of many roofing systems (always see the UL Certification Directory) and helps resist dangerous flame spread
- 42" x 100' (1.07 m x 30.48 m); 3.5 Sq. (350 ft2 [32.5 m2]) roll size excludes laps

For the full collection visit gaf.com/RoofDeckProtection



Help guard against shingle blow-offs at the eaves and rakes.





WeatherBlocker™	 Premium starter strip shingles for all asphalt shingles Extra-wide format, pre-perforated design, and factory-applied Dura Grip™ Adhesive Full sheets measure 17" x 40" (432 mm x 1,016 mm) and cover 50 lin. ft. (15 lm) per bundle. Half sheets measure 8 ½" x 40" (216 mm x 1,016 mm) and cover 100 lin. ft. (30 lm) per bundle.
Pro-Start®	 Starter strip shingles for most standard English and metric-sized asphalt shingles Pre-perforated design with factory-applied Dura Grip™Adhesive Full sheets measure 13" x 38" (330 mm x 965 mm) and are split into half sheets measuring 6 ½" x 38" (165 x 965 mm) to cover 120.33 lin. ft. (36.69 lm) per bundle
QuickStart®	 Peel and stick starter strip roll for most standard English and metric-sized asphalt shingles Mineral surfacing with factory-applied Dura Grip™ Adhesive 9" x 33' (228 mm x 10 m) roll size
StarterMatch®	 Complementary-color starter strip shingles for Grand Sequoia® and Grand Canyon® Shingles 25-year StainGuard Plus™ Algae Protection™ Limited Warranty protects StarterMatch® Starter Strip Shingles from unsightly stains.¹ Used in conjunction with WeatherBlocker™ Full sheets measure 13 ¼" x 40" (337 mm x 1,016 mm) and cover 60 lin. ft. (18.3 lm) per bundle

For the full collection visit gaf.com/StarterStrip

^{*} To qualify for this coverage, must be installed with GAF Lifetime† Shingles and at least 3 qualifying GAF Accessories. See GAF.com/LRS for qualifying products and see GAF Roofing System Limited Warranty for complete coverage and restrictions.

¹ 25-year StainGuard Plus[™] Algae Protection Limited Warranty against blue-green algae discoloration is available only on products sold in packages bearing the StainGuard Plus[™] logo. See *GAF Shingle & Accessory Limited Warranty* for complete coverage and restrictions, and qualifying products.



Cobra® Attic Ventilation

Helps reduce attic moisture and heat.¹



Cobra®

Cobra[®]

Exhaust Vent

SnowCountry®

Advanced





- 10 ½" (267 mm), 8" (203 mm), and 11 ¾" (298 mm) widths; 20' (6.1 m) and 50' (15.24 m) lengths
- Includes 2 ½" (64 mm) Smart Nails™ (Hand Nailable) or 1 ¾" (44 mm) Coil Nails (Nail Gunnable)
- NFA: Hand Nailable 16.9 sq. in./lin. ft. (35,772 mm² per lineal meter); Nail Gunnable — 14.1 sq. in./lin. ft. (29,845 mm² per lineal meter)
- Premium plastic ridge vent for colder climates
- Includes 3" (76 mm) ring shank nails, Snow Guard™ Filter & 3" (76 mm) EasyTear® Sizing
- 11 ½" (292 mm) and 9" (229 mm) widths; 4' (1.2 m) length, 40 lin. ft. (12.2 lm) per box
- NFA: 18 sq. in./lin. ft. (38,100 mm² per lineal meter)





- Includes Snow Guard™ Filter & 3" (76 mm) EasyTear® Sizing
- 11 ½" (292 mm) width; 4' (1.2 m) length, 40 lin. ft. (12.2 lm) per box
- NFA: 18 sq. in./lin. ft. (38,100 mm² per lineal meter)





- Includes 3" (76 mm) ring shank nails & 3" (76 mm) EasyTear® Sizing
- 11 ½" (292 mm) and 9" (229 mm) widths; 4' (1.2 m) length, 40 lin. ft. (12.2 lm) per box
- NFA: 18 sq. in./lin. ft. (38,100 mm² per lineal meter)





■ Plastic roll ridge vent for all climates

- Includes 1 3/4 (44 mm) coil nails, Weather Fighter® Filter & 12" (305 mm) EasyTear® Sizing
- 11 ½" (292 mm) width; 20' (6.1 m) length
- NFA: 12.5 sq. in./lin. ft. (26,458 mm² per lineal meter)

Cobra[®] **Hip Vent**



■ Plastic hip vent for all climates

- Includes 1 ¾" (44 mm) coil nails and Dual Weather Fighter® Filter
- 11 ½" (292 mm) width; 4' (1.2 m) length, 40 lin. ft. (12.2 lm) per box
- NFA: 9 sq. in./lin. ft. (19,050 mm² per lineal meter)

Intake Ventilation

Cobra IntakePro®



- Tapered roll intake vent for all climates
- Includes 1 3/4" (44 mm) coil nails and end cap fabric
- 11" (279 mm) width; 20' (6.1 m) length
- NFA: 9 sq. in./lin. ft. (19,050 mm² per lineal meter)
- 1. See photo for product placement

For more details visit gaf.com/Cobra

^{*}To qualify for this coverage, must be installed with GAF Lifetime† Shingles and at least 3 qualifying GAF Accessories. See GAF.com/LRS for qualifying products and see GAF Roofing System Limited Warranty for complete coverage and restrictions.

NOTE: Always have a balanced attic ventilation system. In no case should the amount of exhaust ventilation at or near the ridge exceed the amount of intake ventilation at or near the soffit. Visit aaf.com/ventcalculator for more details.



The finishing touch that helps defend against leaks at the hips and ridges.





TimberTex®	STAINGUARD PLUS ALASE FOUNDATION AND ALASE FOUNDATI	 Premium double-layer ridge cap shingles for use with Timberline HDZ®, Timberline® NS, UHDZ™, and GAF Designer Lifetime¹ Shingles Pre-perforated design & factory-applied Dura Grip™ Adhesive 12" (305 mm) width, 8" (203 mm) exposure, covers 20 lin. ft. (6.1 lm) per bundle Available in all areas (except West area)
Seal-A-Ridge®	STAINGUARD PLUS ALGAE ENGICIONAL TOTAL STAINGUARD ALGAE ENGICE ALGAE ENGIC ALGAE ALGAE ENGIC ALGAE ENGIC ALGAE ENGIC ALGAE ENGIC ALGAE ENGIC	 Traditional look ridge cap shingles for use with Timberline HDZ®, Timberline® NS, UHDZ™, and CS Shingles Pre-perforated design & factory-applied Dura Grip™ Adhesive 12" (305 mm) width, 6 ²/₃ (169 mm) exposure, covers 25 lin. ft. (7.6 lm) per bundle Available in all areas
TimberCrest®	STANGUARD PLUS AUGAL SOUTCHOM AND A SOUTCH COM AND A SOUT	 Premium SBS-modified bullnose ridge cap shingles for use with Timberline HDZ®, Timberline® NS, UHDZ™, RS/RS+, CS, and GAF Designer Lifetime† Shingles Pre-folded/flexed design & factory-applied Dura Grip™ Adhesive 10" (254 mm) width, 8" (203 mm) exposure, covers 20 lin. ft. (6.1 lm) per box Available in the West area
Ridglass®	STAINGUARD PLUS MAN HOUSE COLOR HOUSE COLO	 High-profile SBS-modified ridge cap shingles for use with Timberline HDZ®, Timberline® NS, RS/RS+, and UHDZ™ Shingles Pre-folded design & factory-applied Dura Grip™ Adhesive 10" (254 mm) width, 8" (203 mm) exposure, covers 31 lin. ft. (9.4 lm) per box Available in the West area
Z®Ridge	STAINGUARD PLUS AGAI PROTICTION	 Wood shake-look ridge cap shingles for use with Timberline HDZ®, Timberline® NS, and UHDZ™ Shingles Pre-perforated design with unique Z-fold design 10" (254 mm) width, 5 ⁵/₈" (143 mm) exposure, covers 33.3 lin. ft. (10.1 lm) per bundle Available in the Southwest and West areas
Seal-A-Ridge® AS	STAINGUARD PLUS	 UL Class 4 impact resistance, pre-perforated design & factory-applied Dura Grip™ Adhesive For use with GAF ArmorShield® Series Shingles 12" (305 mm) width, 5" (127 mm) exposure, covers 25 lin. ft. (7.6 lm) per bundle

For more details visit gaf.com/RidgeCaps

^{*}To qualify for this coverage, must be installed with GAF Lifetime[†] Shingles and at least 3 qualifying GAF Accessories. See GAF.com/LRS for qualifying products and see GAF Roofing System Limited Warranty for complete coverage and restrictions.





Ventilation products that help minimize heat and moisture in attics, while helping to resist mold and mildew.









Power attic vents — roof mount		CAF WINDPROVEN PERFECUENCY PERFECUENCY APPENDIX OF THE CONNET	 Exhaust large amounts of heat and moisture from the attic Hardwired electric or EZ Cool™ Plug-in options High-efficiency PSC motors Thermostat control included on all models. Optional combo humidistat/thermostat control available on select models. Available with optional QuickConnect™ Wi-Fi Technology Available in popular colors to complement most finished roofs
Solar- powered vents	2	WINDPROVEN PROFESSION OF THE PROPERTY OF THE PROFESSION OF THE PRO	 Helps reduce electricity costs associated with operating a fully electric powered vent¹ Available in both solar-powered and unique dual-powered models Solar-powered models run off the sun's power, while dual-powered models switch automatically between sun and house power Thermostat or combo humidistat/thermostat control available on select models
Roof louvers	3	WINDPROVEN HANGLOND STEENSTON	 Allow heat and moisture to escape the attic on roofs with limited ridg Styles: slant-back, square-top, dome Construction: aluminum, galvanized, and plastic. Models with optional weather filter also available Net Free Area per Vent: Options from 37-144 sq.in. (23,871-92,903 mm)
Aluminum ridge vent	4	WINDPROVEN BEHALL METERS AND ADMINISTRATION OF THE PROPERTY OF	 Allows heat and moisture to escape the attic Construction: aluminum with built-in baffle Net Free Area: 21.5 Sq. in. per lin. ft. (45,508 mm² per lineal meter)
Wind turbines		2 WINDPROVEN INFINEWING STEEL MOTORIES WEST MOTORIES WINDPROVEN STEEL MO	 Use wind power to pull heat and moisture from the attic Sizes: 12" (305 mm) and 14" (356 mm) Construction: aluminum internally braced, galvanized internally or externally braced
Soffit/ undereave intake vents			 Allow cooler dry air to enter the attic Styles: continuous, oval, rectangular, EmberShield® closeable Net Free Area per Vent: Options from 22-68 Sq. in (14,194-43,871 mm)
Other vents and accessories	4		Also available: Master Flow® Versa Caps, Gable Wall Louvers, Goose Neck Vents, Vent Caps, Chimney Caps, Zinc Strips, Whole House Fans, and Foundation Vents

For the full collection visit gaf.com/MasterFlow

accessories

¹ Energy cost savings are not guaranteed and the amount of savings may vary based on climate zone, utility rates, radiative properties of roofing products, insulation levels, HVAC equipment efficiency, and other factors.

² While Master Flow® Attric Exhaust Ventilation Products are covered separately by the Master Flow® Powered Ventilation Products Limited Warranty or Master Flow® Ventilation Products Limited Warranty, depending on product, they do count as an eligible qualifying accessory product in the GAF Attric Ventilation category of the WindProven™ Limited Wind Warranty. See gaf.com/LRS for eligible products.



The one and only solution for replacing old asbestos siding.



slaing — contains NO asi	Desios.		
Purity™ Shingle		Textured surface with straight, wavy, or thatched edge	■ Size: 12" x 24" (305 mm x 609 mm) ■ Exposure: Straight and Wavy 11" (279 mm), Thatched 10 ½" (267 mm)
Profile Shingle		Striated surface with straight edge	 Size: 9" x 32" (227 mm x 813 mm) Exposure: 8" (203 mm) Size: 12" x 24" (305 mm x 609 mm) Exposure: 11" (279 mm) Size: 14 5/8" x 32" (371 mm x 813 mm) Exposure: 13 5/8" (346 mm)
Emphasis™ Shingle		Extra-thick wood grain look surface with thatched edge	■ Size: 14 ⁵ / ₈ " x 25 ⁵ / ₃₂ " (371 mm x 639 mm) ■ Exposure: 13" (330 mm)
Accessories			
Siding Backer Strips		Help protect the vertical seams between each piece of siding against weather infiltration	■ 9" (227 mm) ■ 12" (305 mm) ■ 14" (357 mm)
Hot-dipped Galvanized Siding Nails		Help provide maximum holding power and an excellent finished look	■ White, ring shank nails ■ 1 ¾" (44 mm)
Pre-primed Individual Corners		Complete the outside corners of your WeatherSide™ Siding job	■ 9" (227 mm) ■ 12" (305 mm) ■ 14" (357 mm) ■ Emphasis™ corners

Visit gaf.com/WeatherSide



Help reduce heat drive into conditioned/living spaces, and ventilated options exhaust excess moisture to reduce the risk of condensation in the roofing system.¹



Ventilated Roof Insulation Panels

ThermaCal® 1



- For asphalt shingle and metal roof systems
- Nominal 4' x 8' (1.21 m x 2.44 m) panels with single layer of sheathing (7/16" OSB [11.1 mm] standard); other options available
- Includes air space and tongue-and-groove polyiso foam to reduce heat loss through panel joints
- Pre-spaced sheathing eliminates the need for H-clips and allows for sheathing expansion

ThermaCal® 2



- For slate, tile, and maximum loading roof systems
- Nominal 4' x 8' (1.21 m x 2.44 m) panels with two layers of sheathing (7/₁₆" OSB [11.1 mm] standard); other options available
- Includes air space and tongue-and-groove polyiso foam to reduce heat loss through panel joints
- Pre-spaced sheathing eliminates the need for H-clips and allows for sheathing expansion

Non-Ventilated Roof Insulation Panels

ThermaCal®



- For metal roof systems
- Nominal 4' x 8' (1.21 m x 2.44 m) panels with single layer of sheathing (7/16" OSB [11.1 mm] standard); other options available
- Tongue-and-groove polyiso foam to reduce heat loss through panel joints
- Pre-spaced sheathing eliminates the need for H-clips and allows for sheathing expansion

Exterior Wall Insulation Panels

ThermaCal® Wall




- Nominal 4' x 8' (1.21 m x 2.44 m) panels with one layer of sheathing (7/16" OSB [11.1 mm] standard); other options available
- Includes tongue-and-groove polyiso foam (8' [2.44 m] sides only) to reduce heat loss through panel joints
- Pre-spaced sheathing (8' [2.44 m] sides) allows for precision fit and sheathing expansion

Nail Base Insulation Panel Fasteners

ThermaCal® **Light-duty drill** point fasteners

ThermaCal® Thread point fasteners



- Designed for attaching ThermaCal® Insulation Panels to steel roof decks/substrates
- Manufactured with case-hardened and tempered carbon steel
- Designed for attaching ThermaCal® Insulation Panels to wood roof decks/substrates
- Manufactured with case-hardened and tempered carbon steel

For the full collection visit gaf.com/ThermaCal



Granulated self-adhering low-slope roofing system. Installs quickly and easily without the hassles of bulky equipment, unpleasant odors, torches, or open flames on your roof. Perfect for porches, garages, car ports, and sunrooms!



LIBERTY™ Premium SBS Flashing Cement		 1 Gallon (3.79L) Meets or exceeds ASTM D4586, Type 1 Meets or exceeds ASTM D3409 	
LIBERTY™ Asphalt Primer		1 Gallon (3.79L)Meets or exceeds ASTM D41	
LIBERTY™ SBS Self-Adhering Base/Ply Sheet	 2 square (216 sq. ft. [20.1 m²]) roll size - excludes laps Meets or exceeds ASTM D4601, Type II and ASTM D1970 		
LIBERTY™ SBS Self-Adhering Cap Sheet		 1 square (112 sq. ft. [10.4 m²]) roll size - excludes laps Meets or exceeds ASTM D6164, Type I 	

LIBERTY™ Cap Sheet Colors¹:



For the full collection visit gaf.com/Liberty



Timberline® UHDZ™ is now our premium laminate shingle

Featuring our patent-pending Dual Shadow Line, LayerLock® Technology and the StrikeZone® Nailing Area, 20% heavier weight, new 30-year StainGuard Plus PRO™1 limited warranty against blue-green algae discoloration, and the opportunity for Master Elite® contractors to offer 30 years of workmanship coverage, Timberline® UHDZ™ shingles go beyond any GAF shingle you've been able to offer to date. Visit gaf.com/uhdz

©2023 GAF • RESGN100-0223 415172-0223