

Antena AirPoint Shielded Antenna AIRPD6G30M2-PRO (DP30) with Protection Isolator Radome for 0.6m Dish Reflector

Product name: MP DP30 Pro

Model	AIRPD6G30M2-PRO (DP30 Pro)		
Electrical Specifications			
Frequency Range (MHz)	4900-5150	5150-6400	6400-6500
Polarization	Adjustable - Dual Polarized (Vertical and Horizontal) or X-Polarized (+45° and -45°)		
Gain	30 ±1 dBi		
VSWR	≤2.0	≤2.0	≤2.2
Horizontal Beamwidth	4.5°		
Vertical Beamwidth	4°		
F/B Ratio	≥32dB		
Isolation	≥28dB		
Nominal Impedance	50Ω		
Maximum Power	100W		
Lightning protection	DC Ground		
Mechanical Specifications			
Connector	2 x N-Female		
Mounting Mast size	Φ40-70mm		
Dimensions	Φ60cm		
Weight	6.5 KG		
Max. Wind Velocity	210km/h		
Operating Temperature	-40~+60℃		
Protection Isolator	MP-ISODISH-30		
Diameter	Φ650mm		
Height	135mm		
Weight	3.0 KG		
Shell Material	Aluminum		
Front Cover Style	Flat surface		
Front Cover Material	UV-ABS		
Color	White		
For use DP30 Pro	AIRPD6G30M2-PRO (DP30 Pro)		
Package Contents	Aluminum shell, front cover, fasteners Silicone sealant		

