

Excavator Series

1.3 Ton mini excavator

HAIHONG

Shandong Haihong Heavy Industry

CTX8012

Pro Excavator



Premium Chinese Mini Excavator

- Engine: Japanese Yanmar 3cyl diesel engine
- Japanese Shimadzu hydraulic pumps
- Pilot joystick controls
- Adjustable tracks / Swing boom
- Two speed tracking
- Soft/dampening hydraulic system
- Robotic welds / powder coating finish
- Strong TOPS foldable portection bar
- Dual hydraulic auxiliary outlets

BESTPRICEME PTY LTD

Australian dealer: 30 Axis Court, Burpengary QLD 4505, Australia/ bestpriceme.me

Technical specification

Performance

Bucket capacity, m ³	0.03
Travel speed, km/h	2.1/3.3 two speeds
Drawbar pulling force, KN	9.77
Bucket digging force, KN	13.1
Arm crowding force, KN	6.95

Engine

Model	Yanmar 3TNV70-SSY
Type	4 cycle, 3 cylinders, water cooled
Power output, kW/rpm	10/2200
Max. Torque, N.m/rpm	51.9/1600
Displacement, L	0.854
Fuel tank, L	10
Optional engine	Kubota D722 Briggs&Stratton SR2100 Koop KD192

Hydraulic system

Pump	Gear pump
Max. discharge flow, ml/r	11.3
Relief valve setting, Mpa	18
Hydraulic oil tank, L	21

General

Machine mass, kg	1,250
Ground pressure, kPa	27
Track type	Rubber
Standard track width, mm	860
Adjustable track width, mm	842-1060
Total length of track, mm	1300
Individual track width, mm	180

Max. digging reach, mm	3,300
Max. digging depth, mm	1,875
Max. digging height, mm	3,124
Max. dumping clearance, mm	2,174
Min. dumping clearance, mm	864
Maxi. vertical wall digging depth, mm	1,811

Side digging mechanism

Type	Boom swing
Offset angle to the left, Degree	52
Offset angle to the right, Degree	52

Dozer Blade

Width x Height, mm	860/1060 x 150
Working ranges(height/depth), mm	144/305

