

FREE STANDING COMBINATION SERIES I

Model	FS Comb Series I 3HP
*Flow Rate	65 GPM
Height	52"
Width	28"
Depth	34"
Weight	475 lbs
Input Power	208 / 230 / 480 3 Phase 60 Cycle
Control Power	115 Volt, 1 Phase, 15 Amp Max
Primary Pump VFD Driven	3.0 HP
Full Load Amps	8.5 / 8.0 / 4.0
Suction Inlet	2" NPT
Filtered Outlet	1½" NPT
Mass Air or Ozone Outlet	1-1/4" NPT
Discharge Outlet	3" NPT
Ballast Tank	20 Gallon Fibrewound

*GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

- **VFD Driven Single Pump will provide 50 PSI Filtered Water**
- **Lifetime Stainless Steel Filter Element**
- **Standard 25 Micron** (.001 the size of a single white blood cell)
- **Stainless Steel Platform, Components, & Fittings**
- **Mass Air Injection Pre-Treatment ***
- **UL Listed Control Panel**
- **HMI Touchscreen**
- **Includes Pump Guard**

* The Mass Air Injection can be used for air sparging of Storage tank water. Mass Air Sparging will help to control tank odor.

We strongly recommend the use of Ozone/BIOZONE for Total Treatment of Grease, Oil and Color Control.

*Large Amounts of Water
for a Small Amount of Money*

VFD Speed Control Drive

*Self-Cleaning Stainless Steel
Zero Maintenance Filter*



Available Options

- ETL Listed Ozone Systems
- **Bio-Treatment Dosing Control**
- Stainless Steel Housings
- Tank Level Control
- Pump Upgrade (75GPM TEFC Motor)
- EFO-Manual/Auto Freshwater Override
- Pit Flush- Manual/Automatic