

CON-SERV



MANUFACTURING

Standard are the Obvious Con-Serv Qualities:

User Friendly ■ Quality Construction ■ Performance ■ Low Cost to Operate ■ Inexpensive to Purchase

Filter Housings



PART NUMBER	DESCRIPTION	MATERIAL	COLOR	IN/OUT	PSI RATING	FILTER SIZE	GPM
1034	FILTER HOUSING 10" x 2.5"	POLYPROPYLENE	BLUE	3/4"	100	10" X 2.5"	4-5
XL 34	FILTER HOUSING 20" x 2.5"	POLYPROPYLENE	BLUE	3/4"	100	20" X 2.5"	8-12
1035	FILTER HOUSING 10" x 4.5"	POLYPROPYLENE	BLUE	1"	100	10" X 4.5"	15-18
XL 1035	FILTER HOUSING 20" x 4.5"	POLYPROPYLENE	BLUE	1"	100	20" X 4.5"	20-28
X100B	BAG FILTER HOUSING	POLYPROPYLENE	BLUE	2"	100	BAG	up to 70 GPM
X100X3	CARTRIDGE FILTER HOUSING	POLYPROPYLENE	BLUE	2"	100	20" X 2.5" (3)	up to 70 GPM
XL234	MODULAR FILTER	POLYPROPYLENE	BLACK	2" npt or 3" flange	85	BAG OR CARTRIDGE	UP TO 140
4FOS2	FILTERHOUSING 20" (4)	304SS	SS	2"	150	20" X 2.5"	56
4FOS4	FILTERHOUSING 40" (4)	304SS	SS	2"	150	40" X 2.5"	112
7SOF4	FILTERHOUSING 40" (7)	304SS	SS	2"	150	40" X 2.5"	196
12FOS2	FILTERHOUSING 20" (12)	304SS	SS	3" F	150	20" X 2.5"	168
12FOS4	FILTERHOUSING 40" (12)	304SS	SS	3" F	150	40" X 2.5"	336
22FOS3	FILTERHOUSING 30" (22)	304SS	SS	4" F	150	30" X 2.5"	462
22FOS4	FILTERHOUSING 40" (22)	304SS	SS	4" F	150	40" X 2.5"	616
36FOS4	FILTERHOUSING 40" (36)	304SS	SS	6" F	150	40" X 2.5"	720
52FOS4	FILTERHOUSING 40" (52)	304SS	SS	6" F	150	40" X 2.5"	1040

*Based on 7 gpm per 10" length with a 25 micron wound cartridge at 2 psid clean and a viscosity of 1 cps. Flow rates are for guide lines only. Actual flow rates are based on fluid, viscosity, cartridge type, micron ratings and other factors.

X 100 Series



316 SS available
On all 304 SS
Models



Other models not listed
Call for information