

FREE STANDING COMBINATION SERIES I

Model	FS Comb Series I 3HP
*Flow Rate	65 GPM
Height	52"
Width	24"
Depth	34"
Weight	475 lbs
Input Power	208 / 230 / 480 3 Phase 60 Cycle
Control Power	115 Volt, 1 Phase, 15 Amp Max
Primary Pump VFD Driven	3.0 HP
Full Load Amps	8.5 / 8.0 / 4.0
Suction Inlet	2" NPT
Filtered Outlet	1½" NPT
Mass Air or Ozone Outlet	1-1/4" NPT
Discharge Outlet	3" NPT
Ballast Tank	20 Gallon Fibrewound

*GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

- **VFD Driven Single Pump will provide 50 PSI Filtered Water**
- **Lifetime Warranty on Stainless Steel Filter Element**
- **Standard 25 Micron** (.001 the size of a single white blood cell)
- **Stainless Steel Platform, Components, & Fittings**
- **Mass Air Injection Pre-Treatment ***
- **UL Listed Control Panel**
- **Includes Pump Guard**

* Designed for Systems not using other pre-treatment processes, such as ozone or enzyme. The Mass Air Injection can be used for air sparging of Storage tank water. Mass Air Sparging will help to control tank odor.

We strongly recommend the use of Ozone for Total Treatment of Grease, Oil and Color Control.

*Large Amounts of Water
for a Small Amount of Money*

VFD Speed Control Drive

*Self-Cleaning Stainless Steel
Zero Maintenance Filter*



Available Options

- **ETL Listed Ozone Systems**
- **Bio-Treatment Dosing Control**
- **Stainless Steel Housing / Separator**
- **Tank Level Control**