



**Standard are the Obvious Con-Serv Qualities:**

User Friendly ■ Quality Construction ■ Performance ■ Low Cost to Operate ■ Inexpensive to Purchase

**WATER RECOVERY SYSTEMS**

## BAG SLIM SERIES - YS 3 / 5

Model	YS 3	YS 5
* Flow Rate	60 GPM	100 GPM
Height	66"	
Width	72"	
Depth	16"	
Weight	625 lbs	700 lbs
Input Power	208/230/480 3 Phase 60 Cycle	
Control Power	115 Volt 1 Phase 15 Amp Max	
Primary Pump	3.0 HP	5.0 HP
Full Load Amps	8.5 / 8.0 / 4.0	13.0 / 12.2 / 6.1
Optional Secondary Pump	¾ HP @ 3.1 / 1.55 Full Load Amp	
Suction Inlet	2" NPT	3" NPT
Filtered Outlet	1.5" NPT	3" NPT
Ozone Outlet	1-1/4" NPT	
Discharge Outlet	3" NPT	

\* GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

### Available Options

- " F . Primary Bag Filter (5-50 micron)
- " B . Bio Treatment Dosing Control
- " 012 . 12 gram Ozone Treatment
- " 024 . 24 gram Ozone Treatment
- " MA . Mass Air Injection
- " Tank Level Control
- " Ballast Pressure Control

- " 3 / 5 HP Process Pump w/Strainer Basket
- " U/L Listed Electrical Control System
- " Flow Rates up to 100 GPM
- " Vortex Particle Accelerator
- " Brass Check Valves
- " Stainless Steel Piping & Fittings
- " Great for In-Bay Operation
- " Only 16+Deep
- " FRP Panel

