

UV Sterilizers



The Silver Series offer a family of UV disinfection systems that can be used in several types of applications where pricing sensitivity is a deciding factor but reliable equipment is still a must.

The Silver controller displays the remaining lamp life via LED, has a universal power input from 100-204V/50-60Hz and holds full electrical certification including both CSA & CE certificates.

Model	Complete Units	Replacement Parts				Quartz
		Ballast	Controller	Sensor	UV Lamp	Sleeve
\$2Q-PA	JV 2 gpm, 100-240V/50-60Hz	BA-ICE-S	N/A	N/A	S330RL	QS-330
\$2Q-PA/2	JV 2 gpm, 100-240V/50-60Hz, European cord	BA-ICE-S	N/A	N/A	S330RL	QS-330
\$5Q-PA	JV 5 gpm, 100-240V/50-60Hz	BA-ICE-S	N/A	N/A	S463RL	QS-463
\$5Q-PA/2	JV 5 gpm, 100-240V/50-60Hz, European cord	BA-ICE-S	N/A	N/A	S463RL	QS-463
\$8Q-PA	JV 8 gpm, 100-240V/50-60Hz	BA-ICE-S	N/A	N/A	S810RL	QS-810
\$8Q-PA/2	JV 8 gpm, 100-240V/50-60Hz, European cord	BA-ICE-S	N/A	N/A	S810RL	QS-810
\$12Q-PA	JV 12 gpm, 100-240V/50-60Hz	BA-ICE-S	N/A	N/A	S36RL	QS-012
\$12Q-PA/2	JV 12 gpm, 100-240V/50-60Hz, European cord	BA-ICE-S	N/A	N/A	S36RL	QS-012
\$24Q	JV 24 gpm, 100-240V/50-60Hz	BA-ICE-S	N/A	N/A	S36RL	QS-012
\$24Q/2	JV 24 gpm, 100-240V/50-60Hz, European cord	BA-ICE-S	N/A	N/A	S36RL	QS-012
\$P600-HO	JV 35 gpm 1.5" connections, 100-240V/50-60Hz	N/A	SPC-ICE-HO	254NM-FP1	S600RL-HO	QS-600
\$P740-HO	JV 42 gpm 1.5" connections, 100-240V/50-60Hz	N/A	SPC-ICE-HO	254NM-FP1	S740RL-HO	QS-740
\$P950-HO	JV 52 gpm 1.5" connections, 100-240V/50-60Hz	N/A	SPC-ICE-HO	254NM-FP1	S950RL-HO	QS-950

The Sterilight Platinum "SP" series has a range of 8 flow rates available from 15 to 52.0 USGPM. Each system comes equipped with an advanced electronic controller providing a universal power input (100-250V/50-60Hz) & visual display of system performance & lamp life. The Flow Pace™ sensor allows the system to operate with minimal power requirements & heat build-up.



Larger Sizes Available,
Call for Quote.