

CON-SERV



Standard are the Obvious Con-Serv Qualities:

User Friendly ■ Quality Construction ■ Performance ■ Low Cost to Operate ■ Inexpensive to Purchase

MANUFACTURING

Water Softeners (single tank)



Fleck 2510



Fleck 2750



Fleck 2850



Fleck 2900



Fleck 3900

PART NUMBER	DESCRIPTION	Grains	Valve	Inlet/ Outlet	CFT Media	Media Tank	Brine Tank w/ovrflw	Voltage
WCS - 1.0 CFT	WATER SOFTENER 32K	32K	FLECK 2510 TC	3/4"	1	9X48	14X14X34	120/60
WCS - 1.5 CFT	WATER SOFTENER 48K	48K	FLECK 2510 TC	3/4"	1.5	10X54	14X14X34	120/60
WCS - 2.0 CFT	WATER SOFTENER 60K	60K	FLECK 2510 TC	3/4"	2	12X52	14X14X34	120/60
WCS - 3.0 CFT	WATER SOFTENER 96K	96K	FLECK 2750 TC	1"	3	14X65	24RX41	120/60
WCS - 4.0 CFT	WATER SOFTENER 128K	128K	FLECK 2750 TC	1"	4	16X65	24RX41	120/60
WCT - 5.0 CFT	WATER SOFTENER 160K	160K	FLECK 2850 TC	1.5"	5	18X65	24RX41	120/60
WCT - 7.0 CFT	WATER SOFTENER 224K	224K	FLECK 2850 TC	1.5"	7	21X65	24RX41	120/60
WCT - 10 CFT	WATER SOFTENER 320K	320K	FLECK 2850 TC	1.5"	10	24X72	24RX41	120/60
WCT - 15 CFT	WATER SOFTENER 480K	480K	FLECK 2900 NXT	2"	15	30X72	30RX50	120/60
WCT - 20 CFT	WATER SOFTENER 640K	640K	FLECK 3900 NXT	3"	20	36X72	30RX50	120/60
WCT - 30 CFT	WATER SOFTENER 900K	900K	FLECK 3900 NXT	3"	30	42X72 6" T&B Flange	39RX60	120/60
WCT - 40 CFT	WATER SOFTENER 1.2MK	1.2M	FLECK 3900 NXT	3"	40	48X72 6" T&B Flange	39RX60	120/60
WCT - 72 CFT	WATER SOFTENER 2.1MK	2.1M	FLECK 3900 NXT SIDE MOUNT	3"	72	63X86 6" T&B Flange	39RX60	120/60

Optional Features Available

Safety Brine Valve
 Bypass Valve
 220V/50HZ
 Metered Valve



NXT Controller