



SPECIFICATION SHEET

Low Wattage DIRECT-BURIAL



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- NEMA 12 PVC NON-METALLIC BOX WITH BRASS SCREW INSERTS
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MUST USE WATER-TIGHT CONNECTORS DURING INSTALLATION
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER	1030-P-446
PRIMARY VOLTAGE	120VAC-1A MAX
OUTPUT VOLTAGE	12VAC-10A MAX
BREAKERS	1x10A (100VA MAX OUTPUT)
FREQUENCY	60 Hz
DIMENSIONS	4" x 4" x 6"
WEIGHT	6 LBS.