



1200 Watt Magnetic Transformer

24 VAC

Class 1



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- AVAILABLE IN 120VAC OR 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC		277VAC
Part Number:	1028-24	1028-24-C***	1028-24-277
Primary	120VAC - 10A	120VAC - 10A	277VAC - 5A
Secondary:	12VAC - 100A	12VAC - 100A	12VAC - 100A
Protection:	4 x 25A	4 x 25A	4 x 25A
Frequency:	60 Hz	60 Hz	60 Hz
Dimensions (IN):	10.25 x 5.70 x 5.25	10.25 x 5.70 x 5.25	10.25 x 5.70 x 5.25
Weight (LB):	28	28	28

***Note: Sebco 1028-24-C comes standard with a 3' primary line cord