

SPECIFICATION SHEET

12VDC "REGULATED" **MAGNETIC** I FD POWFR SUPPLIES



FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- DUAL PRIMARY OPTIONS OF 120VAC & 277VAC
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MEET CLASS 2 OUTPUT LIMITS
- 12 VOLT PURE "DC" REGULATED RATED OUTPUT
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS

MEETS CLASS 2 LIMITATION REQUIREMENTS. 5 AMP MAX AT 12VDC



 MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)

WATTAGE PART NUMBER PRIMARY VOLTAGE OUTPUT VOLTAGE BREAKERS FREQUENCY DIMENSIONS (L x W x D)

20 WATT 120VAC-1A MAX 12VDC-2A MAX 1x1.7A 60 Hz

5 LBS.

JC20-12DC-120/277, JC40-12DC-120/277, JC60-12DC-120/277 120VAC-1A MAX 12VDC-3.4A 1x3.4A 60 Hz 14-1/4" x 3" x 2-7/8" | 14-1/4" x 3" x 2-7/8" | 14-1/4" x 3" x 2-7/8" 5 LBS.

40 WATT

60 WATT 120VAC-1A MAX 12VDC-5A MAX 1x5A 60 Hz 5 LBS.