

## 150 Watt Magnetic Transformer 24 VAC

Class 2



10 YEAR FREE REPLACEMENT WARRANTY

## **FEATURES**

- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- 2 X 75 WATT CLASS 2 OUTPUTS (TOTAL COMBINED OUT PUT CANNOT EXCEED 150) WATTS)
- AVAILABLE IN 120VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

## **REQUIREMENTS**

- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC
Part Number:	1112
Primary	120VAC - 1A
Secondary:	24VAC - 6.25A
Protection:	2 x 4A Auto Reset
Frequency:	60 Hz
Dimensions (IN):	6.75 x 5 x 4.5
Weight (LB):	10

\*\*120VAC LINE CORD AVAILABLE\*\*