

SPECIFICATION SHEET

24VDC MAGNETIC DIMMABLE LED POWER SUPPLIES



FEATURES

- 3 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MEET CLASS 2 OUTPUT LIMITS
- 24 VOLT "DC" RATED OUTPUT
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS

- MEETS THE REQUIREMENTS FOR UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL. ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER PRIMARY VOLTAGE **OUTPUT VOLTAGE** BREAKERS FREQUENCY DIMENSIONS WEIGHT

192 WATT **288 WATT**

SEB24DC-192W-3R | SEB24DC-288W-3R 120VAC-1A MAX 120VAC-1A MAX 24VDC-8A MAX 24VDC-12A 2x4A 3x4A 60 Hz 60 Hz

14" x 8" x 5" 14" x 8" x 5" 13 LBS. 14 LBS.