



SPECIFICATION SHEET

24VDC "REGULATED"
MAGNETIC
LED POWER SUPPLIES



FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- DUAL PRIMARY OPTIONS OF 120VAC & 277VAC
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MEET CLASS 2 OUTPUT LIMITS
- 24 VOLT "DC" REGULATED RATED OUTPUT
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS

- MEETS CLASS 2 LIMITATION REQUIREMENTS. 4 AMPS AT 24VDC
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)

	20 WATT	40 WATT	60 WATT	96 WATT
PART NUMBER	JC20-24DC-120/277	JC40-24DC-120/277	JC60-24DC-120/277	JC96-24DC-120/277
PRIMARY VOLTAGE	120VAC-1A MAX	120VAC-1A MAX	120VAC-1A MAX	120VAC-1A MAX
OUTPUT VOLTAGE	24VDC-1A MAX	24VDC-2A	24VDC-2.5A MAX	24VDC-4A MAX
BREAKERS	1x1A	1x2A	1x3A	1x4A
FREQUENCY	60 Hz	60 Hz	60 Hz	60 Hz
DIMENSIONS (L x W x D)	14-1/4" x 3" x 2-7/8"	14-1/4" x 3" x 2-7/8"	14-1/4" x 3" x 2-7/8"	14-3/4" x 4-5/16" x 4-13/16"
WEIGHT	5 LBS.	5 LBS.	5 LBS.	8 LBS.