

250 Watt Magnetic Transformer 12 VAC

Class 1



• FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER

FEATURES

10 YEAR FREE REPLACEMENT WARRANTY

- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- AVAILABLE IN 100VAC, 120VAC or 230VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838

REQUIREMENTS

 MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)



• MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC		100VAC	230VAC
Part Number:	1024-12	1083***	1075-12	1063-12
Primary	120VAC - 2.3A	120VAC - 2.3A	100VAC - 2.5A	230VAC - 1.2A
Secondary:	12VAC - 21A	12VAC - 21A	12VAC - 21A	12VAC - 21A
Protection:	1 x 25A	1 x 25A	1 x 25A	1 x 25A
Frequency:	60 Hz	60 Hz	50 Hz	50Hz
Dimensions (IN):	8.25 x 5.75 x 5			
Weight (LB):	13	13	13	13

***Note: Sebco 1083 comes standard with a 3' primary line cord