



# 300 Watt Magnetic Transformer

## 12 VAC

### Class 2



#### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- 5 X 60 WATT OUTPUTS (TOTAL COMBINED OUTPUT CANNOT EXCEED 300 WATTS),
- AVAILABLE IN 120VAC or 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

#### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC	277VAC
<b>Part Number:</b>	<b>1123</b>	<b>1105-12-2</b>
<b>Primary</b>	120VAC - 2.75A	277VAC - 1.2A
<b>Secondary:</b>	12VAC - 25A	12VAC - 25A
<b>Protection:</b>	5 x 5A Auto Reset	5 x 5A Auto Reset
<b>Frequency:</b>	60 Hz	60 Hz
<b>Dimensions (IN):</b>	6.75 x 5 x 4.5	6.75 x 5 x 4.5
<b>Weight (LB):</b>	13	13

\*\*120VAC LINE CORD AVAILABLE\*\*