

300 Watt Magnetic Transformer 24 VAC

Class 1



10 YEAR FREE REPLACEMENT WARRANTY

FEATURES

- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- AVAILABLE IN 120VAC or 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838

REQUIREMENTS

 MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)



• MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC		277VAC
Part Number:	1101-24	1101-24-C***	1105-24
Primary	120VAC - 2.75A	120VAC - 2.75A	277VAC - 1.2A
Secondary:	24VAC - 12.5A	24VAC - 12.5A	24VAC - 12.5A
Protection:	1 x 15A	1 x 15A	1 x 15A
Frequency:	60 Hz	60 Hz	60 Hz
Dimensions (IN):	6.75 x 5 x 4.5	6.75 x 5 x 4.5	6.75 x 5 x 4.5
Weight (LB):	13	13	13

***Note: Sebco 1101-24-C comes standard with a 3' primary line cord