



500 Watt Magnetic Transformer

12 VAC

Class 2



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- 8 X 60 WATT OUTPUTS (TOTAL COMBINED OUTPUT CANNOT EXCEED 500 WATTS),
- AVAILABLE IN 120VAC, 230VAC, OR 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC	277VAC	230VAC
Part Number:	1110	1106-12-2	1063-12-2
Primary	120VAC - 5A	277VAC - 2A	230VAC - 2.4A
Secondary:	12VAC - 42A	12VAC - 42A	12VAC - 42A
Protection:	8 x 5A Auto Reset	8 x 5A Auto Reset	8 X 5A Auto Reset
Frequency:	60 Hz	60 Hz	50 Hz
Dimensions (IN):	8.25 x 5.75 x 5	8.25 x 5.75 x 5	8.25" x 5.75" x 5"
Weight (LB):	19	19	19

120VAC LINE CORD AVAILABLE