



# 500 Watt Magnetic Transformer

## 24 VAC

### Class 2



#### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- 5 X 96 WATT OUTPUTS (TOTAL COMBINED OUTPUT CANNOT EXCEED 500 WATTS),
- AVAILABLE IN 120VAC, 230VAC, OR 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

#### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

|                         | 120VAC            | 277VAC            | 230VAC             |
|-------------------------|-------------------|-------------------|--------------------|
| <b>Part Number:</b>     | <b>1114</b>       | <b>1106-24-2</b>  | <b>1063-24-2</b>   |
| <b>Primary</b>          | 120VAC - 5A       | 277VAC - 2A       | 230VAC - 2.4A      |
| <b>Secondary:</b>       | 24VAC - 21A       | 24VAC - 21A       | 24VAC - 21A        |
| <b>Protection:</b>      | 5 x 4A Auto Reset | 5 x 4A Auto Reset | 5 X 4A Auto Reset  |
| <b>Frequency:</b>       | 60 Hz             | 60 Hz             | 50 Hz              |
| <b>Dimensions (IN):</b> | 8.25 x 5.75 x 5   | 8.25 x 5.75 x 5   | 8.25" x 5.75" x 5" |
| <b>Weight (LB):</b>     | 19                | 19                | 19                 |

\*\*120VAC LINE CORD AVAILABLE\*\*