



600 Watt Direct Burial Transformer

12 VAC

Class 1



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- NEMA 12 PVC NON-METALLIC BOX WITH BRASS SCREW INSERTS
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MUST USE WATER-TIGHT CONNECTORS WHEN DURING INSTALLATION
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005,2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	120VAC	277VAC
Part Number:	1032	1032-277
Primary	5.5 A	5.5 A
Secondary:	12-15VAC	12-15VAC
Protection:	2 x 25A	2 x 25A
Frequency:	60Hz	60Hz
Dimensions (IN):	12 x 12 x 6	12 x 12 x 6
Weight (LB):	26	26