

## 600 Watt Magnetic Transformer 24 VAC

Class 1



10 YEAR FREE REPLACEMENT WARRANTY

## **FEATURES**

- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 18GA STEEL, POWDER COATED NEMA 3R CASE (Indoor / Outdoor Rated)
- AVAILABLE IN 120VAC or 277VAC PRIMARY.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838

## **REQUIREMENTS**

 MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)



• MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

|                  | 120VAC          |                 | 277VAC          |
|------------------|-----------------|-----------------|-----------------|
| Part Number:     | 1102-24         | 1102-24-C***    | 1130-24         |
| Primary          | 120VAC - 5.5A   | 120VAC - 5.5A   | 277VAC - 2.5A   |
| Secondary:       | 24VAC - 25A     | 24VAC - 25A     | 24VAC - 25A     |
| Protection:      | 1 x 25A         | 1 x 25A         | 1 x 25A         |
| Frequency:       | 60 Hz           | 60 Hz           | 60 Hz           |
| Dimensions (IN): | 8.25 x 5.75 x 5 | 8.25 a 5.75 x 5 | 8.25 x 5.75 x 5 |
| Weight (LB):     | 22              | 22              | 22              |

\*\*\*Note: Sebco 1102-24-C comes standard with a 3' primary line cord