



SPECIFICATION SHEET

SEBCO VDC Direct Burial Power Supplies



FEATURES


- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- COMPRESSION MOLDED, FIBERGLASS REINFORCED POLYESTER COMPOSITE HOUSING
- RESISTANT TO RUST, CORROSION, OILS, GASOLINE, & DETERGENTS
- PRIMARY VOLTAGE RANGE FROM 100-305VAC
- WATTAGE RANGE FROM 100 - 185 WATTS. 24VDC CONSTANT VOLTAGE SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS

REQUIREMENTS



- CONFORMS TO UL 2108 / 1838
- CSA CERTIFIED C22.2#218.1:2013 ED 2 + E1
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET SYSTEM REQUIREMENTS AS LONG AS ALL PARTS ARE LISTED TO SAME ANSI/UL STANDARD

PART NUMBER	LE-100-24-TL	LE-150-24-TL	LE-185-24-TL
PRIMARY VOLTAGE	100-305VAC	100-305VAC	100-305VAC
OUTPUT VOLTAGE	24VDC / 4A	24VDC / 6.25A	24VDC / 7.8A
FREQUENCY	47—63Hz	47—63Hz	47—63Hz
WATTAGE	96 Watts	150 Watts	185 Watts
DIMENSIONS	12" x 7.5" x 5"	12" x 7.5" x 5"	12" x 7.5" x 5"
WEIGHT	4 LBS	4.5LBS	4.8LBS



WWW.SEBCOINDUSTRIES.COM

CALIFORNIA OFFICE (714) 557-1710 / TEXAS OFFICE (817) 464-0145