



## SPECIFICATION SHEET

# SEBCO VDC Direct Burial Power Supplies



### FEATURES


- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- COMPRESSION MOLDED, FIBERGLASS REINFORCED POLYESTER COMPOSITE HOUSING
- RESISTANT TO RUST, CORROSION, OILS, GASOLINE, & DETERGENTS
- PRIMARY VOLTAGE RANGE FROM 100-305VAC
- WATTAGE RANGE FROM 100- 185 WATTS. 12VDC CONSTANT VOLTAGE SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS

### REQUIREMENTS



- CONFORMS TO UL 2108 / 1838
- CSA CERTIFIED C22.2#218.1:2013 ED 2 + E1
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET SYSTEM REQUIREMENTS AS LONG AS ALL PARTS ARE LISTED TO SAME ANSI/UL STANDARD

PART NUMBER	LE-100-12-TL	LE-150-12-TL	LE-185-12-TL
PRIMARY VOLTAGE	100-240VAC	100-305VAC	100-305VAC
OUTPUT VOLTAGE	12VDC / 8.3A	12VDC / 12.5A	12VDC / 13A
FREQUENCY	47—63Hz	47—63Hz	47—63Hz
WATTAGE	100 Watts	150 Watts	156 Watts
DIMENSIONS	12" x 7.5" x 5"	12" x 7.5" x 5"	12" x 7.5" x 5"
WEIGHT	4 LBS	4.5LBS	4.8LBS



WWW.SEBCOINDUSTRIES.COM

CALIFORNIA OFFICE (714) 557-1710 / TEXAS OFFICE (817) 464-0145