


SPECIFICATION SHEET





FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- NEMA 3R OUTDOOR RATED ENCLOSURE. 12X12X4 (10X10X4 OPTION AVAILABLE)
- 16 GAUGE GALVINIZED STEEL. ANSI 61 GRAY POLYESTER POWDER PAINT FINISH
- PRIMARY VOLTAGE RANGE FROM 100-305VAC
- WATTAGE RANGE FROM 150 240 WATTS. 12VDC CONSTANT VOLTAGE SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS

REQUIREMENTS



- LISTED TO UL 379. POWER UNITS FOR FOUNTAIN, SWIMMING POOL AND SPA REQUIREMENTS
- CSA CERTIFIED C22.2#218.1:2013 ED 2 + E1
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET SYSTEM REQUIREMENTS AS LONG AS ALL PARTS ARE LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
FREQUENCY
WATTAGE
DIMENSIONS
WEIGHT

LE-150-12-PS

100-305VAC

12VDC / 12.5A

47—63Hz

150 Watts

12" x 12" x 4"

8 LBS

LE-185-12-PS

100-305VAC

12VDC / 13A

47—63Hz

156 Watts

12" x 12" x 4"

8 LBS

100-305VAC 12VDC / 16A 47—63Hz 192 Watts 12" x 12" x 4" 10 LBS

LE-240-12-PS

WWW.SEBCOINDUSTRIES.COM

CALIFORNIA OFFICE (714) 557-1710 / TEXAS OFFICE (817) 464-0145