



SPECIFICATION SHEET



SEBCO LE-12VDC-Driver

FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- Nema 3R outdoor rated enclosure
- 16, 14 OR 12 GAUGE STEEL OR PLATED SEEL ENCLOSURES
- PRIMARY VOLTAGE RANGE FROM 120-277VAC
- WATTAGE RANGE FROM 40 TO 60 WATT. 12 & 24VDC SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO UL STANDARDS 2108. CSA C22.2#9.0:1996 ED. 1+S1
- LED POWER SUPPLY UL RECOGNIZED UNDER UL8750.
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
 PRIMARY VOLTAGE
 OUTPUT VOLTAGE
 BREAKERS
 FREQUENCY
 DIMENSIONS
 WEIGHT

CLASS 1	CLASS 1
LE-12-40 (40 Watt)	LE-12-60 (60 Watt)
90-305VAC / .6A	90-305VAC / .8A
12VDC/3.34A MAX	12VDC/5A MAX
1x3.5A	1x5A
50/60 Hz	50/60 Hz
10.5" x 3.5" x 2.75"	10.5" x 35" x 2.75"
4 LBS.	6 LBS.