



SPECIFICATION SHEET



SEBCO LE-12VDC-Driver

FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- NEMA 3R OUTDOOR RATED ENCLOSURE. 12X12X4
- 16, 14 OR 12 GAUGE STEEL OR PLATED SEEL ENCLOSURES
- PRIMARY VOLTAGE RANGE FROM 120-277VAC
- WATTAGE RANGE FROM 150 TO 320 WATT. 12VDC SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO UL STANDARDS 2108. CSA C22.2#9.0:1996 ED. 1+S1
- LED POWER SUPPLY UL RECOGNIZED UNDER UL8750.
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1	CLASS 1	CLASS 1	CLASS 1
LE-12-150 (150 Watt)	LE-12-185 (156 Watt)	LE-12-240 (192 Watt)	LE-12-320 (264 Watt)
90-305VAC / 1.7A	90-305VAC / 1.8A	90-305VAC / 3A	90-305VAC / 3.5A
12VDC/12.5A MAX	12VDC/13A MAX	12VDC/16A MAX	12VDC/22A MAX
50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
12" x 12" x 4"	12" x 12" x 4"	12" x 12" x 4"	12" x 12" x 4"
8 LBS	9 LBS	9 LBS	10 LBS