



## SPECIFICATION SHEET



# SEBCO LE-24VDC-Driver

### FEATURES

- 5 YEAR FREE REPLACEMENT WARRANTY
- 0-10V DIMMING OPTION AVAILABLE. CONSULT FACTORY
- Nema 3R OUTDOOR RATED ENCLOSURE. 12X12X4
- 16, 14 OR 12 GAUGE STEEL OR PLATED SEEL ENCLOSURES
- PRIMARY VOLTAGE RANGE FROM 120-277VAC
- WATTAGE RANGE FROM 150 TO 320 WATT. 24VDC SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

### REQUIREMENTS



- LISTED TO UL STANDARDS 2108. CSA C22.2#9.0:1996 ED. 1+S1
- LED POWER SUPPLY UL RECOGNIZED UNDER UL8750.
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

**PART NUMBER**  
**PRIMARY VOLTAGE**  
**OUTPUT VOLTAGE**  
**FREQUENCY**  
**DIMENSIONS**  
**WEIGHT**

CLASS 1	CLASS 1	CLASS 1	CLASS 1
LE-24-150 (150 Watt)	LE-24-185 (185 Watt)	LE-24-240 (240 Watt)	LE-24-320 (320 Watt)
90-305VAC / 1.7A	90-305VAC / 1.8A	90-305VAC / 3A	90-305VAC / 3.5A
24VDC/6.3A MAX	24VDC/7.8A MAX	24VDC/10A MAX	24VDC/13.3A MAX
50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
12" x 12" x 4"	12" x 12" x 4"	12" x 12" x 4"	12" x 12" x 4"
8 LBS	9 LBS	9 LBS	10 LBS