



## SPECIFICATION SHEET



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- INPUT VOLTAGE OF 277 VAC. OUTPUT VOLTAGE OF 115 VAC.
- UL INSULATION SYSTEM E86543-CLASS F 155°C
- CONSERVATIVE HEAT RISE CHARACTERISTICS
- BI-DIRECTIONAL DESIGN FOR STEP-UP OR STEP-DOWN USE
- 50, 100 AND 250 WATT OPTIONS AVAILABLE

### REQUIREMENTS



- UL LISTED TRANSFORMER.
  - ANSI/UL506
  - ANSI/UL5085-1
  - ANSI/UL5085-2
- RoHS AND REACH COMPLIANT

|                   | 50 WATT              | 100 WATT            | 250 WATT              |
|-------------------|----------------------|---------------------|-----------------------|
| SEBCO PART NUMBER | MC-50                | MC-100              | MC-250                |
| UL P/N            | 4-56-0050            | 4-56-0100           | 4-56-0250             |
| PRIMARY VOLTAGE   | 277 VAC              | 277 VAC             | 277 VAC               |
| OUTPUT VOLTAGE    | 115 VAC              | 115 VAC             | 115 VAC               |
| FREQUENCY         | 50/60 Hz             | 50/60 Hz            | 50/60 Hz              |
| DIMENSIONS        | 2.30" X 2.0" X 1.98" | 2.4" x 2.25" x 2.3" | 3.50" x 3.00" x 3.25" |
| WEIGHT            | 1.5 LBS.             | 1.65 LBS            | 3.85 LBS              |