



# Stainless Steel Transformer

## 12 VAC

### Class 1

#### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- LARGE SECONDARY CONNECTION BLOCK FOR EASY WIRING
- 1/8' STAINLESS STEEL NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- MULTI-VOLT SECONDARY UP TO 15 VOLTS
- **STANDARD 6' LINE CORD ATTACHED. SINGLE GANG JUNCTION BOX CAN BE INSTALLED UPON REQUEST**
- TIMER AND PHOTOCELL READY. SOLD SEPARATELY.

#### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005, 2008, 2011, 2014)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	<b>120VAC</b>		
<b>Part Number:</b>	<b>1023-12-SS</b>	<b>1101-12-SS</b>	<b>1102-12-SS</b>
<b>Watts:</b>	150	300	600
<b>Primary</b>	1A	3A	5.5A
<b>Secondary:</b>	12-15 VAC	12-15 VAC	12-15 VAC
<b>Protection:</b>	1 x 15A	1 x 25A	2 x 25A (Dual 300 Watt)
<b>Frequency:</b>	60Hz	60 Hz	60 Hz
<b>Dimensions (IN):</b>	13 x 5-1/2 x 5-1/2	13 x 5-1/2 x 5-1/2	15 x 5-1/2 x 6
<b>Weight (LB):</b>	15	20	29