



FPSG HYBRID-PAC[®] SAFSS

SERIAL No.:	<input type="text"/>	MODEL:	<input type="text"/>
CUSTOMER PO No.:	<input type="text"/>	DATE OF MANUFACTURE:	<input type="text" value="01-03-2017"/>
RATED VOLTAGE:	<input type="text" value="120/1/60Hz"/>	MAX AMP LOAD:	<input type="text" value="60-AMPS"/>
ENCLOSURE RATING:	<input type="text" value="NEMA 1,2"/>		
OPERATING RANGE:			
TEMPERATURE:	<input type="text" value="40 F - 120F"/>	HUMIDITY:	<input type="text" value="0% - 93+-2%RH"/>
DESIGN INPUT:			
SAFETY CLASSIFICATION:	<input type="text"/>		
SEISMIC CRITERIA:	<input type="text"/>	WEIGHT:	<input type="text"/>
LOCATION OF INSTALLATION:	<input type="text"/>		
VOLUME OF PROTECTED SPACE:	<input type="text"/>		
ZONE ELEVATION ABOVE SEA LEVEL:	<input type="text"/>	DURATION OF DISCHARGE:	<input type="text"/>
EMITTER DATA:			
EMITTER QUANTITY:	<input type="text"/>	EMITTER ORIFICE:	<input type="text"/>
NITROGEN FLOW RATE:	<input type="text"/>	WATER FLOW RATE:	<input type="text"/>

1512 Kona Drive | Rancho Dominguez, CA 90220
(310) 223-3990 | www.fireandpumpservice.com

MADE IN USA
PATENT