

DISCOVER

# THE WORLD'S FIRST

CARBON NEUTRAL TIRE BRAND



## PRODUCT RANGE

CAR/CUV/SUV/LIGHT TRUCK/VAN



CO2  
NEUTRAL  
SINCE 2013

**RADAR**<sup>®</sup>  
**TIRES**

## INTRODUCTION

---

ABOUT US	01-02
SOCIAL RESPONSIBILITY	03-05
RENEGADE PROGRAM	06

## CAR/CUV/SUV

---

<b>SPORT/TOURING A/S</b> - DIMAX A/S-8 / DIMAX A/S-6 / RCX-8 / RIVERA PRO TOUR	09-12
<b>SPORT/TOURING</b> - DIMAX R8/R8+ / DIMAX e-SPORT 1/2/3 / DIMAX e-TOURING 1 RPX 800/800+ / RIVERA PRO 2	13-21

## SUV/LIGHT TRUCK

---

<b>HIGHWAY TERRAIN</b> - RIVERA GT-10 / RENEGADE H/T	23-24
<b>ALL TERRAIN</b> - RENEGADE A/T PRO / RENEGADE A/T5 / RXS-8 / RXS-9	25-28
<b>RUGGED TERRAIN</b> - RENEGADE R/T / R/T+	29-30
<b>MUD TERRAIN</b> - RENEGADE R7 M/T / RENEGADE R5 M/T	31-32

## VAN/TRAILER

---

<b>VAN</b> - ARGONITE RV-4 / ARGONITE RVX-1 / RLT-71	35-37
<b>TRAILER</b> - ANGLER ST-100 / ANGLER RST-22 / ARGONITE RV-4T	38-40

## ALL WEATHER

---

<b>4 SEASON</b> - DIMAX 4 SEASON	43
<b>4 SEASON VAN</b> - ARGONITE 4 SEASON <sup>RV-4S</sup>	44

## WINTER

---

<b>ALPINE</b> - DIMAX ALPINE / DIMAX WINTER SPORT / ARGONITE ALPINE	47-49
<b>NORDIC/NORDIC STUDD</b> - DIMAX ICE / ICE LOCK	50-51

## CLASSIC

---

<b>SPORT TOURING</b> - DIMAX CLASSIC	53
---	----

## TECHNICAL SPECIFICATIONS

---

SIZES AND SPECIFICATIONS	55-96
--------------------------	-------



*"Today as we see the world getting more conscious about climate change and its far reaching impacts, we are proud to have been on this journey since 2012 and offering customers products that are not only carbon neutral but also add value to their daily lives and give back to society. We will continue providing world-class products and keep focusing on sustainability and giving back to society."*  
**GS Sareen, Founder and CEO, Omni United.**

## ABOUT US **OUR STORY**

In 2003, G.S. Sareen founded Omni United in Singapore after successfully identifying the market opportunity for an efficient, customer-service oriented and design-driven global tire supplier, with in-house state-of-the-art design, engineering, logistics and supply chain management. Under his direction, the company grew exponentially, and by 2006 Omni United was amongst the fastest growing companies in Singapore.

In order to reach a wider audience globally, in 2006 Omni United launched its flagship brand, Radar Tires. This brand was born out of the market's need for a value product that also offered functionality, quality and aesthetics. Today Radar Tires is distributed in over 80 countries, across more than 15,000 retailers and the brand has become synonymous with accessible premium fitments for on-road and off-road applications offering more than 1400 SKUs.

## **OUR PHILOSOPHY**

Radar Tires is a design-driven brand, offering safety, performance and sustainability for all. Our mission is to make premium vehicle ownership accessible to all, by offering fitments with a unique combination of technology and sustainability, designed and engineered without compromise.

Distributed in over 80 countries, Radar tires offers a wide selection of patterns, fitments and performance attributes. This unique range of choices allows any driver, in collaboration with our skilled global dealer network, to select the perfect fitment for their

vehicle and their unique driving requirements.

As part of the Omni United group we have deep rooted values of giving back to society. Radar Tires has been an active supporter of the Breast Cancer Research Foundation since 2011. Sustainability is another key value and part of our heritage. Radar Tires has been Carbon Neutral since 2013, being ahead of the curve and playing an active role in combating climate change as well as inspiring others to do so.



DISCOVER  
**THE WORLD'S FIRST**  
CARBON NEUTRAL TIRE BRAND



SOCIAL RESPONSIBILITY  
**MOBILIZING SUSTAINABILITY**

We have always believed in proactively engaging and influencing all functions along our value chain towards sustainable management of resources. It was in 2012 when we committed to measure and offset the carbon dioxide emissions generated in the production of Radar Tires. We commissioned EY (Ernst & Young) to do an in-depth study on the impact of our production footprint on the environment. EY examined and quantified the amount of greenhouse gases (primarily carbon dioxide) produced from procuring raw materials, manufacturing, as well as energy used in the company's offices and employees' travel. Based on the study recommendations, we undertook a number of changes to our business processes and actions geared to off-set the carbon footprint, such as investing in projects ranging from reforestation to agroforestry. As a result, Radar Tires became the world's first tire brand to be 100% carbon neutral by late 2013 and to date Radar Tires remains carbon neutral.

*"We cannot transform the world alone, but we want to demonstrate that if a small company like ours can invest the time, effort and resources necessary to make a difference, then anyone can."*  
**GS Sareen, Founder and CEO, Omni United.**

SOCIAL RESPONSIBILITY  
**MOBILIZING HOPE**

Proud partner of the Breast Cancer Research Foundation since 2011. We have always believed in giving back, both to the environment and to the society and this is one of the pillars that Radar Tires has been built on. It was these beliefs that led us to partner with the Breast Cancer Research Foundation (BCRF) in 2011, the leading and highest rated breast cancer organization in the US. Together we launched "Mobilizing Hope", a corporate alliance program that

supports BCRF's global research to prevent and cure breast cancer by advancing the world's most promising research. Our support to the BCRF has not just been monetary but also heavily aimed at bringing awareness of their work into the forefront of our industry. Through this program, we continue to fund and support thousands of hours of critical life-saving research.



SPONSORSHIPS  
**RENEGADE PROGRAM**

The Renegade Program is about sharing our underdog spirit with drivers, athletes and enthusiasts across different fields. This program was launched in 2012 and it nurtures those who have world-class talent and a burning desire to achieve their ambitions but may be underrepresented in their fields. Through this program Radar Tires provides a helping hand to those who dare to push the boundaries and undertake feats that others wouldn't dare to think of.

GOLF

Radar Tires brand ambassador, British-born Jodi Ewart Shadoff is a star in the prestigious LPGA (Ladies Professional Golf Association) ranking of women golfers worldwide. She has been a professional golfer since 2010 and qualified for the LPGA Tour in 2011. She has been a brand ambassador of Radar Tires since April 2016. Jodi represents Radar Tires at all major global ladies

golf championships in the US, Europe and APAC. She has also been actively supporting the Breast Cancer Research Foundation (BCRF) with Radar Tires since 2016. Over the years Jodi has had multiple top 10 finishes and also played in the prestigious Solheim Cup in 2013, 2017 & 2019 and the UL International Crown in 2016 and 2018.

*"I am so pleased to have Omni United and Radar Tires support and sponsor me. I have always been impressed with the company's approach to making the tire world more accessible and exciting for woman drivers, for example, supporting the Breast Cancer Research Foundation since 2011 and being the first tire brand to become carbon neutral in 2013."*  
LPGA Golfer, Jodi Ewart Shadoff



**CAR/CUV/SUV**

# SPORT TOURING A/S

## DIMAX® A/S-8

The Dimax A/S-8 is a premium all-season sport touring tire that has been designed to complement and perform well on the latest high-performance cars and SUVs. The Dimax A/S-8 offers an optimal combination of traction, precise handling and exceptional mileage making it the ideal choice for drivers looking for high-performance and total assurance in all-seasons.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b> Rim: 16-26 Width: 205-315 Aspect Ratio: 30-70 Speed Rating: H, V, W, Y Load Range: SL, XL	<b>UTQG</b> 600 A A
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty Up to 60,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### GOOD TRACTION AND EVEN WEAR

- Asymmetric pattern with an optimized profile to maximize grip and wear

### EXCEPTIONAL TREAD WEAR (UTQG: 600 A A)

- Optimized silica tread compound technology coupled with a broached tread pattern ensures exceptional value for money

### ENHANCED TRACTION IN ALL WEATHER CONDITIONS

- Large number of lateral sipes offer outstanding mechanical grip in wet, slush and snow conditions

# TOURING A/S

## DIMAX® A/S-6

The Dimax A/S-6 is the new all-season touring tire that has been designed and developed especially for small to mid-sized passenger cars. This range features a state-of-the-art silica based tread compound which ensures exceptional handling in all conditions and balanced wear giving confidence and good value to the discerning customer. The large number of lateral sipes coupled with an innovative tread pattern design and the latest materials ensure outstanding mechanical grip in both dry and wet conditions making it an ideal choice for optimal all-season performance.



<b>KEY FITMENTS</b> CAR/CUV	
<b>SIZE SUMMARY</b> Rim: 15 Width: 185-215 Aspect Ratio: 55-70 Speed Rating: H, V Load Range: SL, XL	<b>UTQG</b> 600 A A
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty 50,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### OPTIMAL ALL-SEASON PERFORMANCE

- Silica based tread compound coupled with large number of lateral sipes offer outstanding mechanical grip in dry and wet conditions

### LONG LIFE (UTQG: 600 A A)

- Innovative design coupled with the best compounds ensure that the tire wears evenly and gives long life

### QUIET AND COMFORTABLE RIDE

- Optimized materials ensure good handling, a comfortable ride and low noise

## SPORT TOURING A/S

### RCX-8

The RCX-8 is an all-season sport touring tire that has been designed for high performance CUVs and SUVs that spend most of their time on-road. This range offers high mileage without compromising on safety and comfort in all-seasons with light off-road performance.



#### KEY FITMENTS CUV/SUV

##### SIZE SUMMARY

Rim: 16-20  
Width: 235-255  
Aspect Ratio: 50-70  
Speed Rating: H, V  
Load Range: SL, XL

##### UTQG

500 A A

##### MARKINGS

M+S

##### WARRANTY

Workmanship and Material Limited Warranty  
45,000 Mile Treadwear Limited Warranty  
Road Hazard Warranty

#### ENHANCED MILEAGE

- Balanced tread compound

#### QUIET DRIVING EXPERIENCE

- Optimized tread pitch sequence

#### DRIVING CONFIDENCE AT HIGH SPEEDS AND IN ALL SEASONS

- High performance tread compound combined with an innovative asymmetric pattern design

## TOURING A/S

### RIVERA® PRO TOUR

The Pro Tour is an all-season touring tire that has been designed for compact and mid-size cars. This range offers good mileage, a quiet ride and good grip in all driving conditions making it an ideal choice for drivers requiring excellent all-season capabilities and performance.



#### KEY FITMENTS CAR/CUV/SUV

##### SIZE SUMMARY

Rim: 13-17  
Width: 155-225  
Aspect Ratio: 50-80  
Speed Rating: S, H, V  
Load Range: SL

##### UTQG

520 A A

##### MARKINGS

M+S

##### WARRANTY

Workmanship and Material Limited Warranty  
50,000 Mile Treadwear Limited Warranty  
Road Hazard Warranty

#### ENHANCED TRACTION AND DRIVING CONFIDENCE

- Symmetric tread design with high sipe density

#### GOOD HYDROPLANING RESISTANCE

- Wide circumferential grooves

#### GOOD STEERING RESPONSE AND CENTER FEEL

- Wide center rib



**DIMAX® R8+**

The Dimax R8+ is the next generation sport tire range in the Radar Tires Dimax family that has been engineered for ultra-high performance passenger cars and SUV's. This range has been specifically designed to give high performance on vehicles that demand the best tires and offers the ultimate blend of excellent wet and dry grip, precise handling and comfort. This range incorporates most of the run-flat sizes for vehicles in this segment.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-26	320 A A
Width: 205-315	
Aspect Ratio: 30-55	
Speed Rating: V, W, Y	<b>MARKINGS</b>
Load Range: SL, XL, RFT	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
35,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

**PRECISE HANDLING AT HIGH SPEEDS**

- Asymmetric tread design with advanced silica formulated tread compound technology.

**SAFETY ON WET AND DRY CONDITIONS**

- Four wide longitudinal grooves that provide efficient water clearance and aquaplaning resistance.

**QUIET AND COMFORTABLE RIDE**

- Optimized tread pitch sequence for a quieter ride.

**DIMAX® R8**

The Dimax R8 is the sport tire range in the Radar Tires Dimax family. This range has been specifically designed for high performance passenger cars and offers the ideal blend of excellent wet and dry grip, precise handling and comfort. This line is available in a wide variety of fitments including key run-flat sizes for vehicles in this segment.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-20	320 A A
Width: 205-275	
Aspect Ratio: 30-60	
Speed Rating: V, W, Y	<b>MARKINGS</b>
Load Range: SL, XL, RFT	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
35,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

**PRECISE HANDLING AT HIGH SPEEDS**

- Asymmetric tread design with advanced silica formulated tread compound technology

**SAFETY ON WET AND DRY CONDITIONS**

- Four wide longitudinal grooves that provide efficient water clearance and aquaplaning resistance

**QUIET AND COMFORTABLE RIDE**

- Optimized tread pitch sequence for a quieter ride

**DIMAX® e SPORT 1**

The Dimax e-Sport 1 is the high performance range within the Dimax e-Collection from Radar Tires. This range offers a blend of high performance, increased safety, high mileage and is eco-friendly at the same time. The e-Sport 1 is engineered using a special low rolling resistance compound and light weight construction that minimizes the energy lost from heat, improving the vehicle's fuel efficiency and reducing the amount of CO2 emitted into the environment. It also features a silica based tread compound that provides added safety through shorter braking distance.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 15-18	440 A A – 440 B A
Width: 205-235	
Aspect Ratio: 50-65	
Speed Rating: V, W	<b>MARKINGS</b>
Load Range: SL, XL	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty Road Hazard Warranty 30-Day Satisfaction Guarantee*	

**PRECISE HANDLING AND STABILITY AT HIGH SPEEDS**

- Asymmetric tread pattern with a solid outside shoulder provides stability and precise handling at high speeds

**SAVE UP TO \$200 IN GAS OVER THE LIFE OF YOUR TIRE AT \$3.75 PER GALLON\***

- Lightweight construction combined with a special tread compound keeps the tire cooler, helping your engine improve fuel efficiency and reduce CO2 emissions

**STOP UP TO 8 FEET SHORTER FOR ADDED SAFETY\*\***

- Silica based tread compound provides no compromise braking, that results up to 8 feet shorter stopping distance

\*Based on rolling resistance test with Radar Dimax A/S-8, 215/60R16 size. Car's fuel consumption approx. 3.5-4 gallons/100 miles. Estimated 40,000-45,000 miles during the tire's lifetime. Fuel savings are estimates only. Actual on-road savings may vary.

\*\*Based on wet braking test with Radar Dimax A/S-8, 215/60R16 size tire from a speed of 50 mph to 0.

\*Terms & Conditions apply. For the latest warranty information please visit [www.omni-united.com/radar-us/limited-warranty](http://www.omni-united.com/radar-us/limited-warranty)

**DIMAX® e SPORT 2**

The Dimax e-Sport 2 is the high performance range within the Dimax e-Collection from Radar Tires. This range offers a blend of high performance, increased safety, high mileage and is eco-friendly at the same time. The e-Sport 2 is engineered using a special low rolling resistance compound and light weight construction that minimizes the energy lost from heat, improving the vehicle's fuel efficiency and reducing the amount of CO2 emitted into the environment. It also features a silica based tread compound that provides added safety through shorter braking distance.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-18	440 A A
Width: 215-245	
Aspect Ratio: 40-55	
Speed Rating: W, Y	<b>MARKINGS</b>
Load Range: XL	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty Road Hazard Warranty 30-Day Satisfaction Guarantee*	

**PRECISE HANDLING AND CORNERING STABILITY AT HIGH SPEEDS**

- Asymmetric tread pattern with a solid outside shoulder provides stability and precise handling at high speeds

**SAVE UP TO \$200 IN GAS OVER THE LIFE OF YOUR TIRE AT \$3.75 PER GALLON\***

- Lightweight construction combined with a special tread compound keeps the tire cooler, helping your engine improve fuel efficiency and reduce CO2 emissions

**STOP UP TO 8 FEET SHORTER FOR ADDED SAFETY\*\***

- Silica based tread compound provides no compromise braking, that results up to 8 feet shorter stopping distance

\*Based on rolling resistance test with Radar Dimax A/S-8, 215/60R16 size. Car's fuel consumption approx. 3.5-4 gallons/100 miles. Estimated 40,000-45,000 miles during the tire's lifetime. Fuel savings are estimates only. Actual on-road savings may vary.

\*\*Based on wet braking test with Radar Dimax A/S-8, 215/60R16 size tire from a speed of 50 mph to 0.

\*Terms & Conditions apply. For the latest warranty information please visit [www.omni-united.com/radar-us/limited-warranty](http://www.omni-united.com/radar-us/limited-warranty)

## DIMAX® e SPORT 3

The Dimax e-Sport 3 is the high performance range within the Dimax e-Collection from Radar Tires. This range offers a blend of high performance, increased safety, high mileage and is eco-friendly at the same time. The e Sport-3 is engineered using a special low rolling resistance compound and light weight construction that minimizes the energy lost from heat, improving the vehicle's fuel efficiency and reducing the amount of CO2 emitted into the environment. It also features a silica based tread compound that provides added safety through shorter braking distance.



KEY FITMENTS CAR/CUV/SUV	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-19	440 A A
Width: 215-235	
Aspect Ratio: 50-65	<b>MARKINGS</b>
Speed Rating: V, W	M+S
Load Range: XL	
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty Road Hazard Warranty 30-Day Satisfaction Guarantee*	

### INCREASED TRACTION

- Optimal ground contact patch provides high traction

### SAVE UP TO \$200 IN GAS OVER THE LIFE OF YOUR TIRE AT \$3.75 PER GALLON\*

- Lightweight construction combined with a special tread compound keeps the tire cooler, helping your engine improve fuel efficiency and reduce CO2 emissions

### STOP UP TO 8 FEET SHORTER FOR ADDED SAFETY\*\*

- Silica based tread compound provides no compromise braking, that results up to 8 feet shorter stopping distance

\*Based on rolling resistance test with Radar Dimax A/S-8, 215/60R16 size. Car's fuel consumption approx. 3.5-4 gallons/100 miles. Estimated 40,000-45,000 miles during the tire's lifetime. Fuel savings are estimates only. Actual on-road savings may vary.

\*\*Based on wet braking test with Radar Dimax A/S-8, 215/60R16 size tire from a speed of 50 mph to 0.

\*Terms & Conditions apply. For the latest warranty information please visit [www.omni-united.com/radar-us/limited-warranty](http://www.omni-united.com/radar-us/limited-warranty)

## DIMAX® e TOURING 1

The Dimax e-Touring 1 is the latest touring range within the Dimax e-Collection from Radar Tires. This range offers a combination of safety, stability and is eco-friendly at the same time. The e-Touring 1 is engineered for high mileage and eco-friendly performance. It utilizes a special low rolling resistance compound and light weight construction that minimizes the energy lost from heat, improving the vehicle's fuel efficiency and reducing the amount of CO2 emitted into the environment. It also features a silica based tread compound that provides added safety through shorter braking distance.



KEY FITMENTS CAR/CUV	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 15-16	440 A A – 440 B A
Width: 185-205	
Aspect Ratio: 55-65	<b>MARKINGS</b>
Speed Rating: H, V	M+S
Load Range: SL	
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 45,000 Mile Treadwear Limited Warranty Road Hazard Warranty 30-Day Satisfaction Guarantee*	

### SAVE UP TO \$200 IN GAS OVER THE LIFE OF YOUR TIRE AT \$3.75 PER GALLON\*

- Lightweight construction combined with a special tread compound keeps the tire cooler, helping your engine improve fuel efficiency and reduce CO2 emissions

### STOP UP TO 8 FEET SHORTER FOR ADDED SAFETY\*\*

- Silica based tread compound provides no compromise braking, that results up to 8 feet shorter stopping distance

### QUIETNESS FOR A MORE COMFORTABLE RIDE

- Computer optimized tread pitch sequence combined with a light weight construction for a quiet and comfortable ride.

\*Based on rolling resistance test with Radar Dimax A/S-8, 215/60R16 size. Car's fuel consumption approx. 3.5-4 gallons/100 miles. Estimated 40,000-45,000 miles during the tire's lifetime. Fuel savings are estimates only. Actual on-road savings may vary.

\*\*Based on wet braking test with Radar Dimax A/S-8, 215/60R16 size tire from a speed of 50 mph to 0.

\*Terms & Conditions apply. For the latest warranty information please visit [www.omni-united.com/radar-us/limited-warranty](http://www.omni-united.com/radar-us/limited-warranty)

# SPORT TOURING

## RPX 800+

The RPX 800+ is a sport touring tire that has been designed primarily for SUVs. This range offers drivers good control on both dry and wet roads, ensuring a comfortable driving experience. It combines real-world performance with outstanding good looks. This range incorporates the popular run-flat sizes in this segment.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 16-18	520 A A
Width: 215-265	
Aspect Ratio: 60-70	
Speed Rating: H, V, W	<b>MARKINGS</b>
Load Range: SL, XL, RFT	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
45,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

### GOOD GRIP, HANDLING AND MILEAGE

- High performance tread compound combined with an innovative asymmetric pattern design, grips the road well, offers low rolling resistance and wears evenly

### DRIVING CONFIDENCE AT HIGH SPEEDS

- Optimized construction that gives a torsionally stiffer ride, allowing for precise, confident maneuvers

### QUIET AND COMFORTABLE DRIVING EXPERIENCE

- Optimized tread pitch sequence coupled with a radially compliant construction, optimizes driver comfort and experience

# SPORT TOURING

## RPX 800

The RPX 800 is a sport touring tire that has been designed for compact and mid-size cars. This range offers drivers good control on both dry and wet roads, ensuring a comfortable driving experience. It combines real-world performance with outstanding good looks. This range incorporates the popular run-flat sizes in this segment.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 13-18	520 A A
Width: 155-245	
Aspect Ratio: 35-70	
Speed Rating: T, H, V, W, Y	<b>MARKINGS</b>
Load Range: SL, XL, RFT	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
45,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

### GOOD GRIP AND HIGH MILEAGE

- High performance tread compound along with an optimized contact patch gives good grip and even wear

### DRIVING CONFIDENCE AT HIGH SPEEDS

- Solid outer shoulder along with an optimized construction ensures precise handling at high speeds

### QUIET DRIVING EXPERIENCE

- Optimized tread pitch sequence and asymmetric tread pattern allows for a quiet and comfortable ride

**RIVERA® PRO 2**

The Rivera Pro 2 is a touring tire that has been designed for compact and mid-size cars. This range offers a combination of modern looks, good handling, durability and a quiet and comfortable ride.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b> Rim: 13-16 Width: 135-225 Aspect Ratio: 45-80 Speed Rating: T, H, V, W Load Range: SL, XL	<b>UTQG</b> 400 A A
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty 35,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

**GOOD STEERING RESPONSE**

- Tread pattern gives confidence in cornering and handling

**GOOD BALANCE OF GRIP AND MILEAGE**

- Specially formulated tread compound gives a good combination of grip and longevity

**QUIET DRIVING EXPERIENCE**

- Optimized tread pitch sequence ensures a quiet ride

**SUV/LIGHT TRUCK**

# HIGHWAY TERRAIN

## RIVERA® GT 10

The Rivera GT 10 is an all-season highway tire that has been designed for SUVs and light trucks. This robust range delivers all-season traction, safety, high mileage and a quiet ride.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b> Rim: 15-20 Width: 215-285, 10.50 Aspect Ratio: 55-85 Speed Rating: Q, S, T, H Load Range: SL, XL, C, D, E	<b>UTQG</b> 500 A A
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty 45,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### ENHANCED TRACTION AND MILEAGE IN ALL-WEATHER CONDITIONS

- Specially formulated compound

### QUIET AND COMFORTABLE RIDE

- Symmetric tread design

### GOOD HYDROPLANING RESISTANCE

- Wide circumferential grooves

# HIGHWAY TERRAIN

## RENEGADE® H/T

The Renegade H/T is a highway tire that is designed for SUVs and light trucks. This range offers drivers a unique combination of good grip on both wet and dry surfaces with high mileage and high load carrying capability. Another notable feature of this range is its quiet and comfortable ride.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b> Rim: 16-17 Width: 225-265 Aspect Ratio: 70-85 Speed Rating: S Load Range: E	<b>UTQG</b> -
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### GOOD GRIP AND LONG LIFE

- Optimized tread compound with a combination of natural and synthetic rubber reinforced with carbon black

### ENHANCED GRIP AND TRACTION IN WET AND DRY CONDITIONS

- Lateral grooves combined with multiple tread sipes add biting edges for traction

### QUIET AND COMFORTABLE RIDE

- Variable pitch design and optimized construction

## RENEGADE® A/T PRO

The Renegade A/T Pro is the brand new all-terrain range from Radar Tires that is engineered for drivers that need exceptional off-road performance while giving a quiet, smooth on-road ride. This range offers a combination of increased off-road grip and handling with excellent traction. The tires also utilize a special silica based tread compound that offers outstanding cut and chip resistance along with the all-new innovative "M-sipe", designed for Maximum grip in all conditions. Each tire features a Rattlesnake inspired dual sidewall design which allows you to customize the look of your vehicle. The "fang" side features a snake head design and fangs for added traction and the "rattle" side features a snake tail design for added protection.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-22	540 A A – 540 A B
Width: 245-305, 12.50	
Aspect Ratio: 45-75	
Speed Rating: R, S, T, H	<b>MARKINGS</b>
Load Range: SL, XL, E, F	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
50,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

### INCREASED STABILITY AND HANDLING

- Wide center block design ensures no pattern movement on-road and a smooth, quiet ride and even wear

### EXCEPTIONAL ALL-TERRAIN TRACTION AND STABILITY

- Optimized interlocking tread block design ensures the pattern works in harmony with the terrain

### OUTSTANDING CUT AND CHIP RESISTANCE

- Special silica based compound that provides cut and chip resistance and grip in all conditions

### UNIQUE STONE-EJECTOR-TECHNOLOGY

- Prevents stones from drilling and lodging in the tread

## RENEGADE® A/T5

The Renegade A/T5 is the exceptional all-terrain tire range in the Radar Tires Renegade family. This range has been designed for most SUVs and light trucks and vehicles with lift kits. The A/T5 features the innovative and unique stone-ejector-technology that prevents stones from drilling and lodging in the tread. It has been test proven against the best competitors in the toughest terrains. This makes it an ideal choice for those who like to venture off-road but need an assured ride on-road as well. All sizes have the Three Peak Mountain Snowflake symbol (3PMSF).



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 15-22	500 A A
Width: 205-325, 10.50-12.50	
Aspect Ratio: 40-85	
Speed Rating: Q, R, S, T, H, V	<b>MARKINGS</b>
Load Range: SL, XL, C, E	M+S,  3PMSF
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty	
50,000 Mile Treadwear Limited Warranty	
Road Hazard Warranty	

### ENHANCED STABILITY, HANDLING AND EVEN TREAD WEAR

- Wide center tread blocks help balance the weight distribution and ensure the tread wears evenly

### EXCEPTIONAL ALL-TERRAIN TRACTION

- Computer optimized tread block sizes and shapes with multiple lateral grooves and angled sipes ensure superb traction on all terrains

### INCREASED STABILITY AND RESISTANCE TO PUNCTURES

- Robust 3-ply construction reduces the risk of punctures and gives sure-footed handling on all surfaces

### REDUCED LODGING AND DRILLING OF STONES IN THE TREAD

- Innovative stone-ejector-technology

# ALL TERRAIN

## RXS-8

The RXS-8 is an all-season, all-terrain tire that has been specifically designed for SUVs and light trucks. This range offers versatile performance in all conditions with good handling and mileage while enhancing the looks of the vehicle.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 15-20	520 A B
Width: 215-275, 10.50	
Aspect Ratio: 55-75	<b>MARKINGS</b>
Speed Rating: Q, S, T, H	M+S
Load Range: SL, XL, C	
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty (P-Metric Sizes) Road Hazard Warranty	

### ENHANCED TREAD LIFE

- Balanced tread compound for high mileage

### GOOD STEERING RESPONSE

- Continuous center rib

### DRIVING CONFIDENCE AT HIGH SPEEDS

- Optimized carcass construction

# ALL TERRAIN

## RXS-9

The RXS-9 is an all-season, all-terrain tire range that has been specifically designed for SUVs and light trucks. This bold and rugged all-terrain range offers excellent on/off road capabilities.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 16-17	520 A B
Width: 235-265	
Aspect Ratio: 65-70	<b>MARKINGS</b>
Speed Rating: T	M+S
Load Range: SL	
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty 40,000 Mile Treadwear Limited Warranty (P-Metric Sizes) Road Hazard Warranty	

### HIGH MILEAGE AND LONGEVITY

- A combination of an exceptionally long wearing tread compound, robust construction and class-beating pattern depth ensures good mileage

### SUPERIOR CASING AND SIDEWALL PROTECTION FROM CURBING AND SIDEWALL IMPACT

- Optimized sidewall protector design extends the life of the tire by protecting the casing from curbing and other sidewall damage

### ENHANCED DURABILITY, STABILITY AND HANDLING

- Reinforced and robust construction enables confident handling at highway speeds and easy maneuverability at low speeds



# RUGGED TERRAIN

## RENEGADE® R/T

The Renegade R/T is the all-new rugged terrain range that is designed to give exceptional off-road performance coupled with on-road comfort and sophistication. On-road, this tire gives drivers superior handling with a quiet and smooth ride, while off-road it has the capability to go anywhere that a pure M/T tire can. All sizes come with a Dual Sidewall design and gives drivers a choice of either the mud-penetrating sidewall with dagger-shaped lugs or the flaming demon design with wedge-shaped lugs. These lugs offer added traction and sidewall protection.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 17-24	600 A A
Width: 265-325, 11.50-13.50	
Aspect Ratio: 45-70	
Speed Rating: Q, T	<b>MARKINGS</b>
Load Range: XL, E, F	M+S
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty Up to 45,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### EXCEPTIONAL ALL-TERRAIN TRACTION

- Computer optimized tread block sizes and shapes with multiple lateral grooves and angled sipes ensure superb traction on all terrains

### INCREASED STABILITY AND RESISTANCE TO PUNCTURES

- Robust 3-ply construction reduces the risk of punctures and gives sure-footed handling on all surfaces

### ENHANCED STABILITY, HANDLING AND EVEN TREADWEAR

- Wide center tread blocks help balance the weight distribution and ensure the tread wears evenly

### DUAL SIDEWALL DESIGN

- Featuring a flaming demon design on one side and mud-penetrating dagger-shaped lugs on the other

# RUGGED TERRAIN

## RENEGADE® R/T+

The Renegade R/T+ is the new rugged terrain tire range in the Radar Tires Renegade family. This range is designed to give exceptional off-road performance coupled with on-road comfort and sophistication. On-road, this tire gives drivers superior handling with a quiet and smooth ride, while off-road it has the capability to go anywhere that a pure MT tire can. The Renegade R/T+ offers both aggressive and rugged looks with great on/off-road performance making it a combination between an All-Terrain and Mud-Terrain tire and offers the best of both worlds. This range also features a Dual Sidewall design and gives drivers a choice of either the mud-penetrating sidewall with dagger shaped side biters or the outlaw sidewall with skull & piston and wedge shaped side biters. These side biters offer added traction and sidewall protection.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 16-24	-
Width: 245-325, 12.50-15.50	
Aspect Ratio: 50-75	
Speed Rating: Q	<b>MARKINGS</b>
Load Range: D, E, F	M+S,  3PMSF*
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty Up to 45,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

### EXCEPTIONAL ALL-TERRAIN TRACTION

- Computer optimized tread block sizes and shapes with multiple lateral grooves and angled sipes ensure superb traction on all terrains

### INCREASED STABILITY AND RESISTANCE TO PUNCTURES

- Robust 3 ply construction reduces the risk of punctures and gives sure-footed handling on all surfaces

### ENHANCED STABILITY, HANDLING AND EVEN TREADWEAR

- Wide center tread blocks help balance the weight distribution and ensure the tread wears evenly

### REDUCED LODGING AND DRILLING OF STONES IN THE TREAD

- Unique state-of-the-art stone ejector technology that prevents stones from drilling and lodging in the tread

\* = On selected sizes

# MUD TERRAIN

## RENEGADE® R7 M/T

The Renegade R7 M/T is a mud terrain tire that has been designed specifically for extreme off-road applications. This range is designed to fit SUVs and light trucks and is suitable for vehicles with lift-kits. It features a reinforced 3-ply casing for high durability and state-of-the-art Stone-Ejector-Technology which prevents stone retention and subsequent tire damage. An ideal choice for drivers who want no compromise with off-road traction and handling.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b> Rim: 16-22 Width: 235-315, 12.50-13.50 Aspect Ratio: 60-85 Speed Rating: P, Q Load Range: D, E, F	<b>UTQG</b> -
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty	

### OUTSTANDING TRACTION IN ALL CONDITIONS

- Aggressive pattern featuring a high void ratio and open shoulder design

### REDUCED LODGING AND DRILLING OF STONES IN THE TREAD

- Innovative stone-ejector-technology

### SUPERIOR OVERALL RESISTANCE TO DAMAGE

- Reinforced 3-ply casing construction

# MUD TERRAIN

## RENEGADE® R5 M/T

The Renegade R5 M/T is an extreme off-road tire that has been designed, developed and tested in some of the world's harshest off-road conditions. This range is designed for SUVs, light trucks and modified vehicles and offers drivers extreme off-road usage, good traction and durability. It is race proven in the world's toughest competitions.



<b>KEY FITMENTS</b> SUV/LIGHT TRUCK	
<b>SIZE SUMMARY</b> Rim: 15-17 Width: 235-285, 10.50-11.50 Aspect Ratio: 70-85 Speed Rating: Q, S Load Range: C, E	<b>UTQG</b> -
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty	

### HIGH RESISTANCE TO DAMAGE IN OFF-ROAD CONDITIONS

- Robust carcass and open shoulders

### GOOD TRACTION AND DURABILITY

- Specially designed "hooked" tread blocks

### PROVEN PERFORMANCE IN EXTREME OFF-ROAD CONDITIONS

- High void ratio

**VAN**

## ARGONITE® RV-4

The Argonite RV-4 is a state-of-the-art, high-mileage van tire. This range has been designed for medium to large light commercial vans. It offers excellent mileage, stability, high load carrying capability, stability, aquaplaning resistance and low noise emission. The range features robust sidewall protectors that have been designed to cope with curbing damage and protect the carcass. Available in speed ratings up to H (130mph), this range offers a good combination of value and performance.



KEY FITMENTS VAN	
SIZE SUMMARY	UTQG
Rim: 12-17	-
Width: 145-235	
Aspect Ratio: 55-75	
Speed Rating: R, S, T, H	
Load Range: SL, XL	
MARKINGS	
M+S	
WARRANTY	
Workmanship and Material Limited Warranty	

### HIGH MILEAGE AND LONGEVITY

- A combination of an exceptionally long wearing tread compound, robust construction and class-beating pattern depth ensures good mileage

### SUPERIOR CASING AND SIDEWALL PROTECTION FROM CURBING AND SIDEWALL IMPACT

- Optimized sidewall protector design extends the life of the tire by protecting the casing from curbing and other sidewall damage

### ENHANCED DURABILITY, STABILITY AND HANDLING

- Reinforced and robust construction enables confident handling at highway speeds and easy maneuverability at low speeds

## ARGONITE® RVX-1

The Argonite RVX-1 is an all-seasons light commercial tire. This range is designed for medium to large vans and light commercial vehicles. It offers the ideal blend of good wet and dry performance, mileage and safety with high load carrying capacity.



KEY FITMENTS VAN	
SIZE SUMMARY	UTQG
Rim: 14-16	-
Width: 185-235	
Aspect Ratio: 65-70	
Speed Rating: R	
Load Range: D, E	
MARKINGS	
M+S	
WARRANTY	
Workmanship and Material Limited Warranty	

### GOOD MILEAGE AND HIGH FUEL EFFICIENCY

- Specially formulated tread compound

### INCREASED WET TRACTION AND BRAKING

- Lateral grooves

### HIGHER LOAD CARRYING CAPACITY AND DURABILITY

- Strong casing

**RLT 71**

The RLT-71 is a premium, all-season light commercial tire. This range is specifically designed for small to medium vans and light commercial vehicles. It offers good wet and dry performance, mileage and safety with high load carrying capacity which makes it the ideal choice for this application.



KEY FITMENTS VAN	
<b>SIZE SUMMARY</b> Rim: 12-16 Width: 165-225 Aspect Ratio: 70-80 Speed Rating: Q, R, S Load Range: D	<b>UTQG</b> -
<b>MARKINGS</b> M+S	
WARRANTY	
Workmanship and Material Limited Warranty	

**HIGHER LOAD CARRYING CAPACITY AND DURABILITY**

- Strong casing manufactured with high density polyester plies

**GOOD MILEAGE AND HIGH FUEL EFFICIENCY**

- Specially formulated tread compound that wears evenly and provides lower rolling resistance

**INCREASED WET TRACTION AND BRAKING**

- Lateral grooves that provide efficient water evacuation and aquaplaning resistance

**ANGLER® ST-100**

The Angler ST-100 is a special purpose trailer tire developed specifically for use on travel trailers, pop-up campers, boat trailers, toy haulers and fifth wheels. This range features a rounded profile which helps improve ride quality. Its symmetric tread design with closely spaced ribs provides increased contact patch for straight tracking and highway stability. The construction of the ST-100 features twin steel belts with a nylon overlay and polyester body-ply which provides stability, puncture resistance and durability. The range also utilizes a special compound that offers increased mileage and fuel efficiency.



KEY FITMENTS TRAILER	
<b>SIZE SUMMARY</b> Rim: 13-16 Width: 175-235 Aspect Ratio: 75-85 Speed Rating: M Load Range: C, D, E	<b>UTQG</b> -
<b>MARKINGS</b> -	
WARRANTY	
Workmanship and Material Limited Warranty Road Hazard Warranty	

**HIGH LOAD CARRYING CAPABILITY, STABILITY AND PUNCTURE RESISTANCE**

- Twin steel belts provide increased strength for carrying heavy loads, offers stability and puncture resistance

**LONG-LIFE AND IMPROVED FUEL ECONOMY**

- Special tread compound that provides low rolling resistance and a long tread life.

**HIGH STABILITY AND DURABILITY**

- Use of full nylon overlay in all sizes provides improved stability and durability.

**ANGLER® RST-22**

The Angler RST-22 is a trailer tire that is designed for travel trailers, boat trailers, pop-up campers and all high-load carrying trailers including utility. This range offers increased traction, strength and high load carrying capacity with greater control.



KEY FITMENTS TRAILER	
<b>SIZE SUMMARY</b> Rim: 13-16 Width: 175-235 Aspect Ratio: 75-85 Speed Rating: L Load Range: C, D, E, F	<b>UTQG</b> -  <b>MARKINGS</b> -
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

**INCREASED TRACTION**

- Open tread shoulders

**HIGH LOAD CARRYING CAPACITY**

- Robust casing developed to carry heavy loads

**KEY TRAILER FITMENTS**

- 13" to 16" rim diameters

**ARGONITE® RV-4T**

The Argonite RV-4T is a modern range of trailer tires that are perfect for non-driven wheels such as those of low-loaders, caravans, livestock and delivery trailers. This range has been specifically designed, developed and tested for trailers and every size carries the FRT (Free Rolling tire) designation. Most sizes are dual load rated as well.



KEY FITMENTS TRAILER	
<b>SIZE SUMMARY</b> Rim: 12-15 Width: 155-225 Aspect Ratio: 50-70 Speed Rating: N, R Load Range: C, D, E, F	<b>UTQG</b> -  <b>MARKINGS</b> -
<b>WARRANTY</b> Workmanship and Material Limited Warranty	

**EXCELLENT LOAD CARRYING CAPACITY ON SINGLE, DOUBLE AND MULTIPLE AXLE TRAILERS**

- Reinforced construction and optimized inflated shape ensures loads are carried evenly across the footprint

**GREAT DIRECTIONAL STABILITY AND AQUA PLANNING RESISTANCE**

- Sinusoidal pattern with wide circumferential grooves and lateral open shoulder grooves give directional stability and efficient water clearance

**INCREASED PROTECTION AGAINST DAMAGE AND CURBING**

- Optimized sidewall protector design extends the life of the tire by protecting the casing from curbing and other sidewall damages

**ALL WEATHER**

## 4 SEASON

### **DIMAX<sup>®</sup> 4 SEASON**

The Dimax 4 Season is the new and innovative all-weather tire range designed for drivers living in urban areas, who need a versatile mobility solution all year round. It offers exceptional grip in winter as well as in summer conditions. All sizes have the Three Peak Mountain Snowflake symbol (3PMSF) and are officially approved for winter use.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b> Rim: 14-21 Width: 155-295 Aspect Ratio: 35-70 Speed Rating: H, V, W, Y Load Range: SL, XL, RFT	<b>UTQG</b> 360 A A
<b>MARKINGS</b> M+S,  3PMSF	
<b>WARRANTY</b> Workmanship and Material Limited Warranty 35,000 Mile Treadwear Limited Warranty Road Hazard Warranty	

#### SAFETY IN EVERY WEATHER CONDITION

- Dual compound technology that keeps the tire flexible in both hot summer weather and cold winter temperatures.

#### UNIQUE TREAD PATTERN FOR PERFORMANCE

- Asymmetric tread pattern with four circumferential grooves provides aquaplaning resistance on wet roads and high density sipes provide exceptional grip on wet, slush and snow.

#### QUIET RIDE

- Optimized casing profile and pitch sequence ensure a quieter ride.

## 4 SEASON VAN

### **ARGONITE<sup>®</sup> 4 SEASON (RV-4S)**

The Argonite 4 Season (RV-4S) is an all-weather van tire designed for year-round use. Developed and engineered for light commercial vehicles, this tire is the ideal choice for drivers seeking excellent handling, high mileage, high load carrying capability, low rolling resistance and great performance in all weather conditions. All sizes have the Three Peak Mountain Snowflake symbol (3PMSF) and are officially approved for winter use. Available in a variety of fitments for small, medium and large vans.



<b>KEY FITMENTS</b> VAN	
<b>SIZE SUMMARY</b> Rim: 15-17 Width: 195-235 Aspect Ratio: 55-75 Speed Rating: R, S, T, H Load Range: SL	<b>UTQG</b> -
<b>MARKINGS</b> M+S,  3PMSF	
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

#### SAFETY IN ALL WEATHER CONDITIONS

- Symmetric tread pattern with three circumferential grooves provides aquaplaning resistance on wet roads and high density sipes provide exceptional grip on wet, slush and snow.

#### OPTIMAL TRACTION IN ALL SEASONS

- Unique dual compound technology that keeps the tire flexible in both hot summer weather and cold winter temperatures.

#### REINFORCED FOR ROBUSTNESS

- Reinforced construction using the latest materials and techniques provides stability and high load carrying capability.



# WINTER

# ALPINE

## DIMAX® ALPINE

The Dimax Alpine is the all new winter range that has been designed and developed to meet the needs of the European winter driver. This range offers safety and excellent performance in Alpine winter conditions. The sizes fit popular passenger cars, CUVs and SUVs.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 15-20	-
Width: 185-275	
Aspect Ratio: 35-65	
Speed Rating: T, H, V	<b>MARKINGS</b>
Load Range: SL, XL	M+S,  3PMSF
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty Road Hazard Warranty	

### EXCELLENT STEERING AND HANDLING PERFORMANCE IN WET, SLUSH AND SNOW

- High density of zig-zag sipes help increase the grip on snow and slush which provides excellent steering and handling performance. Optimized tread compound with advanced synthetic polymers and silica ensure that the rubber stays grippy in wet and cold weather conditions.

### PREVENTS SLUSH-PLANING AND AQUA-PLANING

- Directional tread design offers improved self-cleaning action on wet and slushy roads, as well as optimizing gripping edges on snowy roads.

### SHORTER BRAKING DISTANCE

- Optimized pattern design featuring more gripping edges providing increased grip on snow and ice for a shorter braking distance.

# ALPINE

## DIMAX® WINTER SPORT

The Dimax Winter Sport is an Alpine winter tire range designed for modern high-end premium vehicles. This range has been designed to achieve maximum safety, control and performance in all winter weather conditions.



<b>KEY FITMENTS</b> CAR/CUV/SUV/RUN-FLAT	
<b>SIZE SUMMARY</b>	<b>UTQG</b>
Rim: 14-21	360 A A
Width: 195-255	
Aspect Ratio: 35-70	
Speed Rating: H, V	<b>MARKINGS</b>
Load Range: SL, XL, RFT	M+S,  3PMSF
<b>WARRANTY</b>	
Workmanship and Material Limited Warranty Road Hazard Warranty	

### SAFETY IN ALL WINTER CONDITIONS

- Advanced Silica filled winter tread compound that keeps the tire flexible even in freezing conditions allowing the tread to grip better in wet, slush and snow.

### CONTROL AND DRIVING PRECISION

- A combination of high density sipes and lateral grooves provides efficient water clearance and hydroplaning resistance in cold weather conditions.

### MAXIMUM DRIVING COMFORT

- Optimized casing profile and computer optimized pitch sequence ensures a quiet and comfortable ride.

# ALPINE VAN

## ARGONITE® ALPINE

The Argonite Alpine has been designed for light commercial applications. This range provides drivers improved performance in all winter conditions and optimizes stability, high load carrying capability and durability.



KEY FITMENTS VAN	
<b>SIZE SUMMARY</b> Rim: 16-17 Width: 185-235 Aspect Ratio: 55-75 Speed Rating: R, T Load Range: SL	<b>UTQG</b> -
<b>MARKINGS</b> M+S,  3PMSF	
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

### SAFETY IN ALL WINTER CONDITIONS

- High density of zig-zag sipes help increase the grip on snow and slush which provides excellent steering and handling performance. Optimized tread compound with advanced synthetic polymers and silica ensure that the rubber stays grippy in wet and cold weather conditions.

### TOTAL CONTROL AND STABLE HANDLING

- Optimized pattern and construction results in a contact patch that has been optimized to ensure predictable cornering and handling.

### HIGH LOAD CARRYING CAPABILITY

- Reinforced casing and robust steel belts ensure that the vehicle will be stable whilst under heavy and light loads.

# NORDIC

## DIMAX® ICE

The Dimax Ice is specifically designed for those who drive in extreme winter Nordic conditions and features a unique super soft compound that stays grippy even in extremely cold temperatures. This stud-less range provides increased safety, control and enhanced traction on ice and hard packed snow making it the ideal choice for extreme winter use.



KEY FITMENTS CAR/CUV/SUV	
<b>SIZE SUMMARY</b> Rim: 15-19 Width: 195-235 Aspect Ratio: 35-65 Speed Rating: T Load Range: XL	<b>UTQG</b> -
<b>MARKINGS</b> M+S,  3PMSF	
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

### SAFETY AND CONTROL IN ALL WINTER CONDITIONS

- Special super soft compound that remains flexible even in extremely cold temperatures combined with a high density of zig-zag sipes allowing for better traction and braking safety.

### ENHANCED GRIP ON ICE

- A high density of zig-zag sipes provide more biting edges for increased mechanical grip on ice.

### EXTRA GRIP ON HARD-PACKED SNOW

- Directional self-cleaning tread design coupled with thousands of additional gripping edges provides exceptional grip on hard-packed snow.

# NORDIC STUDDED

## **DIMAX<sup>®</sup> ICE LOCK**

The Dimax Ice Lock is the new generation of studded tires that are specifically designed to increase performance and provide safety and control in harsh winter Nordic conditions. This range features a unique super soft tread compound that has been formulated to stay soft and grippy in harsh Nordic weather conditions. These tires also feature special factory fitted Tikka Spike studs that offer increased mechanical grip and enhanced braking on ice and hard packed snow.



<b>KEY FITMENTS</b> CAR/CUV/SUV	
<b>SIZE SUMMARY</b> Rim: 15-19 Width: 195-235 Aspect Ratio: 35-65 Speed Rating: T Load Range: XL	<b>UTQG</b> -  <b>MARKINGS</b> M+S,  3PMSF
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

### **SAFETY AND CONTROL IN ALL WINTER CONDITIONS**

- Special super soft compound that remains flexible even in extreme Nordic temperatures combined with high density of zig-zag sipes allows for better traction and braking safety.

### **ENHANCED GRIP ON ICE**

- High density of zig-zag sipes provide more biting edges for increased mechanical grip on ice.

### **EXTRA GRIP ON HARD-PACKED SNOW**

- Directional self-cleaning tread design coupled with sipes and studs provides exceptional grip on hard-packed snow.

### **ENHANCED TRACTION AND GRIP ON HARD PACKED ICE**

- Factory fitted with high-end Tikka Spike studs enhance traction, grip and braking on hard packed ice and snow.

# CLASSIC

## Dimax® Classic

The Dimax Classic is a Touring tire specially designed and developed for classic cars. This range offers a combination of classic looks yet state-of-the-art pattern technology and the latest in materials sophistication that ensures the tire delivers exceptional handling, durability and comfort, while completely complimenting and adding to the overall aesthetic of your classic/vintage vehicle. Available in either a retro white sidewall or a sophisticated black sidewall finish.



KEY FITMENTS CAR	
<b>SIZE SUMMARY</b> Rim: 12-16 Width: 125-255 Aspect Ratio: 50-70 Speed Rating: S, T, H, V, W Load Range: SL	<b>UTQG</b> -
	<b>MARKINGS</b> M+S
<b>WARRANTY</b> Workmanship and Material Limited Warranty Road Hazard Warranty	

### HIGH MILEAGE

- Specially formulated tread compound

### DELIVERS SHORTER BRAKING DISTANCE

- Sport touring tread pattern

### CLASSIC AESTHETICS FOR CLASSIC/VINTAGE VEHICLES

- Vintage tread and sidewall design available in either black or retro white sidewall finish

# CAR/CUV/SUV

## SPORT/TOURING A/S



DIMAX A/S-8



DIMAX A/S-6



RCX-8



RIVERA PRO TOUR

## SPORT/TOURING



DIMAX R8+



DIMAX R8



DIMAX E-SPORT 1



DIMAX E-SPORT 2



DIMAX E-SPORT 3



DIMAX E-TOURING 1



RPX 800+



RPX 800



RIVERA PRO 2

# CAR/CUV/SUV

SIZE	LI/SR.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>DIMAX A/S-8</b>								
SPORT TOURING A/S								
<b>Ø 26</b>								
295/30R26	107W	XL	10.0-(10.5)-11.0	33.0	11.9	10.1	600 A A	
305/30R26	109W	XL	10.5-(11.0)-11.5	33.2	12.3	10.1	600 A A	
<b>Ø 24</b>								
285/40R24	112V	XL	9.5-(10.0)-11.0	33.0	11.4	10.5	600 A A	
295/35R24	110V	XL	10.0-(10.5)-11.5	32.1	11.9	10.1	600 A A	
305/35R24	112V	XL	10.0-(11.0)-12.0	32.4	12.3	10.1	600 A A	
<b>Ø 22</b>								
235/30R22	90Y	XL	(8.0)	27.6	9.5	10.1	600 A A	
245/30R22	92W	XL	8.0-(8.5)-9.0	27.8	9.8	10.1	600 A A	
255/30R22	95W	XL	8.5-(9.0)-9.5	28.1	10.2	10.1	600 A A	
265/35R22	102V	XL	9.0-(9.5)-10.5	29.3	10.7	10.1	600 A A	
265/40R22	106W	XL	9.0-(9.5)-10.5	30.4	10.7	10.1	600 A A	
275/50R22	111H	-	7.5-(8.5)-9.5	32.9	11.2	10.5	600 A A	
285/40R22	110V	XL	9.5-(10.0)-11.0	31.0	11.4	10.5	600 A A	
285/45R22	114W	XL	9.0-(9.5)-10.5	32.1	11.2	10.5	600 A A	
295/25R22	97Y	XL	10.0-(10.5)-11.0	27.8	11.9	10.1	600 A A	
305/40R22	114W	XL	10.0-(11.0)-12.0	31.6	12.3	10.1	600 A A	
305/45R22	118V	XL	9.5-(10.0)-11.5	32.8	11.9	10.1	600 A A	
<b>Ø 20</b>								
235/55R20	105W	XL	6.5-(7.5)-8.5	30.2	9.6	10.1	600 A A	
245/35R20	95W	XL	8.0-(8.5)-9.5	26.8	9.8	10.1	600 A A	
245/40R20	99W	XL	8.0-(8.5)-9.5	27.7	9.8	10.1	600 A A	
245/45R20	103W	XL	7.5-(8.0)-9.0	28.7	9.6	10.1	600 A A	
245/50R20	102V	-	7.0-(7.5)-8.5	29.7	10.0	10.1	600 A A	
255/40R20	101W	XL	8.5-(9.0)-10.0	28.0	10.2	10.1	600 A A	
255/45R20	105W	XL	8.0-(8.5)-9.5	29.1	10.0	10.1	600 A A	
255/50R20	109W	XL	7.0-(8.0)-9.0	30.1	10.4	10.1	600 A A	
255/55R20	110W	XL	7.0-(8.0)-9.0	31.0	10.4	10.1	600 A A	
265/45R20	108W	XL	8.5-(9.0)-10.0	29.4	10.5	10.1	600 A A	
265/50R20	111V	XL	7.5-(8.5)-9.5	30.5	10.9	10.1	600 A A	
265/50R20	111W	XL	7.5-(8.5)-9.5	30.5	10.9	10.1	600 A A	
275/35R20	102W	XL	9.0-(9.5)-11.0	27.6	10.9	10.1	600 A A	
275/40R20	106W	XL	9.0-(9.5)-11.0	28.7	10.9	10.1	600 A A	
275/45R20	110W	XL	8.5-(9.0)-10.5	29.8	10.9	10.5	600 A A	
275/50R20	113W	XL	7.5-(8.5)-9.5	30.9	11.2	10.5	600 A A	
275/55R20	117V	XL	7.5-(8.5)-9.5	31.9	11.2	10.5	600 A A	
275/60R20	115V	-	7.5-(8.0)-9.5	33.0	11.0	10.5	600 A A	
285/50R20	116V	XL	8.0-(9.0)-10.0	31.3	11.7	10.5	600 A A	
295/35R20	105W	XL	10.0-(10.5)-11.5	28.1	11.9	10.5	600 A A	
295/40R20	110Y	XL	10.0-(10.5)-11.5	29.3	11.9	10.5	600 A A	
295/45R20	114W	XL	9.5-(10.0)-11.0	30.5	11.7	10.1	600 A A	
315/35R20	110Y	XL	10.5-(11.0)-12.5	28.7	12.6	10.5	600 A A	
<b>Ø 19</b>								
225/55R19	103V	XL	6.0-(7.0)-8.0	28.8	9.2	10.1	600 A A	
235/35R19	91Y	XL	8.0-(8.5)-9.5	25.5	9.5	10.1	600 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX A/S-8 (CONT.)**

SPORT TOURING A/S

Ø 19								
235/40R19	96W	XL	8.0-(8.5)-9.5	26.4	9.5	10.1	600 A A	
235/45R19	99W	XL	7.5-(8.0)-9.0	27.4	9.3	10.1	600 A A	
235/50R19	103W	XL	6.5-(7.5)-8.5	28.3	9.6	10.1	600 A A	
235/55R19	105V	XL	6.5-(7.5)-8.5	29.2	9.6	10.1	600 A A	
245/35R19	93Y	XL	8.0-(8.5)-9.5	25.8	9.9	10.1	600 A A	
245/40R19	98W	XL	8.0-(8.5)-9.5	26.7	9.8	10.1	600 A A	
245/45R19	102W	XL	7.5-(8.0)-9.0	27.7	9.6	10.1	600 A A	
245/55R19	107V	XL	7.0-(7.5)-8.5	29.6	10.0	10.1	600 A A	
255/40R19	100W	XL	8.5-(9.0)-10.0	27.0	10.2	10.1	600 A A	
255/45R19	104W	XL	8.0-(8.5)-9.5	28.1	10.0	10.1	600 A A	
255/50R19	107W	XL	7.0-(8.0)-9.0	29.0	10.3	10.1	600 A A	
255/55R19	111W	XL	7.0-(8.0)-9.0	30.0	10.3	10.1	600 A A	
255/60R19	113V	XL	7.0-(7.5)-9.0	31.0	10.2	10.1	600 A A	
265/30R19	93Y	XL	9.0-(9.5)-10.0	25.3	10.6	10.1	600 A A	
265/50R19	110W	XL	7.5-(8.5)-9.5	29.4	10.6	10.1	600 A A	
275/30R19	96Y	XL	9.0-(9.5)-10.0	25.5	11.0	10.1	600 A A	
275/35R19	100W	XL	9.0-(9.5)-11.0	26.6	10.9	10.1	600 A A	
275/55R19	111W	-	7.5-(8.5)-9.5	30.9	11.0	10.1	600 A A	
285/40R19	103W	-	9.5-(10.0)-11.0	28.0	11.4	10.5	600 A A	

Ø 18								
215/55R18	99V	XL	6.0-(7.0)-7.5	27.3	8.9	10.1	600 A A	
225/40R18	92W	XL	7.5-(8.0)-9.0	25.1	9.1	10.1	600 A A	
225/45R18	95W	XL	7.0-(7.5)-8.5	25.9	8.9	10.1	600 A A	
225/50R18	99W	XL	6.0-(7.0)-8.0	26.9	9.2	10.1	600 A A	
225/55R18	102V	XL	6.0-(7.0)-8.0	27.8	9.2	10.1	600 A A	
225/60R18	104W	XL	6.0-(6.5)-8.0	28.6	9.0	10.1	600 A A	
235/45R18	98W	XL	7.5-(8.0)-9.0	26.3	9.3	10.1	600 A A	
235/50R18	101V	XL	6.5-(7.5)-8.5	27.3	9.6	10.1	600 A A	
235/55R18	104V	XL	6.5-(7.5)-8.5	28.1	9.6	10.1	600 A A	
235/60R18	107V	XL	6.5-(7.0)-8.5	29.1	9.4	10.1	600 A A	
235/65R18	110W	XL	6.5-(7.0)-8.5	30.0	9.4	10.1	600 A A	
245/40R18	97W	XL	8.0-(8.5)-9.5	25.7	9.8	10.1	600 A A	
245/45R18	100W	XL	7.5-(8.0)-9.0	26.7	9.6	10.1	600 A A	
245/60R18	105V	-	(7.0)-8.5	29.6	9.8	10.1	600 A A	
255/55R18	109W	XL	7.0-(8.0)-9.0	29.0	10.4	10.1	600 A A	
255/60R18	112W	XL	7.0-(7.5)-9.0	30.0	10.2	10.1	600 A A	
255/65R18	115H	XL	7.0-(7.5)-9.0	31.1	10.2	10.1	600 A A	
265/60R18	114V	XL	7.5-(8.0)-9.5	30.5	10.7	10.1	600 A A	
275/65R18	116H	-	7.5-(8.0)-9.5	32.1	11.0	10.1	600 A A	

Ø 17								
205/50R17	93W	XL	5.5-(6.5)-7.5	25.1	8.4	10.1	600 A A	
215/45R17	91W	XL	(7.0)-8.0	24.6	8.4	10.1	600 A A	
215/50R17	95W	XL	6.0-(7.0)-7.5	25.5	8.9	10.1	600 A A	
215/55R17	94V	-	6.0-(7.0)-7.5	26.3	8.9	10.1	600 A A	
215/60R17	100H	XL	6.0-(6.5)-7.5	27.2	8.7	10.7	600 A A	
215/65R17	103H	XL	6.0-(6.5)-7.5	28.0	8.7	10.7	600 A A	
225/45R17	94W	XL	7.0-(7.5)-8.5	25.0	8.9	10.1	600 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX A/S-8 (CONT.)**

SPORT TOURING A/S

Ø 17								
225/50R17	98W	XL	6.0-(7.0)-8.0	25.9	9.2	10.1	600 A A	
225/55R17	101V	XL	6.0-(7.0)-8.0	26.8	9.2	10.1	600 A A	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	10.7	600 A A	
225/65R17	106V	XL	6.0-(6.5)-8.0	28.5	9.0	10.7	600 A A	
235/45R17	97W	XL	7.5-(8.0)-9.0	25.4	9.3	10.1	600 A A	
235/55R17	103V	XL	6.5-(7.5)-8.5	27.2	9.6	10.1	600 A A	
235/60R17	102V	-	6.5-(7.0)-8.5	28.1	9.4	10.7	600 A A	
235/65R17	108V	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	600 A A	
245/40R17	95Y	XL	8.0-(8.5)-9.5	24.7	9.8	10.7	600 A A	
245/45R17	99W	XL	7.5-(8.0)-9.0	25.7	9.8	10.1	600 A A	
245/65R17	111H	XL	(7.0)-8.5	29.5	9.8	10.1	600 A A	
255/65R17	110H	-	7.0-(7.5)-9.0	30.1	10.2	10.1	600 A A	
265/65R17	112H	-	7.5-(8.0)-9.5	30.6	10.7	10.1	600 A A	
265/65R17	116V	XL	7.5-(8.0)-9.5	30.6	10.7	10.1	600 A A	

Ø 16								
205/55R16	91V	-	5.5-(6.5)-7.5	24.9	8.4	10.7	600 A A	
205/60R16	92V	-	5.5-(6.0)-7.5	25.7	8.2	10.7	600 A A	
205/65R16	95V	-	5.5-(6.0)-7.5	26.5	8.2	10.7	600 A A	
215/55R16	93V	-	6.0-(7.0)-7.5	25.3	8.9	10.7	600 A A	
215/60R16	95V	-	6.0-(6.5)-7.5	26.1	8.7	10.7	600 A A	
215/65R16	98V	-	6.0-(6.5)-7.5	27.0	8.7	10.7	600 A A	
215/70R16	104V	XL	5.5-(6.5)-7.0	27.9	8.7	10.7	600 A A	
225/55R16	95V	-	6.0-(7.0)-8.0	25.7	9.2	10.7	600 A A	
225/60R16	102V	XL	6.0-(6.5)-8.0	26.6	9.0	10.7	600 A A	
225/65R16	100H	-	6.0-(6.5)-8.0	27.5	9.0	10.7	600 A A	
225/70R16	107H	XL	6.0-(6.5)-7.5	28.4	9.1	10.7	600 A A	
235/60R16	100V	-	6.5-(7.0)-8.5	27.1	9.4	10.7	600 A A	
235/65R16	103H	-	6.5-(7.0)-8.5	28.0	9.4	10.7	600 A A	
235/70R16	106H	-	6.0-(7.0)-8.0	29.0	9.4	10.7	600 A A	

**DIMAX A/S-6**

TOURING A/S

Ø 15								
185/60R15	88H	XL	5.0-(5.5)-6.5	23.7	7.4	9.8	600 A A	
185/65R15	88H	-	5.0-(5.5)-6.5	24.4	7.4	9.8	600 A A	
185/65R15	92V	XL	5.0-(5.5)-6.5	24.4	7.4	9.8	600 A A	
195/55R15	89V	XL	5.5-(6.0)-7.0	23.4	7.9	10.1	600 A A	
195/60R15	88H	-	5.5-(6.0)-7.0	24.2	7.9	10.1	600 A A	
195/60R15	92V	XL	5.5-(6.0)-7.0	24.2	7.9	10.1	600 A A	
195/65R15	91H	-	5.5-(6.0)-7.0	25.0	7.9	10.1	600 A A	
195/65R15	95V	XL	5.5-(6.0)-7.0	25.0	7.9	10.1	600 A A	
205/60R15	91H	-	5.5-(6.0)-7.5	24.7	8.2	10.1	600 A A	
205/60R15	95V	XL	5.5-(6.0)-7.5	24.7	8.2	10.1	600 A A	
205/65R15	94H	-	5.5-(6.0)-7.5	25.5	8.2	10.1	600 A A	
205/65R15	99V	XL	5.5-(6.0)-7.5	25.5	8.2	10.1	600 A A	
205/70R15	100H	XL	5.0-(6.0)-7.0	26.3	8.2	10.1	600 A A	
215/70R15	98H	-	5.5-(6.5)-7.0	26.9	8.7	10.5	600 A A	

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

**RCX-8** SPORT TOURING A/S

Ø 20								
245/50R20	102V	-	7.0-(7.5)-8.5	29.7	10.0	11.3	500 A A	

Ø 18								
235/55R18	104H	XL	6.5-(7.5)-8.5	28.1	9.6	11.3	500 A A	
235/60R18	107V	XL	6.5-(7.0)-8.5	29.1	9.4	11.3	500 A A	
245/60R18	105V	-	(7.0)-8.5	29.6	9.8	11.3	500 A A	
255/55R18	109V	XL	7.0-(8.0)-9.0	29.0	10.4	11.3	500 A A	
255/65R18	109H	-	7.0-(7.5)-9.0	31.1	10.2	11.3	500 A A	

Ø 17								
235/60R17	102H	-	6.5-(7.0)-8.5	28.1	9.4	11.3	500 A A	

Ø 16								
235/70R16	106H	-	6.0-(7.0)-8.0	29.0	9.4	12.6	500 A A	

**RIVERA PRO TOUR** TOURING A/S

Ø 17								
215/55R17	94V	-	6.0-(7.0)-7.5	26.3	8.7	10.0	520 A A	
225/50R17	94V	-	6.0-(7.0)-8.0	25.9	9.1	10.0	520 A A	

Ø 16								
205/55R16	91H	-	5.5-(6.5)-7.5	24.9	8.3	10.0	520 A A	
205/60R16	92H	-	5.5-(6.0)-7.5	25.7	8.3	10.0	520 A A	
215/60R16	95V	-	6.0-(6.5)-7.5	26.2	8.7	10.0	520 A A	
225/60R16	97S	-	6.0-(6.5)-8.0	26.6	9.1	10.0	520 A A	

Ø 15								
195/60R15	88H	-	5.5-(6.0)-7.0	24.2	7.9	10.0	520 A A	
195/65R15	91V	-	5.5-(6.0)-7.0	25.0	7.9	10.0	520 A A	
205/65R15	92S	-	5.5-(6.0)-7.5	25.5	8.3	10.0	520 A A	
205/70R15	95S	-	5.0-(6.0)-7.0	26.3	8.3	10.0	520 A A	
215/65R15	95S	-	6.0-(6.5)-7.5	26.0	8.7	10.0	520 A A	
215/70R15	97S	-	5.5-(6.5)-7.0	26.9	8.7	10.0	520 A A	

Ø 14								
175/65R14	81S	-	(5.0)-6.0	23.0	7.1	10.0	520 A A	
185/65R14	85S	-	5.0-(5.5)-6.5	23.5	7.5	10.0	520 A A	
185/70R14	87S	-	4.5-(5.5)-6.0	24.3	7.5	10.0	520 A A	
185/75R14	89S	-	4.5-(5.0)-6.0	25.0	7.5	10.0	520 A A	
195/70R14	90S	-	5.0-(6.0)-6.5	24.8	7.9	10.0	520 A A	
195/75R14	92S	-	5.0-(5.5)-6.5	25.5	7.7	10.0	520 A A	
205/70R14	93S	-	5.0-(6.0)-7.0	25.3	8.3	10.0	520 A A	
205/75R14	95S	-	5.0-(5.5)-7.0	26.1	8.3	10.0	520 A A	
215/70R14	96S	-	5.5-(6.5)-7.0	25.9	8.7	10.0	520 A A	

Ø 13								
155/80R13	79S	-	4.0-(4.5)-5.0	22.8	6.3	10.0	520 A A	
175/70R13	82S	-	4.5-(5.0)-6.0	22.7	7.1	10.0	520 A A	

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX R8+ | RUN-FLAT** SPORT

Ø 22								
275/40RF22	108Y	XL, RFT	9.0-(9.5)-11.0	30.7	10.9	10.5	320 A A	

Ø 21								
245/35RF21	96Y	XL, RFT	8.0-(8.5)-9.5	27.7	9.8	10.5	320 A A	
265/40RF21	105Y	XL, RFT	9.0-(9.5)-10.5	29.3	10.7	10.1	320 A A	
275/30RF21	98Y	XL, RFT	9.0-(9.5)-10.0	27.5	10.9	10.5	320 A A	
275/40RF21	107Y	XL, RFT	9.0-(9.5)-11.0	29.6	10.9	10.5	320 A A	
285/35RF21	105Y	XL, RFT	9.5-(10.0)-11.0	28.9	11.4	10.5	320 A A	

Ø 20								
245/35RF20	95Y	XL, RFT	8.0-(8.5)-9.5	26.8	9.8	10.1	320 A A	
245/40RF20	99Y	XL, RFT	8.0-(8.5)-9.5	27.7	9.8	10.1	320 A A	
245/45RF20	103Y	XL, RFT	7.5-(8.0)-9.0	28.6	9.9	10.1	320 A A	
255/40RF20	101Y	XL, RFT	8.5-(9.0)-10.0	28.0	10.2	10.1	320 A A	
255/45RF20	101W	RFT	8.0-(8.5)-9.5	29.1	10.0	10.1	320 A A	
265/45RF20	104Y	RFT	8.5-(9.0)-10.0	29.4	10.5	10.1	320 A A	
275/35RF20	102Y	XL, RFT	9.0-(9.5)-11.0	27.6	10.9	10.5	320 A A	
275/40RF20	106Y	XL, RFT	9.0-(9.5)-11.0	28.6	10.9	10.5	320 A A	
275/45RF20	110Y	XL, RFT	8.5-(9.0)-10.5	29.7	10.8	10.5	320 A A	
285/30RF20	99Y	XL, RFT	9.5-(10.0)-10.5	26.7	11.5	10.5	320 A A	
315/35RF20	110Y	XL, RFT	10.5-(11.0)-12.5	28.6	12.5	10.5	320 A A	

Ø 19								
225/35RF19	88Y	XL, RFT	7.5-(8.0)-9.0	25.2	9.1	10.1	320 A A	
225/40RF19	93Y	XL, RFT	7.5-(8.0)-9.0	26.1	9.1	10.1	320 A A	
225/45RF19	92W	RFT	7.0-(7.5)-8.5	27.0	8.9	10.1	320 A A	
235/45RF19	95V	RFT	7.5-(8.0)-9.0	27.4	9.3	10.1	320 A A	
235/55RF19	105Y	XL, RFT	6.5-(7.5)-8.5	29.2	9.6	10.5	320 A A	
245/45RF19	102Y	XL, RFT	7.5-(8.0)-9.0	27.7	9.6	10.1	320 A A	
255/30RF19	91Y	XL, RFT	8.5-(9.0)-9.5	25.1	10.2	10.1	320 A A	
255/35RF19	96Y	XL, RFT	8.5-(9.0)-10.0	26.0	10.2	10.1	320 A A	
255/40RF19	100Y	XL, RFT	8.5-(9.0)-10.0	27.0	10.2	10.1	320 A A	
255/45RF19	104Y	XL, RFT	8.0-(8.5)-9.5	28.1	10.0	10.1	320 A A	
255/50RF19	107W	XL, RFT	7.0-(8.0)-9.0	29.1	10.4	10.1	320 A A	
255/55RF19	111Y	XL, RFT	7.0-(8.0)-9.0	30.0	10.4	10.1	320 A A	
265/50RF19	110W	XL, RFT	7.5-(8.5)-9.5	29.5	10.8	10.5	320 A A	
275/35RF19	100Y	XL, RFT	9.0-(9.5)-11.0	26.6	10.9	10.5	320 A A	
275/40RF19	101Y	RFT	9.0-(9.5)-11.0	27.7	10.9	10.5	320 A A	
275/55RF19	111Y	RFT	7.5-(8.5)-9.5	30.9	11.2	10.5	320 A A	
285/45RF19	111W	XL, RFT	9.0-(9.5)-10.5	29.1	11.2	10.5	320 A A	

Ø 18								
205/40RF18	86Y	XL, RFT	7.0-(7.5)-8.0	24.4	8.3	10.1	320 A A	
215/40RF18	85Y	RFT	7.0-(7.5)-8.5	24.8	8.6	10.1	320 A A	
225/40RF18	92Y	XL, RFT	7.5-(8.0)-9.0	25.1	9.1	10.1	320 A A	
225/45RF18	95Y	XL, RFT	7.0-(7.5)-8.5	25.9	8.9	10.1	320 A A	
225/50RF18	99W	XL, RFT	6.0-(7.0)-8.0	26.9	9.2	10.1	320 A A	
235/40RF18	95Y	XL, RFT	8.0-(8.5)-9.5	25.4	9.4	10.5	320 A A	
235/50RF18	97V	RFT	6.5-(7.5)-8.5	27.3	9.6	10.1	320 A A	
235/55RF18	104Y	XL, RFT	6.5-(7.5)-8.5	28.1	9.6	10.1	320 A A	
245/35RF18	92Y	XL, RFT	8.0-(8.5)-9.5	24.8	9.8	10.1	320 A A	
245/40RF18	97Y	XL, RFT	8.0-(8.5)-9.5	25.7	9.8	10.1	320 A A	
245/50RF18	104Y	XL, RFT	7.0-(7.5)-8.5	27.7	9.9	10.1	320 A A	



SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX R8+ | RUN-FLAT (CONT.)**

SPORT

Ø 18								
255/35RF18	94Y	XL, RFT	8.5-(9.0)-10.0	25.0	10.2	10.1	320 A A	
255/40RF18	99Y	XL, RFT	8.5-(9.0)-10.0	26.0	10.2	10.1	320 A A	
255/45RF18	103Y	XL, RFT	8.0-(8.5)-9.5	27.0	10.0	10.1	320 A A	
255/55RF18	109Y	XL, RFT	7.0-(8.0)-9.0	29.0	10.4	10.1	320 A A	
265/40RF18	101Y	XL, RFT	9.0-(9.5)-10.5	26.3	10.7	10.1	320 A A	
275/35RF18	95Y	RFT	9.0-(9.5)-11.0	25.6	10.9	10.5	320 A A	
275/40RF18	103Y	XL, RFT	9.0-(9.5)-11.0	26.7	10.9	10.5	320 A A	
Ø 17								
225/45RF17	94Y	XL, RFT	7.0-(7.5)-8.5	25.0	8.9	10.1	320 A A	
225/50RF17	98Y	XL, RFT	6.0-(7.0)-8.0	25.9	9.1	10.1	320 A A	
225/55RF17	97Y	RFT	6.0-(7.0)-8.0	26.8	9.2	10.1	320 A A	

**DIMAX R8+**

SPORT

Ø 26								
305/30R26	109W	XL	10.5-(11.0)-11.5	33.2	12.3	10.5	320 A A	
Ø 24								
295/35R24	110V	XL	10.0-(10.5)-11.5	32.1	11.9	10.5	320 A A	
305/35R24	112V	XL	10.0-(11.0)-12.0	32.4	12.3	10.5	320 A A	
Ø 22								
265/35R22	102Y	XL	9.0-(9.5)-10.5	29.3	10.6	10.5	320 A A	
265/40R22	106Y	XL	9.0-(9.5)-10.5	30.4	10.6	10.5	320 A A	
275/35R22	104Y	XL	9.0-(9.5)-11.0	29.6	10.9	10.5	320 A A	
275/40R22	108Y	XL	9.0-(9.5)-11.0	30.7	10.9	10.5	320 A A	
285/35R22	106Y	XL	9.5-(10.0)-11.0	29.8	11.4	10.5	320 A A	
295/30R22	103Y	XL	10.0-(10.5)-11.0	29.0	11.8	10.5	320 A A	
295/40R22	112W	XL	10.0-(10.5)-11.5	31.3	11.9	10.5	320 A A	
305/40R22	114V	XL	10.0-(11.0)-12.0	31.6	12.3	10.5	320 A A	
305/45R22	118V	XL	9.5-(10.0)-11.5	32.8	11.9	10.5	320 A A	
Ø 21								
245/35R21	96Y	XL	8.0-(8.5)-9.5	27.7	9.9	10.1	320 A A	
255/35R21	98Y	XL	8.0-(9.0)-10.0	28.0	10.2	10.1	320 A A	
255/40R21	102Y	XL	8.5-(9.0)-10.0	29.0	10.2	10.1	320 A A	
265/35R21	96Y	XL	9.0-(9.5)-10.5	28.3	10.6	10.1	320 A A	
265/40R21	105Y	XL	9.0-(9.5)-10.5	29.3	10.7	10.1	320 A A	
265/45R21	108Y	XL	8.5-(9.0)-10.0	30.3	10.7	10.1	320 A A	
275/30R21	98Y	XL	9.0-(9.5)-10.0	27.5	10.9	10.5	320 A A	
275/40R21	107Y	XL	9.0-(9.5)-11.0	29.6	10.9	10.5	320 A A	
275/45R21	110Y	XL	8.5-(9.0)-10.5	30.7	10.7	10.5	320 A A	
285/35R21	105Y	XL	9.5-(10.0)-11.0	28.9	11.4	10.5	320 A A	
285/40R21	109Y	XL	9.5-(10.0)-11.0	30.0	11.4	10.5	320 A A	
295/35R21	107Y	XL	10.0-(10.5)-11.5	29.1	11.9	10.5	320 A A	
295/40R21	111Y	XL	10.0-(10.5)-11.5	30.3	11.5	10.5	320 A A	
Ø 20								
235/45R20	100Y	XL	7.5-(8.0)-9.0	28.3	9.5	10.1	320 A A	
245/30R20	90Y	XL	8.0-(8.5)-9.0	25.8	9.7	10.1	320 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX R8+ (CONT.)**

SPORT

Ø 20								
245/35R20	98Y	-	8.0-(8.5)-9.5	26.8	9.8	10.1	320 A A	
245/35R20	95Y	XL	8.0-(8.5)-9.5	26.8	9.8	10.1	320 A A	
245/40R20	99Y	XL	8.0-(8.5)-9.5	27.7	9.8	10.1	320 A A	
245/45R20	103Y	XL	7.5-(8.0)-9.0	28.6	9.9	10.1	320 A A	
245/50R20	105W	XL	7.0-(7.5)-8.5	29.7	10.0	10.1	320 A A	
255/40R20	101Y	XL	8.5-(9.0)-10.0	28.0	10.2	10.1	320 A A	
255/45R20	105Y	XL	8.0-(8.5)-9.5	29.1	10.0	10.1	320 A A	
255/50R20	109Y	XL	7.0-(8.0)-9.0	30.1	10.4	10.1	320 A A	
255/55R20	110Y	XL	7.0-(8.0)-9.0	30.9	10.3	10.1	320 A A	
265/35R20	99Y	XL	9.0-(9.5)-10.5	27.3	10.7	10.1	320 A A	
265/45R20	108Y	XL	8.5-(9.0)-10.0	29.4	10.5	10.1	320 A A	
265/50R20	111Y	XL	7.5-(8.5)-9.5	30.5	10.9	10.1	320 A A	
275/35R20	102Y	XL	9.0-(9.5)-11.0	27.6	10.9	10.5	320 A A	
275/40R20	106Y	XL	9.0-(9.5)-11.0	28.7	10.9	10.5	320 A A	
275/45R20	110Y	XL	8.5-(9.0)-10.5	29.8	10.7	10.5	320 A A	
285/30R20	99Y	XL	9.5-(10.0)-10.5	26.7	11.5	10.5	320 A A	
295/40R20	110Y	XL	10.0-(10.5)-11.5	29.3	11.9	10.5	320 A A	
315/35R20	110Y	XL	10.5-(11.0)-12.5	28.7	12.6	10.5	320 A A	
Ø 19								
225/35R19	88Y	XL	7.5-(8.0)-9.0	25.2	9.1	10.1	320 A A	
225/40R19	93Y	XL	7.5-(8.0)-9.0	26.1	9.1	10.1	320 A A	
225/45R19	96Y	XL	7.0-(7.5)-8.5	27.0	8.9	10.1	320 A A	
225/55R19	103Y	XL	6.0-(7.0)-8.0	28.8	9.2	10.1	320 A A	
235/35R19	91Y	XL	8.0-(8.5)-9.5	25.5	9.4	10.1	320 A A	
235/40R19	96Y	XL	8.0-(8.5)-9.5	26.4	9.5	10.1	320 A A	
235/45R19	99Y	XL	7.5-(8.0)-9.0	27.4	9.3	10.1	320 A A	
235/50R19	103W	XL	6.5-(7.5)-8.5	28.3	9.6	10.1	320 A A	
235/55R19	105Y	XL	6.5-(7.5)-8.5	29.2	9.6	10.1	320 A A	
245/45R19	102Y	XL	7.5-(8.0)-9.0	27.7	9.6	10.1	320 A A	
255/30R19	91Y	XL	8.5-(9.0)-9.5	25.1	10.2	10.1	320 A A	
255/35R19	96Y	XL	8.5-(9.0)-10.0	26.0	10.2	10.1	320 A A	
255/40R19	100Y	XL	8.5-(9.0)-10.0	27.0	10.2	10.1	320 A A	
255/45R19	104Y	XL	8.0-(8.5)-9.5	28.1	10.0	10.1	320 A A	
255/50R19	107Y	XL	7.0-(8.0)-9.0	29.1	10.4	10.1	320 A A	
255/55R19	111Y	XL	7.0-(8.0)-9.0	30.0	10.4	10.1	320 A A	
265/50R19	110Y	XL	7.5-(8.5)-9.5	29.5	10.9	10.1	320 A A	
275/30R19	96Y	XL	9.0-(9.5)-10.0	25.6	10.9	10.5	320 A A	
275/35R19	100Y	XL	9.0-(9.5)-11.0	26.6	10.9	10.5	320 A A	
275/40R19	105Y	XL	9.0-(9.5)-11.0	27.7	10.9	10.5	320 A A	
275/45R19	108Y	XL	8.5-(9.0)-10.5	28.8	10.7	10.5	320 A A	
275/55R19	111Y	-	7.5-(8.5)-9.5	30.9	11.2	10.5	320 A A	
285/45R19	111Y	XL	9.0-(9.5)-10.5	29.1	11.2	10.5	320 A A	
Ø 18								
205/40R18	86Y	XL	7.0-(7.5)-8.0	24.4	8.3	10.1	320 A A	
215/40R18	89Y	XL	7.0-(7.5)-8.5	24.8	8.6	10.1	320 A A	
215/45R18	93Y	XL	(7.0)-8.0	25.6	8.4	10.1	320 A A	
225/35R18	87Y	XL	7.5-(8.0)-9.0	24.2	9.1	10.1	320 A A	
225/40R18	92Y	XL	7.5-(8.0)-9.0	25.1	9.1	10.1	320 A A	
225/45R18	95Y	XL	7.0-(7.5)-8.5	25.9	8.9	10.1	320 A A	
225/50R18	99Y	XL	6.0-(7.0)-8.0	26.9	9.2	10.1	320 A A	
235/40R18	95Y	XL	8.0-(8.5)-9.5	25.4	9.4	10.5	320 A A	
235/45R18	98Y	XL	7.5-(8.0)-9.0	26.3	9.3	10.1	320 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX R8+ (CONT.)**

SPORT

Ø 18								
235/50R18	101Y	XL	6.5-(7.5)-8.5	27.3	9.6	10.1	320 A A	
235/55R18	104Y	XL	6.5-(7.5)-8.5	28.1	9.6	10.1	320 A A	
245/35R18	92Y	XL	8.0-(8.5)-9.5	24.8	9.8	10.1	320 A A	
245/40R18	97Y	XL	8.0-(8.5)-9.5	25.7	9.8	10.1	320 A A	
245/50R18	104Y	XL	7.0-(7.5)-8.5	27.7	9.9	10.1	320 A A	
255/35R18	94Y	XL	8.5-(9.0)-10.0	25.0	10.2	10.1	320 A A	
255/40R18	99Y	XL	8.5-(9.0)-10.0	26.0	10.2	10.1	320 A A	
255/45R18	103Y	XL	8.0-(8.5)-9.5	27.0	10.0	10.1	320 A A	
255/55R18	109Y	XL	7.0-(8.0)-9.0	29.0	10.4	10.1	320 A A	
265/35R18	97Y	XL	9.0-(9.5)-10.5	25.3	10.7	10.1	320 A A	
265/40R18	101Y	XL	9.0-(9.5)-10.5	26.3	10.7	10.1	320 A A	
275/35R18	99Y	XL	9.0-(9.5)-11.0	25.6	10.9	10.5	320 A A	
275/40R18	103Y	XL	9.0-(9.5)-11.0	26.7	10.9	10.5	320 A A	

Ø 17								
215/40R17	87Y	XL	7.0-(7.5)-8.5	23.8	8.6	10.1	320 A A	
215/55R17	98Y	XL	6.0-(7.0)-7.5	26.3	8.8	10.1	320 A A	
225/45R17	94Y	XL	7.0-(7.5)-8.5	25.0	8.9	10.1	320 A A	
225/50R17	98Y	XL	6.0-(7.0)-8.0	25.9	9.1	10.1	320 A A	
225/55R17	101Y	XL	6.0-(7.0)-8.0	26.8	9.2	10.1	320 A A	
235/55R17	103Y	XL	6.5-(7.5)-8.5	27.2	9.6	10.1	320 A A	

**DIMAX R8 | RUN-FLAT**

SPORT

Ø 20								
245/35R20	98Y	RFT	8.0-(8.5)-9.5	26.8	9.8	10.1	320 A A	

Ø 19								
225/35RF19	88Y	XL, RFT	7.5-(8.0)-9.0	25.2	9.1	10.1	320 A A	
245/40RF19	94Y	RFT	8.0-(8.5)-9.5	26.7	9.8	10.1	320 A A	

Ø 18								
225/40RF18	88W	RFT	7.5-(8.0)-9.0	25.1	9.1	10.1	320 A A	
245/40RF18	93Y	RFT	8.0-(8.5)-9.5	25.7	9.8	10.1	320 A A	
245/45RF18	100Y	XL, RFT	7.5-(8.0)-9.0	26.7	9.6	10.1	320 A A	

Ø 17								
205/45RF17	84W	RFT	6.5-(7.0)-7.5	24.3	8.1	10.1	320 A A	
205/50RF17	89W	RFT	5.5-(6.5)-7.5	25.1	8.4	10.1	320 A A	
225/45RF17	91W	RFT	7.0-(7.5)-8.5	25.0	8.9	10.1	320 A A	
225/50RF17	94V	RFT	6.0-(7.0)-8.0	25.9	9.2	10.1	320 A A	

**DIMAX R8**

SPORT

Ø 20								
225/30R20	85Y	XL	(8.0)	25.4	9.1	10.1	320 A A	
225/35R20	90Y	XL	7.5-(8.0)-9.0	26.2	9.1	10.1	320 A A	
245/30R20	97W	XL	8.0-(8.5)-9.0	25.8	9.8	10.1	320 A A	
245/35R20	95Y	XL	8.0-(8.5)-9.5	26.8	9.8	10.1	320 A A	
255/35R20	97Y	XL	8.5-(9.0)-10.0	27.0	10.2	10.1	320 A A	
275/30R20	97Y	XL	9.0-(9.5)-10.0	26.5	10.9	10.1	320 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX R8**

SPORT

Ø 19								
225/35R19	88Y	XL	7.5-(8.0)-9.0	25.2	9.1	10.1	320 A A	
235/35R19	91Y	XL	8.0-(8.5)-9.5	25.5	9.5	10.1	320 A A	
245/35R19	93Y	XL	8.0-(8.5)-9.5	25.8	9.8	10.1	320 A A	
245/40R19	98Y	XL	8.0-(8.5)-9.5	26.7	9.8	10.1	320 A A	

Ø 18								
215/35R18	84Y	XL	7.0-(7.5)-8.5	23.9	8.6	10.1	320 A A	
225/40R18	92Y	XL	7.5-(8.0)-9.0	25.1	9.1	10.1	320 A A	
235/40R18	95Y	XL	8.0-(8.5)-9.5	25.4	9.5	10.1	320 A A	
245/40R18	97Y	XL	8.0-(8.5)-9.5	25.7	9.8	10.1	320 A A	
245/45R18	100Y	XL	7.5-(8.0)-9.0	26.7	9.6	10.1	320 A A	

Ø 17								
205/40R17	84Y	XL	7.0-(7.5)-8.0	23.5	8.3	10.1	320 A A	
205/45R17	88Y	XL	6.5-(7.0)-7.5	24.3	8.1	10.1	320 A A	
205/50R17	93Y	XL	5.5-(6.5)-7.5	25.1	8.4	10.1	320 A A	
215/45R17	91Y	XL	(7.0)-8.0	24.6	8.4	10.1	320 A A	
215/50R17	95Y	XL	6.0-(7.0)-7.5	25.5	8.9	10.1	320 A A	
215/55R17	98Y	XL	6.0-(7.0)-7.5	26.3	8.9	10.1	320 A A	
225/45R17	94Y	XL	7.0-(7.5)-8.5	25.0	8.9	10.1	320 A A	
225/50R17	98Y	XL	6.0-(7.0)-8.0	25.9	9.2	10.1	320 A A	
225/60R17	99W	-	6.0-(6.5)-8.0	27.6	9.0	10.1	320 A A	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	10.1	320 A A	
235/45R17	97Y	XL	7.5-(8.0)-9.0	25.4	9.3	10.1	320 A A	
235/55R17	103Y	XL	6.5-(7.5)-8.5	27.2	9.6	10.1	320 A A	
245/40R17	95Y	XL	8.0-(8.5)-9.5	24.7	9.8	10.1	320 A A	
245/45R17	99Y	XL	7.5-(8.0)-9.0	25.7	9.6	10.1	320 A A	

**DIMAX E-SPORT 1/2/3**

SPORT TOURING

Ø 19								
235/55R19	105W	XL	6.5-(7.5)-8.5	29.1	9.6	9.7	440 A A	

Ø 18								
215/55R18	99V	XL	6.0-(7.0)-7.5	27.2	8.9	10.1	440 A A	
225/40R18	92Y	XL	7.5-(8.0)-9.0	25.0	9.2	9.6	440 A A	
225/55R18	102W	XL	6.0-(7.0)-8.0	27.6	9.2	9.6	440 A A	
235/45R18	98Y	XL	7.5-(8.0)-9.0	26.2	9.4	9.6	440 A A	
235/50R18	101V	XL	6.5-(7.5)-8.5	27.2	9.7	9.7	440 A A	
235/55R18	104W	XL	6.5-(7.5)-8.5	28.1	9.7	9.7	440 A A	
235/60R18	107W	XL	6.5-(7.0)-8.5	29.1	9.6	9.7	440 A A	
245/40R18	97Y	XL	8.0-(8.5)-9.5	25.6	9.8	9.6	440 A A	
245/45R18	100Y	XL	7.5-(8.0)-9.0	26.5	9.6	9.6	440 A A	

Ø 17								
205/50R17	93W	XL	5.5-(6.5)-7.5	25.0	8.4	10.1	440 A A	
215/45R17	91Y	XL	(7.0)-8.0	24.5	8.4	9.6	440 A A	
215/50R17	95W	XL	6.0-(7.0)-7.5	25.4	8.7	10.1	440 A A	
215/55R17	94W	-	6.0-(7.0)-7.5	26.2	8.9	10.1	440 A A	
215/60R17	100V	XL	6.0-(6.5)-7.5	27.2	8.7	10.1	440 A A	
215/65R17	103V	XL	6.0-(6.5)-7.5	28.0	8.7	9.7	440 A A	
225/45R17	94Y	XL	7.0-(7.5)-8.5	24.8	8.8	9.6	440 A A	

# CAR/CUV/SUV

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>DIMAX E-SPORT 1/2/3 (CONT.)</b> SPORT TOURING								
<b>Ø 17</b>								
225/50R17	98Y	XL	6.0-(7.0)-8.0	25.8	9.1	9.6	440 A A	
225/55R17	101W	XL	6.0-(7.0)-8.0	26.6	9.3	9.6	440 A A	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	9.7	440 A A	
225/65R17	106V	XL	6.0-(6.5)-8.0	28.5	9.0	9.7	440 A A	
235/45R17	97Y	XL	7.5-(8.0)-9.0	25.2	9.4	9.6	440 A A	
235/55R17	99V	-	6.5-(7.5)-8.5	27.2	9.6	10.1	440 A A	
235/65R17	108W	XL	6.5-(7.0)-8.5	29.0	9.6	9.7	440 A A	
245/45R17	99Y	XL	7.5-(8.0)-9.0	25.6	9.7	9.6	440 A A	
<b>Ø 16</b>								
215/60R16	99V	XL	6.0-(6.5)-7.5	26.1	8.8	10.1	440 A A	
215/65R16	98V	-	6.0-(6.5)-7.5	26.9	8.8	10.1	440 A A	
<b>Ø 15</b>								
205/60R15	91V	-	5.5-(6.0)-7.5	24.6	8.2	10.1	440 B A	

<b>DIMAX E-TOURING 1</b> TOURING								
<b>Ø 16</b>								
205/55R16	91V	-	5.5-(6.5)-7.5	24.8	8.4	9.0	440 A A	
205/60R16	92H	-	5.5-(6.0)-7.5	25.5	8.2	9.0	440 A A	
<b>Ø 15</b>								
185/65R15	88H	-	5.0-(5.5)-6.5	24.3	7.3	9.0	440 B A	
195/60R15	88H	-	5.5-(6.0)-7.0	24.1	7.8	9.0	440 B A	
195/65R15	91H	-	5.5-(6.0)-7.0	24.8	7.8	9.0	440 B A	
205/65R15	94H	-	5.5-(6.0)-7.5	25.3	8.2	9.0	440 A A	

<b>RPX-800+   RUN-FLAT</b> SPORT TOURING								
<b>Ø 18</b>								
225/60RF18	104W	XL, RFT	6.0-(6.5)-8.0	28.6	9.1	10.1	520 A A	
235/60RF18	107W	XL, RFT	6.5-(7.0)-8.5	29.1	9.4	10.1	520 A A	
<b>Ø 17</b>								
225/60RF17	99V	RFT	6.0-(6.5)-8.0	27.6	9.1	10.1	520 A A	

<b>RPX-800+</b> SPORT TOURING								
<b>Ø 18</b>								
225/60R18	104W	XL	6.0-(6.5)-8.0	28.6	9.1	10.1	520 A A	
235/60R18	107W	XL	6.5-(7.0)-8.5	29.1	9.4	10.1	520 A A	
255/60R18	112W	XL	7.0-(7.5)-9.0	30.0	10.2	10.1	520 A A	
265/60R18	114V	XL	7.5-(8.0)-9.5	30.5	10.7	10.1	520 A A	
<b>Ø 17</b>								
215/60R17	100H	XL	6.0-(6.5)-7.5	27.2	8.7	10.1	520 A A	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	10.1	520 A A	

# CAR/CUV/SUV

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>RPX-800+ (CONT.)</b> SPORT TOURING								
<b>Ø 17</b>								
225/65R17	106V	XL	6.0-(6.5)-8.0	28.5	9.0	10.1	520 A A	
235/65R17	108W	XL	6.5-(7.0)-8.5	29.1	9.4	10.1	520 A A	
245/65R17	111H	XL	(7.0)-8.5	29.5	9.8	10.1	520 A A	
255/60R17	110V	XL	7.0-(7.5)-9.0	29.1	10.2	10.1	520 A A	
265/65R17	116H	XL	7.5-(8.0)-9.5	30.6	10.7	10.1	520 A A	
<b>Ø 16</b>								
215/70R16	104H	XL	5.5-(6.5)-7.0	27.9	8.7	10.1	520 A A	
235/60R16	104V	XL	6.5-(7.0)-8.5	27.1	9.4	10.1	520 A A	
265/70R16	112H	-	7.0-(8.0)-8.5	30.6	10.7	10.1	520 A A	

<b>RPX-800   RUN-FLAT</b> SPORT TOURING								
<b>Ø 17</b>								
205/55RF17	95Y	XL, RFT	5.5-(6.5)-7.5	25.9	8.4	10.1	520 A A	
<b>Ø 16</b>								
195/55RF16	91W	XL, RFT	5.5-(6.0)-7.0	24.4	7.9	9.8	520 A A	
205/55RF16	94W	XL, RFT	5.5-(6.5)-7.5	24.9	8.4	10.1	520 A A	
205/60RF16	96W	XL, RFT	5.5-(6.0)-7.5	25.6	8.3	9.8	520 A A	

<b>RPX-800</b> SPORT TOURING								
<b>Ø 18</b>								
215/50R18	92W	-	6.0-(7.0)-7.5	26.5	8.6	10.1	520 A A	
215/55R18	99W	XL	6.0-(7.0)-7.5	27.3	8.6	10.1	520 A A	
225/55R18	102Y	XL	6.0-(7.0)-8.0	27.7	9.0	10.1	520 A A	
235/55R18	104Y	XL	6.5-(7.5)-8.5	28.2	9.4	10.1	520 A A	
245/60R18	109H	XL	(7.0)-8.5	29.6	9.8	10.1	520 A A	
<b>Ø 17</b>								
195/40R17	81W	XL	6.5-(7.0)-7.5	23.1	7.9	9.8	520 A A	
195/45R17	85W	XL	6.0-(6.5)-7.5	23.9	7.7	9.6	520 A A	
205/55R17	95Y	XL	5.5-(6.5)-7.5	25.9	8.4	10.1	520 A A	
215/35R17	83W	XL	7.0-(7.5)-8.5	22.9	8.6	10.1	520 A A	

<b>Ø 16</b>								
175/50R16	81V	XL	5.0-(5.5)-6.0	22.9	7.2	9.8	520 A A	
185/50R16	85V	XL	5.0-(6.0)-6.5	23.3	7.5	9.8	520 A A	
195/50R16	88V	XL	5.5-(6.0)-7.0	23.7	7.9	9.8	520 A A	
195/55R16	87V	-	5.5-(6.0)-7.0	24.4	7.9	9.8	520 A A	
195/55R16	91V	XL	5.5-(6.0)-7.0	24.4	7.9	9.8	520 A A	
195/55R16	91W	XL	5.5-(6.0)-7.0	24.4	7.9	9.8	520 A A	
195/60R16	93V	XL	5.5-(6.0)-7.0	25.1	7.9	9.8	520 A A	
205/45R16	87W	XL	6.5-(7.0)-7.5	23.2	8.1	10.1	520 A A	
205/50R16	91W	XL	5.5-(6.5)-7.5	24.1	8.1	10.1	520 A A	
205/55R16	91V	-	5.5-(6.5)-7.5	24.9	8.4	10.1	520 A A	
205/55R16	94V	XL	5.5-(6.5)-7.5	24.9	8.4	10.1	520 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

RPX-800 (CONT.)

SPORT TOURING

Ø 16								
205/55R16	94W	XL	5.5-(6.5)-7.5	24.9	8.4	10.1	520 A A	
205/60R16	96V	XL	5.5-(6.0)-7.5	25.7	8.2	9.8	520 A A	
205/60R16	96W	XL	5.5-(6.0)-7.5	25.7	8.2	10.1	520 A A	
215/45R16	90W	XL	(7.0)-8.0	23.6	8.9	9.8	520 A A	
215/55R16	97W	XL	6.0-(7.0)-7.5	25.3	8.9	9.8	520 A A	
215/60R16	99V	XL	6.0-(6.5)-7.5	26.1	8.7	10.3	520 A A	
215/60R16	99W	XL	6.0-(6.5)-7.5	26.1	8.7	10.1	520 A A	
225/55R16	99W	XL	6.0-(7.0)-8.0	25.7	9.2	10.1	520 A A	
225/60R16	102W	XL	6.0-(6.5)-8.0	26.6	9.0	10.3	520 A A	

Ø 15								
155/60R15	74V	-	(4.5)-5.5	22.3	6.2	9.8	520 A A	
165/60R15	77H	-	4.5-(5.0)-6.0	22.8	6.7	9.8	520 A A	
165/60R15	81H	XL	4.5-(5.0)-6.0	22.8	6.7	9.8	520 A A	
165/65R15	81H	-	4.5-(5.0)-6.0	23.4	6.7	9.8	520 A A	
175/55R15	77V	-	5.0-(5.5)-6.0	22.6	7.2	9.8	520 A A	
175/65R15	84H	-	(5.0)-6.0	24.0	7.0	9.8	520 A A	
175/65R15	88H	XL	(5.0)-6.0	24.0	7.0	9.8	520 A A	
185/55R15	86V	XL	5.0-(6.0)-6.5	23.0	7.6	9.6	520 A A	
185/60R15	84H	-	5.0-(5.5)-6.5	23.7	7.4	9.6	520 A A	
185/60R15	88H	XL	5.0-(5.5)-6.5	23.7	7.4	9.6	520 A A	
185/65R15	88H	-	5.0-(5.5)-6.5	24.4	7.4	9.6	520 A A	
185/65R15	92H	XL	5.0-(5.5)-6.5	24.4	7.4	9.6	520 A A	
195/45R15	78V	-	6.0-(6.5)-7.5	21.9	7.7	9.8	520 A A	
195/50R15	82V	-	5.5-(6.0)-7.0	22.7	7.9	9.8	520 A A	
195/55R15	89V	XL	5.5-(6.0)-7.0	23.4	7.9	9.8	520 A A	
195/60R15	88V	-	5.5-(6.0)-7.0	24.2	7.9	10.1	520 A A	
195/60R15	92H	XL	5.5-(6.0)-7.0	24.2	7.9	10.1	520 A A	
195/60R15	92V	XL	5.5-(6.0)-7.0	24.2	7.9	10.1	520 A A	
195/65R15	91H	-	5.5-(6.0)-7.0	25.0	7.9	10.1	520 A A	
195/65R15	91V	-	5.5-(6.0)-7.0	25.0	7.9	10.1	520 A A	
195/65R15	95V	XL	5.5-(6.0)-7.0	25.0	7.9	10.1	520 A A	
205/60R15	91V	-	5.5-(6.0)-7.5	24.7	8.2	10.1	520 A A	
205/60R15	95V	XL	5.5-(6.0)-7.5	24.7	8.2	10.1	520 A A	
205/65R15	94V	-	5.5-(6.0)-7.5	25.5	8.2	10.1	520 A A	
205/65R15	99V	XL	5.5-(6.0)-7.5	25.5	8.2	10.1	520 A A	
205/70R15	100H	XL	5.0-(6.0)-7.0	26.3	8.2	10.8	520 A A	
215/65R15	100V	XL	6.0-(6.5)-7.5	26.0	8.7	10.5	520 A A	
215/70R15	98H	-	5.5-(6.5)-7.0	26.9	8.7	10.5	520 A A	

Ø 14								
165/70R14	81T	-	4.0-(5.0)-5.5	23.1	6.7	9.6	520 A A	
165/70R14	85H	XL	4.0-(5.0)-5.5	23.1	6.7	9.6	520 A A	
175/65R14	82H	-	(5.0)-6.0	23.0	7.0	9.6	520 A A	
175/65R14	86H	XL	(5.0)-6.0	23.0	7.0	9.6	520 A A	
175/70R14	88H	XL	4.5-(5.0)-6.0	23.7	7.0	9.6	520 A A	
185/55R14	80H	-	5.0-(6.0)-6.5	22.0	7.6	9.6	520 A A	
185/60R14	82H	-	5.0-(5.5)-6.5	22.8	7.4	9.6	520 A A	
185/60R14	86H	XL	5.0-(5.5)-6.5	22.8	7.4	9.6	520 A A	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

RPX-800 (CONT.)

SPORT TOURING

Ø 14								
185/65R14	86H	-	5.0-(5.5)-6.5	23.5	7.4	9.6	520 A A	
185/70R14	88H	-	4.5-(5.5)-6.0	24.3	7.4	9.6	520 A A	
195/60R14	86H	-	5.5-(6.0)-7.0	23.2	7.9	9.8	520 A A	
195/70R14	91H	-	5.0-(6.0)-6.5	24.8	7.9	9.8	520 A A	
205/70R14	95T	-	5.0-(6.0)-7.0	25.4	8.2	9.8	520 A A	

Ø 13								
165/65R13	77H	-	4.5-(5.0)-6.0	21.4	6.7	9.6	520 A A	
175/70R13	82H	-	4.5-(5.0)-6.0	22.7	7.0	9.6	520 A A	
175/70R13	82T	-	4.5-(5.0)-6.0	22.7	7.0	9.6	520 A A	
185/70R13	86H	-	4.5-(5.5)-6.0	23.2	7.4	9.6	520 A A	
185/70R13	86T	-	4.5-(5.5)-6.0	23.2	7.4	9.6	520 A A	

RIVERA PRO 2

TOURING

Ø 16								
185/55R16	83V	-	5.0-(6.0)-6.5	24.0	7.6	10.1	400 A A	
185/55R16	87H	XL	5.0-(6.0)-6.5	24.0	7.6	10.1	400 A A	
195/45R16	84V	XL	6.0-(6.5)-7.5	22.9	7.7	10.0	400 A A	
195/45R16	84W	XL	6.0-(6.5)-7.5	22.9	7.7	10.0	400 A A	
195/50R16	88V	XL	5.5-(6.0)-7.0	23.7	7.9	10.1	400 A A	
205/55R16	91V	-	5.5-(6.5)-7.5	24.9	8.4	10.3	400 A A	
205/60R16	96V	XL	5.5-(6.0)-7.5	25.7	8.2	10.3	400 A A	
215/60R16	99V	XL	6.0-(6.5)-7.5	26.1	8.7	10.3	400 A A	
215/65R16	102V	XL	6.0-(6.5)-7.5	27.0	8.7	10.0	400 A A	
225/60R16	102V	XL	6.0-(6.5)-8.0	26.6	9.0	10.3	400 A A	

Ø 15								
145/65R15	72H	-	4.0-(4.5)-5.0	22.4	5.9	9.4	400 A A	
175/60R15	81V	-	(5.0)-6.0	23.3	7.0	9.4	400 A A	
185/55R15	86V	XL	5.0-(6.0)-6.5	23.0	7.6	10.1	400 A A	
185/60R15	84H	-	5.0-(5.5)-6.5	23.0	7.6	10.1	400 A A	
185/60R15	88H	XL	5.0-(5.5)-6.5	23.7	7.4	10.1	400 A A	
185/65R15	88H	-	5.0-(5.5)-6.5	24.4	7.4	10.1	400 A A	
185/65R15	92H	XL	5.0-(5.5)-6.5	24.4	7.4	10.1	400 A A	
195/50R15	86V	XL	5.5-(6.0)-7.0	22.7	7.9	10.1	400 A A	
195/55R15	89V	XL	5.5-(6.0)-7.0	23.4	7.9	10.1	400 A A	
195/60R15	88H	-	5.5-(6.0)-7.0	24.2	7.9	10.1	400 A A	
195/65R15	91H	-	5.5-(6.0)-7.0	25.0	7.9	10.1	400 A A	
195/65R15	95H	XL	5.5-(6.0)-7.0	25.0	7.9	10.1	400 A A	
195/65R15	95V	XL	5.5-(6.0)-7.0	25.0	7.9	10.1	400 A A	
205/55R15	92V	XL	5.5-(6.5)-7.5	23.9	8.4	10.0	400 A A	
205/60R15	95V	XL	5.5-(6.0)-7.5	24.7	8.2	10.3	400 A A	
205/65R15	94H	-	5.5-(6.0)-7.5	25.5	8.2	10.3	400 A A	
205/65R15	99V	XL	5.5-(6.0)-7.5	25.5	8.2	10.3	400 A A	
205/70R15	96H	-	5.0-(6.0)-7.0	26.3	8.2	10.3	400 A A	

Ø 14								
155/65R14	79H	XL	(4.5)-5.5	22.0	6.2	9.4	400 A A	
165/60R14	79H	XL	4.5-(5.0)-6.0	21.8	6.7	9.4	400 A A	

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>RIVERA PRO 2 (CONT.)</b>								
<b>TOURING</b>								
<b>Ø 14</b>								
165/65R14	83H	XL	4.5-(5.0)-6.0	22.4	6.7	9.4	400 A A	
165/70R14	85T	XL	4.0-(5.0)-5.5	23.1	6.7	9.4	400 A A	
175/60R14	79H	-	(5.0)-6.0	22.3	7.0	9.4	400 A A	
175/65R14	82H	-	(5.0)-6.0	23.0	7.0	9.4	400 A A	
175/65R14	86H	XL	(5.0)-6.0	23.0	7.0	9.4	400 A A	
175/70R14	88H	XL	4.5-(5.0)-6.0	23.7	7.0	9.4	400 A A	
185/60R14	82H	-	5.0-(5.5)-6.5	22.8	7.4	10.1	400 A A	
185/65R14	86H	-	5.0-(5.5)-6.5	23.5	7.4	10.1	400 A A	
185/70R14	88T	-	4.5-(5.5)-6.0	24.3	7.4	10.1	400 A A	
195/60R14	86H	-	5.5-(6.0)-7.0	23.2	7.9	10.3	400 A A	
195/70R14	91T	-	5.0-(6.0)-6.5	24.8	7.9	10.1	400 A A	
205/70R14	95T	-	5.0-(6.0)-7.0	25.4	8.2	10.3	400 A A	
<b>Ø 13</b>								
135/80R13	70T	-	(3.5)-4.5	21.5	5.2	8.8	400 A A	
155/65R13	73T	-	(4.5)-5.5	20.9	6.2	9.4	400 A A	
155/70R13	75T	-	4.0-(4.5)-5.0	21.6	6.2	9.4	400 A A	
155/80R13	79T	-	4.0-(4.5)-5.0	22.8	6.2	9.4	400 A A	
165/65R13	77T	-	4.5-(5.0)-6.0	21.4	6.7	9.4	400 A A	
165/70R13	79T	-	4.0-(5.0)-5.5	22.1	6.7	9.4	400 A A	
165/70R13	83T	XL	4.0-(5.0)-5.5	22.1	6.7	9.4	400 A A	
175/65R13	80T	-	(5.0)-6.0	22.0	7.0	9.4	400 A A	
175/70R13	82T	-	4.5-(5.0)-6.0	22.7	7.0	9.4	400 A A	
185/70R13	86T	-	4.5-(5.5)-6.0	23.2	7.4	10.3	400 A A	

# SUV/LIGHT TRUCK

## HIGHWAY TERRAIN



RIVERA GT-10



RENEGADE H/T


## ALL TERRAIN



RENEGADE A/T PRO



RENEGADE A/T5




RXS-8



RXS-9

## RUGGED TERRAIN



RENEGADE R/T




RENEGADE R/T+

## MUD TERRAIN



RENEGADE R7 M/T



RENEGADE R5 M/T

# SUV/LIGHT TRUCK

SIZE	LI/SR.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	--------	------	--------------	----------	----------	-------------	------	--------

## RIVERA GT-10

HIGHWAY TERRAIN

Ø 20								
275/55R20	117S	XL	7.5-(8.5)-9.5	31.9	11.2	12.0	500 A A	
Ø 18								
LT275/70R18	125/122S	E	7.0-(8.0)-8.5	33.2	11.0	14.5	-	
Ø 17								
225/65R17	102T	-	6.0-(6.5)-8.0	28.5	9.0	12.0	500 A A	
245/65R17	105T	-	(7.0)-8.5	29.5	9.8	12.0	500 A A	
245/70R17	108S	-	6.5-(7.0)-8.0	30.6	9.8	12.0	500 A A	
265/65R17	110S	-	7.5-(8.0)-9.5	30.6	10.7	12.0	500 A A	
265/70R17	113S	-	7.0-(8.0)-9.0	31.7	10.7	12.0	500 A A	
LT245/75R17	121/118Q	E	6.5-(7.0)-7.5	32.0	9.8	14.5	-	
LT265/70R17	121/118Q	E	7.0-(8.0)-8.5	31.7	10.7	14.5	-	
Ø 16								
235/70R16	104T	-	6.0-(7.0)-8.0	29.0	9.4	12.0	500 A A	
245/70R16	111H	XL	6.5-(7.0)-7.5	29.5	9.8	12.0	500 A A	
245/75R16	109S	-	6.5-(7.0)-8.0	30.5	9.8	12.0	500 A A	
255/70R16	109S	-	6.5-(7.5)-8.0	30.1	10.2	12.0	500 A A	
265/70R16	111S	-	7.0-(8.0)-8.5	30.6	10.7	12.0	500 A A	
265/75R16	114S	-	7.0-(7.5)-8.0	31.7	10.5	12.0	500 A A	
LT215/85R16	115/112Q	E	5.5-(6.0)-7.0	30.4	8.5	14.5	-	
LT225/75R16	115/112Q	E	(6.0)-7.0	29.3	8.8	14.5	-	
LT235/85R16	120/116Q	E	6.0-(6.5)-7.5	31.7	9.3	14.5	-	
LT245/75R16	120/116S	E	6.5-(7.0)-8.0	30.5	9.8	12.0	-	
LT265/75R16	123/120S	D	7.0-(7.5)-8.0	31.7	10.5	14.5	-	
LT285/75R16	126/123S	E	7.5-(8.0)-9.0	33.4	11.3	14.5	-	
Ø 15								
235/75R15	108T	XL	6.0-(6.5)-8.0	28.9	9.3	12.0	500 A A	
31X10.50R15LT	109S	C	7.0-(8.5)-9.0	30.5	10.6	14.5	-	

## RENEGADE H/T

HIGHWAY TERRAIN

Ø 17								
LT235/80R17	120/117S	E	6.0-(6.5)-7.5	31.8	9.3	14.5	-	
LT265/70R17	121/118S	E	7.0-(8.0)-8.5	31.7	10.7	14.5	-	
Ø 16								
LT225/75R16	115/112S	E	(6.0)-7.0	29.3	8.8	13.2	-	
LT235/85R16	120/116S	E	6.0-(6.5)-7.5	31.7	9.3	13.2	-	
LT245/75R16	120/116S	E	6.5-(7.0)-8.0	30.5	9.8	13.2	-	

# SUV/LIGHT TRUCK

# SUV/LIGHT TRUCK

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

## RENEGADE A/T PRO

ALL TERRAIN

Ø 22								
285/45R22	114H	XL	9.0-(9.5)-10.5	32.1	11.2	13.6	540 A A	
305/45R22	118H	XL	9.5-(10.0)-11.5	32.8	11.9	13.6	540 A A	
33x12.50R22LT	109R	E	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
33x12.50R22LT	114R	F	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
35x12.50R22LT	117R	E	8.5-(10.0)-11.0	35.0	12.5	17.0	-	
35x12.50R22LT	121R	F	8.5-(10.0)-11.0	35.0	12.5	17.0	-	

Ø 20								
265/50R20	111T	XL	7.5-(8.5)-9.5	30.7	10.9	14.1	540 A B	
275/55R20	117H	XL	7.5-(8.5)-9.5	32.1	11.2	13.6	540 A A	
275/60R20	116T	XL	7.5-(8.0)-9.5	33.2	11.0	14.1	540 A B	
285/50R20	116T	XL	8.0-(9.0)-10.0	31.5	11.7	14.1	540 A B	
LT265/50R20	121/118S	E	7.5-(8.5)-9.5	30.7	10.9	17.0	-	
LT265/60R20	121/118S	E	7.5-(8.0)-9.5	32.8	10.7	17.0	-	
LT275/55R20	120/117S	E	7.5-(8.5)-9.5	32.1	11.2	17.0	-	
LT275/60R20	123/120S	E	7.5-(8.0)-9.5	33.2	11.0	17.0	-	
LT275/65R20	126/123S	E	7.5-(8.0)-9.5	34.3	11.0	17.0	-	
LT285/50R20	119/116S	E	8.0-(9.0)-10.0	31.5	11.7	17.0	-	
LT285/55R20	122/119S	E	8.0-(9.0)-10.0	32.6	11.7	17.0	-	
LT295/55R20	123/120S	E	8.0-(9.5)-10.0	33.0	12.2	17.0	-	
LT305/55R20	121/118S	E	8.5-(9.5)-11.0	33.5	12.4	17.0	-	
LT305/55R20	125/122S	F	8.5-(9.5)-11.0	33.5	12.4	17.0	-	
33x12.50R20LT	114R	E	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
33x12.50R20LT	119R	F	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
35x12.50R20LT	121R	E	8.5-(10.0)-11.0	35.0	12.5	17.0	-	
35x12.50R20LT	125R	F	8.5-(10.0)-11.0	35.0	12.5	17.0	-	

Ø 18								
255/55R18	109T	XL	7.0-(8.0)-9.0	29.3	10.4	14.1	540 A B	
255/70R18	116T	XL	6.5-(7.5)-8.5	32.3	10.2	14.1	540 A B	
265/60R18	114T	XL	7.5-(8.0)-9.5	30.7	10.7	14.1	540 A B	
265/65R18	116H	XL	7.5-(8.0)-9.5	31.8	10.7	13.6	540 A A	
275/65R18	116T	XL	7.5-(8.0)-9.5	32.3	11.0	14.1	540 A B	
285/60R18	120T	XL	8.0-(8.5)-10.0	31.7	11.5	14.1	540 A B	
33x12.50R18LT	118R	E	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
33x12.50R18LT	122R	F	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
35x12.50R18LT	123R	E	8.5-(10.0)-11.0	35.0	12.5	17.0	-	
35x12.50R18LT	128R	F	8.5-(10.0)-11.0	35.0	12.5	17.0	-	

Ø 17								
265/65R17	116H	XL	7.5-(8.0)-9.5	30.8	10.7	13.9	540 A A	
265/70R17	115T	-	7.0-(8.0)-9.0	31.9	10.7	14.1	540 A B	
LT245/75R17	121/118S	E	6.5-(7.0)-7.5	31.7	9.8	17.0	-	
LT265/70R17	121/118S	E	7.0-(8.0)-8.5	31.9	10.7	17.0	-	
LT285/70R17	121/118S	E	7.5-(8.5)-9.0	33.0	11.5	17.0	-	
33x12.50R17LT	120R	E	8.5-(10.0)-11.0	33.0	12.5	17.0	-	
35x12.50R17LT	121R	E	8.5-(10.0)-11.0	35.0	12.5	17.0	-	

SIZE	LI/S.R.	LR.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	----------	--------------	----------	----------	-------------	------	--------

## RENEGADE A/T5

ALL TERRAIN

Ø 22									
275/40R22	108V	XL	-	9.0-(9.5)-11.0	30.7	10.9	13.2	500 A A	
285/45R22	114V	XL	-	9.0-(9.5)-10.5	32.1	11.2	13.2	500 A A	
305/40R22	114H	-	-	10.0-(11.0)-12.0	31.6	12.3	13.2	500 A A	
305/45R22	118S	XL	-	9.5-(10.0)-11.5	32.8	11.9	13.2	500 A A	
LT285/50R22	121/118R	E	OWL	8.0-(9.0)-10.0	33.3	11.7	17.0	-	
LT325/50R22	121Q	E	OWL	9.0-(10.0)-12.0	34.8	13.2	17.0	-	
LT325/50R22	122S	E	OWL	9.0-(10.0)-12.0	34.8	13.2	17.0	-	
33x12.50R22LT	109Q	E	-	8.5-(10.0)-11.0	32.8	12.5	17.0	-	
33x12.50R22LT	114Q	F	-	8.5-(10.0)-11.0	32.8	12.5	17.0	-	
35x12.50R22LT	117Q	E	OWL	8.5-(10.0)-11.0	34.8	12.5	17.0	-	
35x12.50R22LT	121Q	F	OWL	8.5-(10.0)-11.0	34.8	12.5	17.0	-	
37x12.50R22LT	123Q	E	OWL	8.5-(10.0)-11.0	36.8	12.5	17.0	-	
37x12.50R22LT	127Q	F	OWL	8.5-(10.0)-11.0	36.8	12.5	17.0	-	

Ø 20									
255/55R20	110H	XL	-	7.0-(8.0)-9.0	31.4	10.4	13.2	500 A A	
265/50R20	112V	XL	-	7.5-(8.5)-9.5	30.5	10.9	13.0	500 A A	
275/45R20	110H	XL	-	8.5-(9.0)-10.5	29.8	10.7	13.0	500 A A	
275/55R20	117H	XL	-	7.5-(8.5)-9.5	31.9	11.2	13.0	500 A A	
275/60R20	119H	XL	-	7.5-(8.0)-9.5	33.0	11.0	13.0	500 A A	
285/50R20	116V	XL	-	8.0-(9.0)-10.0	31.3	11.7	13.2	500 A A	
305/50R20	120H	XL	-	8.5-(9.5)-11.0	32.0	12.4	13.6	500 A A	
LT265/60R20	121/118S	E	OWL	7.5-(8.0)-9.5	32.5	10.7	16.0	-	
LT275/65R20	126/123S	E	OWL	7.5-(8.0)-9.5	34.1	11.0	16.0	-	
LT285/55R20	122/119S	E	-	8.0-(9.0)-10.0	32.4	11.7	17.0	-	
LT295/55R20	123/120S	E	-	8.0-(9.5)-10.0	33.0	12.2	16.0	-	
LT295/60R20	126/123S	E	-	8.0-(8.5)-10.0	34.2	11.8	16.0	-	
LT295/65R20	129/126S	E	OWL	8.0-(8.5)-10.0	35.4	11.8	17.0	-	
LT305/55R20	121/118S	E	-	8.5-(9.5)-11.0	33.2	12.4	17.0	-	
LT305/55R20	125/122Q	F	-	8.5-(9.5)-11.0	33.2	12.4	17.0	-	
33x12.50R20LT	114Q	E	OWL	8.5-(10.0)-11.0	32.8	12.5	17.0	-	
33x12.50R20LT	119Q	F	OWL	8.5-(10.0)-11.0	32.8	12.5	17.0	-	
35x12.50R20LT	121S	E	OWL	8.5-(10.0)-11.0	34.5	12.5	17.0	-	
35x12.50R20LT	125Q	F	OWL	8.5-(10.0)-11.0	34.5	12.5	17.0	-	
37x12.50R20LT	126R	E	OWL	8.5-(10.0)-11.0	36.8	12.5	17.0	-	

Ø 18									
265/65R18	114H	-	OWL	7.5-(8.0)-9.5	31.5	10.7	13.2	500 A A	
275/65R18	116T	-	OWL	7.5-(8.0)-9.5	32.1	11.0	13.2	500 A A	
LT265/70R18	124/121S	E	OWL	7.0-(8.0)-9.0	32.6	10.7	16.0	-	
LT275/65R18	123/120S	E	OWL	7.5-(8.0)-9.0	32.1	11.0	16.0	-	
LT275/70R18	125/122S	E	OWL	7.0-(8.0)-8.5	33.2	11.0	16.0	-	
LT285/65R18	125/122S	E	OWL	8.0-(8.5)-10.0	32.6	11.5	17.0	-	
35x12.50R18LT	123S	E	OWL	8.5-(10.0)-11.0	34.5	12.5	17.0	-	
35x12.50R18LT	128Q	F	OWL	8.5-(10.0)-11.0	34.5	12.5	17.0	-	

Ø 17									
245/65R17	111H	XL	-	(7.0)-8.5	29.5	9.8	13.9	500 A A	
245/70R17	110T	-	-	6.5-(7.0)-8.0	30.6	9.8	13.9	500 A A	

# SUV/LIGHT TRUCK

SIZE	LI./S.R.	LR.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	----------	--------------	----------	----------	-------------	------	--------

## RENEGADE A/T5 (CONT.)

ALL TERRAIN

Ø 17									
265/65R17	116T	XL	-	7.5-(8.0)-9.5	30.6	10.7	13.6	500 A A	
265/70R17	115H	-	OWL	7.0-(8.0)-9.0	31.7	10.7	13.0	500 A A	
LT235/80R17	120/117S	E	-	6.0-(6.5)-7.5	31.8	9.3	16.0	-	
LT245/70R17	119/116S	E	-	6.5-(7.0)-8.0	30.6	9.8	16.0	-	
LT245/75R17	121/118S	E	-	6.5-(7.0)-7.5	31.5	9.8	15.0	-	
LT255/75R17	111/108Q	C	-	6.5-(7.0)-8.5	32.0	10.0	16.0	-	
LT265/70R17	121/118S	E	-	7.0-(8.0)-8.5	31.7	10.7	16.0	-	
LT285/70R17	121/118S	E	-	7.5-(8.5)-9.0	32.8	11.5	17.0	-	
35x12.50R17LT	121R	E	-	8.5-(10.0)-11.0	34.8	12.5	17.0	-	

Ø 16									
205R16C	110/108S	-	-	5.0-(5.5)-7.0	28.9	8.0	12.0	500 A A	
205/80R16	104T	XL	-	5.0-(5.5)-7.0	28.9	8.0	12.0	500 A A	
235/70R16	106H	-	-	6.0-(7.0)-8.0	29.0	9.4	13.9	500 A A	
245/70R16	111H	XL	-	6.5-(7.0)-7.5	29.5	9.8	13.9	500 A A	
245/75R16	111T	-	-	6.5-(7.0)-8.0	30.5	9.8	13.9	500 A A	
255/70R16	111H	-	-	6.5-(7.5)-8.0	30.1	10.2	13.9	500 A A	
265/70R16	112H	-	OWL	7.0-(8.0)-8.5	30.6	10.7	13.0	500 A A	
265/75R16	116S	-	OWL	7.0-(7.5)-8.0	31.7	10.5	13.0	500 A A	
LT225/75R16	115/112R	E	-	(6.0)-7.0	29.3	8.8	16.0	-	
LT235/85R16	120/116S	E	-	6.0-(6.5)-7.5	31.7	9.3	15.0	-	
LT245/75R16	120/116R	E	-	6.5-(7.0)-8.0	30.5	9.8	15.0	-	
LT265/75R16	123/120R	E	-	7.0-(7.5)-8.0	31.7	10.5	16.0	-	
LT285/75R16	126/123R	E	-	7.5-(8.0)-9.0	32.8	11.3	17.0	-	

Ø 15									
205/70R15	100H	XL	-	5.0-(6.0)-7.0	26.3	8.2	12.0	500 A A	
235/75R15	109T	XL	-	6.0-(6.5)-8.0	28.9	9.3	13.9	500 A A	
31x10.50R15LT	109S	C	OWL	7.0-(8.5)-9.0	30.5	10.6	15.0	-	

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

## RXS-8

ALL TERRAIN

Ø 20									
275/55R20	117H	XL		7.5-(8.5)-9.5	31.9	10.8	10.8	520 A B	

Ø 17									
265/70R17	115H	XL		7.0-(8.0)-9.0	31.7	10.7	10.8	520 A B	

Ø 16									
245/70R16	111T	XL		6.5-(7.0)-7.5	29.5	9.8	12.1	520 A B	
265/70R16	112T	-		7.0-(8.0)-8.5	30.6	10.7	12.9	520 A B	
275/70R16	114T	-		7.0-(8.0)-9.0	31.2	11.0	13.4	520 A B	

Ø 15									
215/75R15	100T	-		5.5-(6.0)-6.5	27.7	8.5	13.1	520 A B	
235/70R15	103T	-		6.5-(7.0)-7.5	28.0	9.4	10.6	520 A B	
235/75R15	109S	XL		6.0-(6.5)-8.0	28.9	9.3	12.1	520 A B	

# SUV/LIGHT TRUCK

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

## RXS-8 (CONT.)

ALL TERRAIN

Ø 15								
265/70R15	112T	-		7.5-(8.0)-8.5	29.6	10.7	12.9	520 A B
31x10.50R15LT	109Q	C		7.0-(8.5)-9.0	30.5	10.6	15.7	-

## RXS-9

ALL TERRAIN

Ø 17								
235/65R17	104T	-		6.5-(7.0)-8.5	29.1	9.4	12.1	520 A B
245/65R17	107T	-		(7.0)-8.5	29.5	9.8	12.1	520 A B
245/70R17	110T	-		6.5-(7.0)-8.0	30.6	9.8	12.1	520 A B
265/65R17	112T	-		7.5-(8.0)-9.5	30.6	10.7	12.9	520 A B
265/70R17	115T	-		7.0-(8.0)-9.0	31.7	10.7	12.9	520 A B

Ø 16								
235/70R16	106T	-		6.0-(7.0)-8.0	29.0	9.4	12.1	520 A B
255/70R16	111T	-		6.5-(7.5)-8.0	30.1	10.2	12.9	520 A B

## RLT-8

ALL TERRAIN

Ø 17								
LT265/70R17	121/118R	E		7.0-(8.0)-9.0	31.7	10.7	15.0	-
LT285/70R17	121/118R	D		7.5-(8.5)-9.0	32.8	11.5	15.7	-

Ø 16								
LT235/85R16	120/116Q	E		6.0-(6.5)-7.5	31.7	9.3	13.6	-
LT245/75R16	120/116Q	E		6.5-(7.0)-8.0	30.5	9.8	12.1	-
LT265/75R16	123/120R	E		7.0-(7.5)-8.0	31.7	10.5	15.7	-
LT285/75R16	122/119Q	D		7.5-(8.0)-9.0	32.8	11.3	16.4	-

Ø 15								
31X10.50R15LT	109Q	C		7.0-(8.5)-9.0	16.4	10.6	15.7	-

## RENEGADE R/T

RUGGED TERRAIN

Ø 24								
33x12.50R24LT	104Q	E		8.5-(10.0)-11.0	33.0	12.5	18.9	-
35x12.50R24LT	114Q	E		8.5-(10.0)-11.0	35.0	12.5	20.2	-
35x13.50R24LT	118Q	E		8.5-(10.0)-11.0	35.0	13.6	18.9	-
37x13.50R24LT	120Q	E		8.5-(11.0)	37.0	13.6	20.2	-

Ø 22								
285/45R22	114T	XL		9.0-(9.5)-10.5	32.3	11.2	13.2	600 A A
LT285/50R22	121/118Q	E		8.0-(9.0)-10.0	33.5	11.7	16.4	-
LT285/55R22	124/121Q	E		8.0-(9.0)-10.0	34.6	11.7	16.4	-
33x12.50R22LT	109Q	E		8.5-(10.0)-11.0	33.0	12.5	18.9	-
33x12.50R22LT	114Q	F		8.5-(10.0)-11.0	33.0	12.5	18.9	-
35x12.50R22LT	117Q	E		8.5-(10.0)-11.0	35.0	12.5	20.2	-
35x12.50R22LT	121Q	F		8.5-(10.0)-11.0	35.0	12.5	20.2	-
35x13.50R22LT	121Q	E		9.5-(11.0)-12.0	35.0	13.6	18.9	-



# SUV/LIGHT TRUCK

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>RENEGADE R/T (CONT.)</b>								
<b>Ø 24</b>								
37x12.50R22LT	127Q	F	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x13.50R22LT	123Q	E	8.5-(11.0)	37.0	13.6	20.2	-	
37x13.50R22LT	128Q	F	8.5-(11.0)	37.0	13.6	20.2	-	
<b>Ø 20</b>								
275/55R20	117T	XL	7.5-(8.5)-9.5	32.1	11.2	13.2	600 A A	
285/50R20	116T	XL	8.0-(9.0)-10.0	31.5	11.7	13.2	600 A A	
LT265/50R20	121/118Q	E	7.5-(8.5)-9.5	30.7	10.9	16.4	-	
LT265/60R20	121/118Q	E	7.5-(8.0)-9.5	32.8	10.7	16.4	-	
LT275/55R20	120/117Q	E	7.5-(8.5)-9.5	32.1	11.2	16.4	-	
LT275/60R20	123/120Q	E	7.5-(8.0)-9.5	33.2	11.0	15.7	-	
LT275/65R20	126/123Q	E	7.5-(8.0)-9.5	34.3	11.0	16.4	-	
LT285/50R20	119/116Q	E	8.0-(9.0)-10.0	31.5	11.7	16.4	-	
LT285/55R20	122/119Q	E	8.0-(9.0)-10.0	32.6	11.7	15.7	-	
LT285/60R20	125/122Q	E	8.0-(8.5)-10.0	33.7	11.5	16.4	-	
LT295/55R20	123/120Q	E	8.0-(9.5)-10.0	33.0	12.2	16.4	-	
LT295/65R20	129/126Q	E	8.0-(8.5)-10.0	35.4	11.8	16.4	-	
LT305/55R20	125/122Q	F	8.5-(9.5)-11.0	33.5	12.4	20.2	-	
LT325/60R20	126/123Q	E	9.0-(9.5)-12.0	35.6	13.0	20.2	-	
33x11.50R20LT	118Q	E	8.0-(9.0)-10.5	33.0	11.4	18.9	-	
33x12.50R20LT	114Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
33x12.50R20LT	119Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x11.50R20LT	124Q	E	8.0-(9.0)-10.5	35.0	11.4	18.9	-	
35x12.50R20LT	121Q	E	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x12.50R20LT	125Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x13.50R20LT	121Q	E	9.5-(11.0)-12.0	35.0	13.6	18.9	-	
35x13.50R20LT	126Q	F	9.5-(11.0)-12.0	35.0	13.6	18.9	-	
37x12.50R20LT	126Q	E	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x12.50R20LT	128Q	F	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x13.50R20LT	127Q	E	8.5-(11.0)	37.0	13.6	20.2	-	
37x13.50R20LT	128Q	F	8.5-(11.0)	37.0	13.6	20.2	-	
<b>Ø 18</b>								
LT275/65R18	123/120Q	E	7.5-(8.0)-9.0	32.3	11.0	16.4	-	
LT275/70R18	125/122Q	E	7.0-(8.0)-8.5	33.4	11.0	16.4	-	
LT285/65R18	125/122Q	E	8.0-(8.5)-10.0	32.8	11.5	15.7	-	
33x12.50R18LT	118Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
33x12.50R18LT	122Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x12.50R18LT	123Q	E	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x12.50R18LT	128Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
37x13.50R18LT	128Q	E	8.5-(11.0)	37.0	13.6	20.2	-	
<b>Ø 17</b>								
LT285/70R17	121/118Q	E	7.5-(8.5)-9.0	33.0	11.5	15.7	-	
LT295/70R17	121/118Q	E	7.5-(8.5)-10.0	33.5	11.8	16.4	-	
33x12.50R17LT	120Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
33x12.50R17LT	121Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x12.50R17LT	121Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x12.50R17LT	125Q	E	8.5-(10.0)-11.0	35.0	12.5	20.2	-	

# SUV/LIGHT TRUCK

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>RENEGADE R/T+</b>								
<b>Ø 24</b>								
35x12.50R24LT	114Q	E	8.5-(10.0)-11	35.0	12.5	18.9	-	
37x13.50R24LT	120Q	E	8.5-(11.0)	37.0	13.6	18.9	-	
40x15.50R24LT	128Q	E	11.0-(12.5)-14.0	39.8	15.4	20.2	-	
<b>Ø 22</b>								
LT285/50R22	121Q	E	8.0-(9.0)-10.0	33.5	11.7	16.4	-	
LT325/50R22	122Q	E	9.0-(10.0)-12.0	35.0	13.2	20.2	-	
LT325/50R22	127Q	F	9.0-(10.0)-12.0	35.0	13.2	20.2	-	
33x12.50R22LT	109Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
33x12.50R22LT	114Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x12.50R22LT	117Q	E	8.5-(10.0)-11.0	35.0	12.5	18.9	-	
35x12.50R22LT	121Q	F	8.5-(10.0)-11.0	35.0	12.5	18.9	-	
37x12.50R22LT	123Q	E	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x12.50R22LT	127Q	F	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x13.50R22LT	123Q	E	8.5-(11.0)	37.0	13.6	20.2	-	
<b>Ø 20</b>								
LT265/50R20	121/118Q	E	7.5-(8.5)-9.5	30.7	10.9	16.4	-	
LT275/55R20	120/117Q	E	7.5-(8.5)-9.5	32.1	11.2	16.4	-	
LT275/60R20	123/120Q	E	7.5-(8.0)-9.5	33.2	11.0	16.4	-	
LT275/65R20	126/123Q	E	7.5-(8.0)-9.5	34.3	11.0	16.4	-	
LT285/50R20	119/116Q	E	8.0-(9.0)-10.0	31.5	11.7	16.4	-	
LT285/55R20	122/119Q	E	8.0-(9.0)-10.0	32.6	11.7	16.4	-	
LT285/60R20	125/122Q	E	8.0-(8.5)-10.0	33.7	11.5	16.4	-	
LT295/55R20	123/120Q	E	8.0-(9.5)-10.0	33.0	12.2	16.4	-	
LT295/60R20	126/123Q	E	8.0-(8.5)-10.0	34.2	11.8	16.4	-	
LT295/65R20	129/126Q	E	8.0-(8.5)-10.0	35.4	11.8	16.4	-	
LT305/55R20	121/118Q	E	8.5-(9.5)-11.0	33.5	12.4	20.2	-	
LT305/55R20	125/122Q	F	8.5-(9.5)-11.0	33.5	12.4	20.2	-	
LT325/60R20	126/123Q	E	9.0-(9.5)-12.0	35.6	13.0	20.2	-	
33x12.50R20LT	114Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
33x12.50R20LT	119Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x12.50R20LT	121Q	E	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x12.50R20LT	125Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x13.50R20LT	126Q	F	9.5-(11.0)-12.0	35.0	13.6	18.9	-	
37x12.50R20LT	126Q	E	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x13.50R20LT	127Q	E	8.5-(11.0)	37.8	13.6	20.2	-	
<b>Ø 18</b>								
LT265/60R18	119/116Q	E	(8.0)-9.5	30.7	10.7	16.4	-	
LT265/65R18	122/119Q	E	7.5-(8.0)-9.5	31.8	10.7	16.4	-	
LT265/70R18	124/121Q	E	7.0-(8.0)-9.0	32.9	10.7	16.4	-	
LT275/65R18	123/120Q	E	7.5-(8.0)-9.0	32.3	11.0	16.4	-	
LT275/70R18	125/122Q	E	7.0-(8.0)-8.5	33.4	11.0	16.4	-	
LT285/60R18	122/119Q	E	8.0-(8.5)-10.0	31.7	11.5	16.4	-	
LT285/65R18	125/122Q	E	8.0-(8.5)-10.0	32.8	11.5	16.4	-	
LT285/75R18	129/126Q	E	7.5-(8.0)-9.5	35.1	11.3	16.4	-	
LT295/70R18	129/126Q	E	7.5-(8.5)-10.0	34.5	11.8	16.4	-	
33x12.50R18LT	118Q	E	8.5-(10.0)-11.0	33.0	12.5	18.9	-	

# SUV/LIGHT TRUCK

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

## RENEGADE R/T+ (CONT.)

RUGGED TERRAIN

Ø 18								
33x12.50R18LT	122Q	F	8.5-(10.0)-11.0	33.0	12.5	18.9	-	
35x12.50R18LT	123Q	E	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
35x12.50R18LT	128Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
37x13.50R18LT	124Q	D	8.5-(11.0)	37.0	13.6	20.2	-	

Ø 17								
LT265/65R17	120/117Q	E	7.5-(8.0)-9.5	30.8	10.7	16.4	-	
LT265/70R17	121/118Q	E	7.0-(8.0)-8.5	31.9	10.7	16.4	-	
LT285/70R17	121/118Q	E	7.5-(8.5)-9.0	33.0	11.5	16.4	-	
35x12.50R17LT	121Q	F	8.5-(10.0)-11.0	35.0	12.5	20.2	-	
37x12.50R17LT	131Q	E	8.5-(10.0)-11.0	37.0	12.5	20.2	-	
37x13.50R17LT	121Q	E	8.5-(11.0)	37.0	13.6	20.2	-	

Ø 16								
LT245/75R16	120/116Q	E	6.5-(7.0)-8.0	30.7	9.8	16.4	-	
LT265/70R16	121/118Q	E	7.0-(8.0)-9.0	30.9	10.7	16.4	-	
LT265/75R16	123/120Q	E	7.0-(7.5)-8.0	31.9	10.5	16.4	-	
LT285/75R16	126/123Q	E	7.5-(8.0)-9.0	33.1	11.3	16.4	-	

SIZE	LI./S.R.	LR.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	----------	--------------	----------	----------	-------------	------	--------

## RENEGADE R7 M/T

MUD TERRAIN

Ø 22								
33x12.50R22LT	109Q	E	-	8.5-(10.0)-11.0	32.5	12.5	20.2	-
33x12.50R22LT	114Q	F	-	8.5-(10.0)-11.0	32.5	12.5	20.2	-
35x12.50R22LT	117Q	E	-	8.5-(10.0)-11.0	34.5	12.5	20.2	-
35x12.50R22LT	121Q	F	-	8.5-(10.0)-11.0	34.5	12.5	20.2	-
37x12.50R22LT	123Q	E	OWL	8.5-(10.0)-11.0	36.5	12.5	20.2	-
37x12.50R22LT	127Q	F	OWL	8.5-(10.0)-11.0	36.5	12.5	20.2	-
37x13.50R22LT	123Q	E	OWL	8.5-(11.0)	36.5	13.6	20.2	-

Ø 20								
LT275/65R20	126/123P	E	OWL	7.5-(8.0)-9.5	34.1	11.0	20.2	-
LT315/60R20	125/122Q	E	OWL	8.5-(9.5)-11.0	34.9	12.7	20.2	-
33x12.50R20LT	114Q	E	OWL	8.5-(10.0)-11.0	32.5	12.5	20.2	-
33x12.50R20LT	119Q	F	OWL	8.5-(10.0)-11.0	32.5	12.5	20.2	-
35x12.50R20LT	121Q	E	OWL	8.5-(10.0)-11.0	34.5	12.5	20.2	-
35x12.50R20LT	125Q	F	OWL	8.5-(10.0)-11.0	34.5	12.5	20.2	-
37x12.50R20LT	126Q	E	OWL	8.5-(10.0)-11.0	36.5	12.5	20.2	-
37x13.50R20LT	127Q	E	OWL	8.5-(11.0)	36.5	13.6	20.2	-

Ø 18								
LT275/70R18	125/122Q	E	OWL	7.0-(8.0)-8.5	33.2	11.0	18.9	-
LT285/65R18	125/122Q	E	OWL	8.0-(8.5)-10.0	32.6	11.5	20.2	-
33x12.50R18LT	118Q	E	OWL	8.5-(10.0)-11.0	32.5	12.5	20.2	-
33x12.50R18LT	122Q	F	OWL	8.5-(10.0)-11.0	32.5	12.5	20.2	-
35x12.50R18LT	123Q	E	OWL	8.5-(10.0)-11.0	34.5	12.5	20.2	-
35x12.50R18LT	128Q	F	OWL	8.5-(10.0)-11.0	34.5	12.5	20.2	-

# SUV/LIGHT TRUCK

SIZE	LI./S.R.	LR.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	----------	--------------	----------	----------	-------------	------	--------

## RENEGADE R7 M/T (CONT.)

MUD TERRAIN

Ø 17									
LT265/70R17	121/118Q	E	OWL	7.0-(8.0)-8.5	31.7	10.7	18.9	-	
LT285/70R17	121/118Q	E	OWL	7.5-(8.5)-9.0	32.8	11.5	18.9	-	
LT295/70R17	121/118Q	E	OWL	7.5-(8.5)-10.0	33.3	11.8	18.9	-	
35x12.50R17LT	125Q	E	OWL	8.5-(10.0)-11.0	34.5	12.5	20.2	-	

Ø 16									
LT235/85R16	120/116Q	E	OWL	6.0-(6.5)-7.5	31.7	9.3	18.9	-	
LT245/75R16	120/116Q	E	OWL	6.5-(7.0)-8.0	30.5	9.8	18.9	-	
LT265/75R16	123/120Q	E	OWL	7.0-(7.5)-8.0	31.7	10.5	18.9	-	
LT285/75R16	126/123Q	E	OWL	7.5-(8.0)-9.0	33.4	11.3	18.9	-	
LT315/75R16	121/118Q	D	OWL	8.0-(8.5)-11.0	36.4	12.3	20.2	-	

SIZE	LI./S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	-----	--------------	----------	----------	-------------	------	--------

## RENEGADE R5 M/T

MUD TERRAIN

Ø 17								
LT265/70R17	121/118Q	E	-	7.0-(8.0)-9.0	32.0	11.0	19.0	-

Ø 16								
LT235/85R16	120/116Q	E	-	6.0-(6.5)-7.5	32.0	9.0	19.0	-
LT245/75R16	120/116Q	E	-	6.5-(7.0)-8.0	30.0	10.0	19.0	-
LT265/75R16	123/120Q	E	-	7.0-(7.5)-8.0	32.0	11.0	19.0	-
LT285/75R16	123/120Q	E	-	7.5-(8.0)-9.0	33.0	11.0	19.0	-

Ø 15								
31x10.50R15LT	109Q	C	-	7.0-(8.5)-9.0	31.0	11.0	19.0	-
32x11.50R15LT	113Q	C	-	8.5-(9.0)-10.0	32.0	11.0	19.0	-
33X10.50R15LT	114S	C	-	7.0-7.5-8.0-(8.5)-9.0	32.5	10.5	19.0	-

# VAN/TRAILER

## VAN



ARGONITE RV-4



ARGONITE RVX-1



RLT-71

## TRAILER



ANGLER ST-100



ANGLER RST-22



ARGONITE RV-4T

# VAN

SIZE	LI/SR.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	--------	------	--------------	----------	----------	-------------	------	--------

## ARGONITE RV-4

VAN

Ø 17								
215/60R17C	109/107T	-	6.0-(6.5)-7.5	27.2	8.7	12.3	-	
225/55R17C	109/107H	-	6.0-(7.0)-8.0	26.7	9.1	12.3	-	
235/60R17C	117/115S	-	6.5-(7.0)-8.5	28.1	9.5	12.3	-	

Ø 16								
175/75R16C	101/99R	-	4.5-(5.0)-6.0	26.3	7.0	12.6	-	
185/75R16C	104/102R	-	4.5-(5.5)-6.0	26.9	7.2	13.9	-	
195/60R16C	99/97H	-	5.5-(6.0)-7.0	25.2	7.9	11.3	-	
195/65R16C	104/102T	-	5.5-(6.0)-7.0	26.0	7.9	11.3	-	
195/75R16C	110/108T	-	5.0-(5.5)-6.5	27.5	7.7	13.9	-	
205/65R16C	107/105T	-	5.5-(6.0)-7.5	26.5	8.2	13.9	-	
205/75R16C	113/111R	-	5.0-(5.5)-7.0	28.1	8.0	13.9	-	
215/60R16C	103/101T	-	6.0-(6.5)-7.5	26.1	8.7	13.9	-	
215/65R16C	109/107T	-	6.0-(6.5)-7.5	27.0	8.7	13.9	-	
215/70R16C	108/106T	-	5.5-(6.5)-7.0	27.8	8.7	13.9	-	
215/75R16C	116/114R	-	5.5-(6.0)-7.0	28.7	8.5	13.9	-	
225/60R16C	111/109T	-	6.0-(6.5)-8.0	26.5	9.1	13.9	-	
225/65R16C	112/110T	-	6.0-(6.5)-8.0	27.5	9.0	13.9	-	
225/75R16C	121/120R	-	(6.0)-7.5	29.3	8.8	13.9	-	
235/65R16C	115/113T	-	6.5-(7.0)-8.5	28.0	9.4	13.9	-	
235/65R16C	121/119R	-	6.5-(7.0)-8.5	28.0	9.4	13.9	-	

Ø 15								
195/65R15C	95T	XL	5.5-(6.0)-7.0	26.0	7.9	11.3	-	
195/65R15C	98/96T	-	5.5-(6.0)-7.0	26.0	7.9	11.3	-	
195/70R15C	104/102R	-	5.0-(6.0)-6.5	25.8	7.9	13.9	-	
195R15C	106/104R	-	5.0-(5.5)-6.5	27.1	8.0	12.6	-	
205/65R15C	102/100T	-	5.5-(6.0)-7.5	25.5	8.2	12.6	-	
205/70R15C	106/104T	-	5.0-(6.0)-7.0	26.3	8.2	13.9	-	
215/65R15C	104/102T	-	6.0-(6.5)-7.5	26.0	8.7	12.6	-	
215/70R15C	109/107T	-	5.5-(6.5)-7.0	26.9	8.7	13.9	-	
225/70R15C	112/110S	-	6.0-(6.5)-7.5	27.4	9.0	13.9	-	

Ø 14								
175/65R14C	90/88T	-	(5.0)-6.0	23.0	7.0	11.0	-	
175/70R14C	95/93T	-	4.5-(5.0)-6.0	23.7	7.0	11.3	-	

Ø 12								
145R12C	86/84R	-	3.5-(4.0)-5.0	21.1	5.7	11.3	-	
155R12C	88/86R	-	4.0-(4.5)-5.0	21.7	6.2	11.3	-	

## ARGONITE RVX-1

VAN

Ø 16								
195/65R16C	106/104R	D	5.5-(6.0)-7.0	26.0	8.1	10.5	-	
205/65R16C	112/110R	D	5.5-(6.0)-7.5	26.4	8.4	10.3	-	
225/65R16C	112/110R	D	6.0-(6.5)-8.0	27.4	9.1	10.5	-	
235/65R16C	121/119R	E	6.5-(7.0)-8.5	28.0	9.7	10.5	-	

Ø 15								
195/70R15C	104/102R	D	5.0-(6.0)-6.5	26.0	8.1	10.5	-	

# VAN/TRAILER

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

## ARGONITE RVX-1 (CONT.)

VAN

Ø 15								
205/70R15C	106/104R	D		5.0-(6.0)-7.0	26.4	8.6	10.3	-
225/70R15C	112/110R	D		6.0-(6.5)-7.5	27.4	9.1	10.5	-

Ø 14								
185R14C	102/100R	D		4.5-(5.0)-6.0	25.7	7.3	11.6	-

SIZE	LI/S.R.	LR.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	----------	--------------	----------	----------	-------------	------	--------

## RLT-71

VAN

Ø 16								
205R16C	110/108S	D	-	5.0-(5.5)-7.0	29.0	8.2	13.2	-
205R16C	110/108S	D	WSW	5.0-(5.5)-7.0	29.0	8.2	13.2	-

Ø 15								
195/80R15C	107/105Q	D	-	5.0-(5.5)-6.5	27.1	7.8	11.3	-
195R15C	106/104Q	D	-	5.0-(5.5)-6.5	27.1	7.8	11.3	-
195R15C	106/104Q	D	WSW	5.0-(5.5)-6.5	27.1	7.8	11.3	-
225/70R15C	112/110R	D	-	6.0-(6.5)-7.5	27.4	9.0	12.6	-
225/70R15C	112/110R	D	WSW	6.0-(6.5)-7.5	27.4	9.0	12.6	-

Ø 14								
185R14C	102/100Q	D	-	4.5-(5.0)-6.0	25.6	7.4	11.3	-
185R14C	102/100Q	D	WSW	4.5-(5.0)-6.0	25.6	7.4	11.3	-
195R14C	106/104Q	D	-	5.0-(5.5)-6.5	26.2	7.8	11.3	-
195R14C	106/104Q	D	WSW	5.0-(5.5)-6.5	26.2	7.8	11.3	-
205/75R14C	109/107R	D	-	5.0-(5.5)-7.0	26.1	8.0	11.3	-
205/75R14C	109/107R	D	WSW	5.0-(5.5)-7.0	26.1	8.0	11.3	-
205R14C	109/107S	D	-	5.5-(6.0)-6.5	26.9	8.2	13.2	-
205R14C	109/107S	D	WSW	5.5-(6.0)-6.5	26.9	8.2	13.2	-

Ø 12								
165/70R12C	90/88S	D	RWL	4.0-(5.0)-5.5	21.1	6.7	7.9	-

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

## ANGLER ST-100

TRAILER

Ø 16								
ST235/80R16	124/120M	E		6.0-(6.5)-8.0	9.3	30.8	10.3	-
ST235/85R16	125/121M	E		6.0-(6.5)-7.5	9.3	31.7	10.3	-

Ø 15								
ST205/75R15	107/102M	D		5.0-(5.5)-7.0	8.0	27.1	9.8	-
ST225/75R15	117/112M	E		(6.0)-7.5	8.8	28.3	10.3	-

Ø 14								
ST205/75R14	105/101M	D		5.0-(5.5)-7.0	8.0	26.1	9.8	-
ST215/75R14	102/98M	C		5.5-(6.0)-7.0	8.5	26.7	9.8	-

# TRAILER

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

## ANGLER ST-100

TRAILER

Ø 13								
ST175/80R13	91/87M	C		4.5-(5.0)-6.0	7.0	24.0	9.4	-

## ANGLER RST-22

TRAILER

Ø 16								
ST235/80R16	123/119L	E		6.0-(6.5)-8.0	30.8	9.3	10.1	-
ST235/85R16	128/124L	F		6.0-(6.5)-7.5	31.7	9.3	10.1	-

Ø 15								
ST205/75R15	107/102L	D		5.0-(5.5)-7.0	27.1	8.0	10.1	-
ST225/75R15	117/112L	E		(6.0)-7.5	28.3	8.8	10.1	-

Ø 14								
ST205/75R14	105/101L	D		5.0-(5.5)-7.0	26.1	8.0	9.8	-
ST215/75R14	102/98L	C		5.5-(6.0)-7.0	26.7	8.5	8.8	-

Ø 13								
ST175/80R13	91/87L	C		4.5-(5.0)-6.0	24.0	7.0	8.8	-

## ARGONITE RV-4T

TRAILER

Ø 15								
225/70R15C	116N	E		6.0-(6.5)-7.5	27.4	8.9	9.4	-

Ø 14								
175R14C	99/98N	D		4.5-(5.0)-5.5	25.0	7.0	9.4	-
185R14C	104/102N	D		4.5-(5.0)-6.0	25.6	7.4	9.4	-
195/70R14C	104/102N	E		5.0-(5.5)-6.0	24.8	7.9	9.4	-
195/70R14C	96N	C		5.0-(5.5)-6.0	24.8	7.9	9.4	-
195R14C	108N	E		5.0-(5.5)-6.5	26.2	7.8	9.4	-

Ø 13								
155R13C	91/89N	D		4.0-(4.5)-5.0	22.8	6.2	9.4	-
155R13C	84N	C		4.0-(4.5)-5.0	22.8	6.2	9.4	-
165R13C	94/92R	D		4.0-(4.5)-5.0	23.5	6.6	9.4	-
185/70R13C	106/104N	F		5.0-(5.5)-6.0	23.2	7.4	9.4	-
195/50R13C	104/101N	F		5.5-(6.0)-7.0	20.7	7.9	9.4	-

Ø 12								
155/70R12C	104/102N	F		4.0-(4.5)-5.0	20.6	6.2	9.4	-

# ALL WEATHER

## 4 SEASON



DIMAX 4 SEASON

## 4 SEASON VAN



ARGONITE 4 SEASON (RV-4S)

# RUNFLAT | CAR/CUV/SUV

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	------	--------------	----------	----------	-------------	------	--------

## DIMAX 4 SEASON | RUNFLAT

4 SEASON

Ø 20								
255/45RF20	105W	XL, RFT	8.0-(8.5)-9.5	29.1	10.0	10.7	360 A A	
Ø 19								
235/55RF19	105W	XL, RFT	6.5-(7.5)-8.5	29.2	9.4	10.7	360 A A	
255/40RF19	100W	XL, RFT	8.5-(9.0)-10.0	27.0	10.4	10.7	360 A A	
255/50RF19	107W	XL, RFT	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
255/55RF19	111W	XL, RFT	7.0-(8.0)-9.0	30.0	10.4	10.7	360 A A	
Ø 18								
225/40RF18	92Y	XL, RFT	7.5-(8.0)-9.0	25.1	9.1	10.7	360 A A	
225/45RF18	95Y	XL, RFT	7.0-(7.5)-8.5	26.0	9.1	10.7	360 A A	
225/60RF18	104W	XL, RFT	6.0-(6.5)-8.0	28.6	9.1	10.7	360 A A	
235/50RF18	101W	XL, RFT	6.5-(7.5)-8.5	27.3	9.6	10.7	360 A A	
235/60RF18	107W	XL, RFT	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
245/40RF18	97W	XL, RFT	8.0-(8.5)-9.5	25.7	9.6	10.7	360 A A	
245/45RF18	100W	XL, RFT	7.5-(8.0)-9.0	26.7	9.6	10.7	360 A A	
245/50RF18	100W	XL, RFT	7.0-(7.5)-8.5	27.7	10.0	10.7	360 A A	
255/55RF18	109V	XL, RFT	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
Ø 17								
205/45RF17	88W	XL, RFT	6.5-(7.0)-7.5	24.3	8.1	10.7	360 A A	
205/50RF17	93W	XL, RFT	5.5-(6.5)-7.5	25.1	8.4	10.7	360 A A	
205/55RF17	95W	XL, RFT	5.5-(6.5)-7.5	25.9	8.4	10.7	360 A A	
225/45RF17	94W	XL, RFT	7.0-(7.5)-8.5	25.0	8.9	10.7	360 A A	
225/50RF17	98W	XL, RFT	6.0-(7.0)-8.0	25.9	9.2	10.7	360 A A	
225/55RF17	101W	XL, RFT	6.0-(7.0)-8.0	26.8	9.2	10.7	360 A A	
225/60RF17	99V	RFT	6.0-(6.5)-8.0	27.6	9.0	10.7	360 A A	
Ø 16								
195/55RF16	91W	XL, RFT	5.5-(6.0)-7.0	24.4	7.9	10.7	360 A A	
205/55RF16	94W	XL, RFT	5.5-(6.5)-7.5	24.9	8.4	10.7	360 A A	
205/60RF16	96W	XL, RFT	5.5-(6.0)-7.5	25.7	8.2	10.7	360 A A	

## DIMAX 4 SEASON

4 SEASON

Ø 21								
295/35R21	107W	XL	10.0-(10.5)-11.5	29.1	11.9	10.7	360 A A	
Ø 20								
255/45R20	105W	XL	8.0-(8.5)-9.5	29.1	10.0	10.7	360 A A	
255/50R20	109W	XL	7.0-(8.0)-9.0	30.1	10.4	10.7	360 A A	
Ø 19								
235/35R19	91W	XL	8.0-(8.5)-9.5	25.5	9.4	10.7	360 A A	
235/55R19	105W	XL	6.5-(7.5)-8.5	29.2	9.4	10.7	360 A A	
255/40R19	100W	XL	8.5-(9.0)-10.0	27.0	10.4	10.7	360 A A	
255/50R19	107W	XL	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
255/55R19	111W	XL	7.0-(8.0)-9.0	30.0	10.4	10.7	360 A A	

SIZE	LI/S.R.	LR	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>DIMAX 4 SEASON (CONT.)</b>								
4 SEASON								
<b>Ø 18</b>								
215/55R18	99V	XL	6.0-(7.0)-7.5	27.3	8.7	10.7	360 A A	
225/40R18	92W	XL	7.5-(8.0)-9.0	25.1	9.1	10.7	360 A A	
225/45R18	95W	XL	7.0-(7.5)-8.5	26.0	9.1	10.7	360 A A	
225/55R18	102V	XL	6.0-(7.0)-8.0	27.7	9.1	10.7	360 A A	
225/60R18	104W	XL	6.0-(6.5)-8.0	28.6	9.1	10.7	360 A A	
235/50R18	101W	XL	6.5-(7.5)-8.5	27.3	9.6	10.7	360 A A	
235/55R18	104V	XL	6.5-(7.5)-8.5	28.1	9.6	10.7	360 A A	
235/60R18	107W	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
245/40R18	97W	XL	8.0-(8.5)-9.5	25.7	9.6	10.7	360 A A	
245/45R18	100W	XL	7.5-(8.0)-9.0	26.7	9.6	10.7	360 A A	
245/50R18	104W	XL	7.0-(7.5)-8.5	27.7	10.0	10.7	360 A A	
255/55R18	109W	XL	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
<b>Ø 17</b>								
205/45R17	88W	XL	6.5-(7.0)-7.5	24.3	8.1	10.7	360 A A	
205/50R17	93W	XL	5.5-(6.5)-7.5	25.1	8.4	10.7	360 A A	
205/55R17	95V	XL	5.5-(6.5)-7.5	25.9	8.4	10.7	360 A A	
215/45R17	91W	XL	(7.0)-8.0	24.6	8.4	10.7	360 A A	
215/50R17	95W	XL	6.0-(7.0)-7.5	25.5	8.5	10.7	360 A A	
215/55R17	98W	XL	6.0-(7.0)-7.5	26.3	8.9	10.7	360 A A	
215/60R17	100H	XL	6.0-(6.5)-7.5	27.2	8.7	10.7	360 A A	
215/65R17	103V	XL	6.0-(6.5)-7.5	28.0	8.7	10.7	360 A A	
225/45R17	94W	XL	7.0-(7.5)-8.5	25.0	8.9	10.7	360 A A	
225/50R17	98W	XL	6.0-(7.0)-8.0	25.9	9.2	10.7	360 A A	
225/55R17	101W	XL	6.0-(7.0)-8.0	26.8	9.2	10.7	360 A A	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	10.7	360 A A	
225/65R17	106V	XL	6.0-(6.5)-8.0	28.5	9.0	10.7	360 A A	
235/45R17	97W	XL	7.5-(8.0)-9.0	25.4	9.3	10.7	360 A A	
235/55R17	103W	XL	6.5-(7.5)-8.5	27.2	9.6	10.7	360 A A	
235/65R17	108V	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
<b>Ø 16</b>								
195/55R16	91V	XL	5.5-(6.0)-7.0	24.4	7.9	10.7	360 A A	
205/55R16	94V	XL	5.5-(6.5)-7.5	24.9	8.4	10.7	360 A A	
205/60R16	96V	XL	5.5-(6.0)-7.5	25.7	8.2	10.7	360 A A	
215/55R16	97V	XL	6.0-(7.0)-7.5	25.3	8.9	10.7	360 A A	
215/60R16	99V	XL	6.0-(6.5)-7.5	26.1	8.7	10.7	360 A A	
215/65R16	102V	XL	6.0-(6.5)-7.5	27.0	8.7	10.7	360 A A	
215/70R16	100H	-	5.5-(6.5)-7.0	27.9	8.7	10.7	360 A A	
225/55R16	99V	XL	6.0-(7.0)-8.0	25.7	9.2	10.7	360 A A	
225/70R16	103H	-	6.0-(6.5)-7.5	28.4	9.0	11.3	360 A A	
235/60R16	100H	-	6.5-(7.0)-8.5	27.1	9.4	11.3	360 A A	
235/70R16	106H	-	6.0-(7.0)-8.0	29.0	9.4	11.3	360 A A	
<b>Ø 15</b>								
155/60R15	74V	-	(4.5)-5.5	22.3	6.2	10.5	360 A A	
165/65R15	81H	-	4.5-(5.0)-6.0	23.4	6.7	10.5	360 A A	
175/55R15	77V	-	5.0-(5.5)-6.0	22.6	7.2	10.5	360 A A	
175/65R15	88H	XL	(5.0)-6.0	24.0	7.0	10.5	360 A A	

SIZE	LI/S.R.	LR	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>DIMAX 4 SEASON (CONT.)</b>								
4 SEASON								
<b>Ø 15</b>								
185/55R15	86V	XL	5.0-(6.0)-6.5	23.0	7.6	10.7	360 A A	
185/60R15	88V	XL	5.0-(5.5)-6.5	23.7	7.4	10.7	360 A A	
185/65R15	92V	XL	5.0-(5.5)-6.5	24.4	7.4	10.7	360 A A	
195/50R15	86V	XL	5.5-(6.0)-7.0	22.7	7.9	10.7	360 A A	
195/55R15	85V	-	5.5-(6.0)-7.0	23.4	7.9	10.7	360 A A	
195/60R15	88V	-	5.5-(6.0)-7.0	24.2	7.9	10.7	360 A A	
195/65R15	95V	XL	5.5-(6.0)-7.0	25.0	7.9	10.7	360 A A	
<b>Ø 14</b>								
155/65R14	75H	-	(4.5)-5.5	22.0	6.2	10.5	360 A A	
165/65R14	79H	-	4.5-(5.0)-6.0	22.4	6.7	10.5	360 A A	
165/70R14	81H	-	4.0-(5.0)-5.5	23.1	6.7	10.5	360 A A	
175/65R14	82H	-	(5.0)-6.0	23.0	7.0	10.5	360 A A	
175/70R14	88H	XL	4.5-(5.0)-6.0	23.7	7.0	10.5	360 A A	
185/60R14	82H	-	5.0-(5.5)-6.5	22.8	7.4	10.7	360 A A	
<b>ARGONITE 4 SEASON</b>								
4 SEASON VAN								
<b>Ø 17</b>								
215/60R17C	109/107T	-	6.0-(6.5)-7.5	27.2	8.7	12.0	-	
225/55R17C	109/107H	-	6.0-(7.0)-8.0	26.8	9.0	12.1	-	
235/60R17C	117/115R	-	6.5-(7.0)-8.5	28.1	9.4	12.2	-	
<b>Ø 16</b>								
195/65R16C	104/102R	-	5.5-(6.0)-7.0	26.0	7.9	12.0	-	
195/75R16C	107/105R	-	5.0-(5.5)-6.5	27.5	7.7	12.0	-	
195/75R16C	110/108T	-	5.0-(5.5)-6.5	27.5	7.7	12.0	-	
205/65R16C	107/105T	-	5.5-(6.0)-7.5	26.5	8.2	12.0	-	
215/65R16C	109/107T	-	6.0-(6.5)-7.5	27.0	8.7	12.0	-	
225/65R16C	112/110S	-	6.0-(6.5)-8.0	27.5	9.0	12.1	-	
235/65R16C	115/113R	-	6.5-(7.0)-8.5	28.0	9.4	12.2	-	
235/65R16C	121/119R	-	6.5-(7.0)-8.5	28.0	9.4	12.2	-	
<b>Ø 15</b>								
195/70R15C	104/102R	-	5.0-(6.0)-6.5	25.8	7.9	12.0	-	
225/70R15C	112/110R	-	6.0-(6.5)-7.5	27.4	9.0	12.1	-	

# WINTER

## ALPINE



DIMAX ALPINE



DIMAX WINTER SPORT

## ALPINE VAN



ARGONITE ALPINE

## NORDIC/NORDIC STUDDED



DIMAX ICE



DIMAX ICE LOCK

# CAR/CUV/SUV

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
<b>DIMAX ALPINE</b>								
<b>Ø 20</b>								
255/45R20	105V	XL	8.0-(8.5)-9.5	29.1	10.0	10.7	-	ALPINE
275/45R20	110V	XL	8.5-(9.0)-10.5	29.8	10.7	10.7	-	
<b>Ø 19</b>								
225/35R19	88V	XL	7.5-(8.0)-9.0	25.2	9.1	10.7	-	
235/35R19	91V	XL	8.0-(8.5)-9.5	25.5	9.5	10.7	-	
235/55R19	105V	XL	6.5-(7.5)-8.5	29.2	9.6	10.7	-	
245/40R19	98V	XL	8.0-(8.5)-9.5	26.7	9.8	10.7	-	
255/35R19	96V	XL	8.5-(9.0)-10.0	26.0	10.2	10.7	-	
255/50R19	107V	XL	7.0-(8.0)-9.0	29.1	10.4	10.7	-	
255/55R19	111V	XL	7.0-(8.0)-9.0	30.0	10.4	10.7	-	
<b>Ø 18</b>								
215/50R18	96V	XL	6.0-(7.0)-7.5	26.5	8.9	11.0	-	
215/55R18	99V	XL	6.0-(7.0)-7.5	27.3	8.9	10.7	-	
225/40R18	92V	XL	7.5-(8.0)-9.0	25.1	9.1	10.7	-	
225/45R18	95V	XL	7.0-(7.5)-8.5	25.9	8.9	10.7	-	
225/55R18	102V	XL	6.0-(7.0)-8.0	27.8	9.2	10.7	-	
225/60R18	104V	XL	6.0-(6.5)-8.0	28.6	9.0	10.7	-	
235/45R18	98V	XL	7.5-(8.0)-9.0	26.3	9.3	10.7	-	
235/50R18	101V	XL	6.5-(7.5)-8.5	27.3	9.6	10.7	-	
235/55R18	104V	XL	6.5-(7.5)-8.5	28.1	9.6	10.7	-	
235/60R18	107V	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	-	
245/40R18	97V	XL	8.0-(8.5)-9.5	25.7	9.8	10.7	-	
245/45R18	100V	XL	7.5-(8.0)-9.0	26.7	9.6	10.7	-	
255/55R18	109V	XL	7.0-(8.0)-9.0	29.0	10.4	10.7	-	
<b>Ø 17</b>								
205/50R17	93V	XL	5.5-(6.5)-7.5	25.1	8.4	10.7	-	
205/55R17	95V	XL	5.5-(6.5)-7.5	25.9	8.4	10.7	-	
215/55R17	94V	XL	6.0-(7.0)-7.5	26.3	8.9	10.7	-	
215/60R17	100V	XL	6.0-(6.5)-7.5	27.2	8.7	10.7	-	
225/45R17	91V	-	7.0-(7.5)-8.5	25.0	8.9	10.7	-	
225/45R17	94V	XL	7.0-(7.5)-8.5	25.0	8.9	10.7	-	
225/50R17	94V	-	6.0-(7.0)-8.0	25.9	9.2	10.7	-	
225/50R17	98V	XL	6.0-(7.0)-8.0	25.9	9.2	10.7	-	
225/55R17	101V	XL	6.0-(7.0)-8.0	26.8	9.2	10.7	-	
225/55R17	97V	-	6.0-(7.0)-8.0	26.8	9.2	10.7	-	
225/60R17	103V	XL	6.0-(6.5)-8.0	27.6	9.0	10.7	-	
225/65R17	106H	XL	6.0-(6.5)-8.0	28.5	9.0	10.7	-	
<b>Ø 16</b>								
195/55R16	91H	XL	5.5-(6.0)-7.0	24.4	7.9	10.7	-	
205/55R16	91H	-	5.5-(6.5)-7.5	24.9	8.4	10.7	-	
205/55R16	94H	XL	5.5-(6.5)-7.5	24.9	8.4	10.7	-	
205/60R16	92H	-	5.5-(6.0)-7.5	25.7	8.2	10.7	-	
205/60R16	96H	XL	5.5-(6.0)-7.5	25.7	8.2	10.7	-	
215/55R16	93H	-	6.0-(7.0)-7.5	25.3	8.9	10.7	-	
215/55R16	97H	XL	6.0-(7.0)-7.5	25.3	8.9	10.7	-	

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	------	--------------	----------	----------	-------------	------	--------

**DIMAX ALPINE (CONT.)**

ALPINE

Ø 16								
215/60R16	99H	XL	6.0-(6.5)-7.5	26.1	8.7	10.7	-	
215/65R16	102H	XL	6.0-(6.5)-7.5	27.0	8.7	10.7	-	
225/55R16	99H	XL	6.0-(7.0)-8.0	25.7	9.2	10.7	-	
Ø 15								
185/60R15	88T	XL	5.0-(5.5)-6.5	23.7	7.4	10.7	-	
185/65R15	88T	-	5.0-(5.5)-6.5	24.4	7.4	10.7	-	
185/65R15	92T	XL	5.0-(5.5)-6.5	24.4	7.4	10.7	-	
195/55R15	89H	XL	5.5-(6.0)-7.0	23.4	7.9	10.7	-	
195/65R15	91H	-	5.5-(6.0)-7.0	25.0	7.9	10.7	-	
195/65R15	91T	-	5.5-(6.0)-7.0	25.0	7.9	10.7	-	
195/65R15	95H	XL	5.5-(6.0)-7.0	25.0	7.9	10.7	-	

**DIMAX WINTER SPORT | RUN-FLAT**

ALPINE

Ø 20								
255/45RF20	105V	XL, RFT	8.0-(8.5)-9.5	29.1	10.0	10.7	360 A A	
Ø 19								
235/55RF19	105V	XL, RFT	6.5-(7.5)-8.5	29.2	9.4	10.7	360 A A	
255/40RF19	100V	XL, RFT	8.5-(9.0)-10.0	27.0	10.4	10.7	360 A A	
255/50RF19	107V	XL, RFT	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
255/55RF19	111V	XL, RFT	7.0-(8.0)-9.0	30.0	10.4	10.7	360 A A	
Ø 18								
225/40RF18	92V	XL, RFT	7.5-(8.0)-9.0	25.1	9.1	10.7	360 A A	
225/45RF18	95V	XL, RFT	7.0-(7.5)-8.5	26.0	9.1	10.7	360 A A	
225/60RF18	104V	XL, RFT	6.0-(6.5)-8.0	28.6	9.1	10.7	360 A A	
235/60RF18	107V	XL, RFT	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
245/40RF18	97V	XL, RFT	8.0-(8.5)-9.5	25.7	9.6	10.7	360 A A	
245/45RF18	100V	XL, RFT	7.5-(8.0)-9.0	26.7	9.6	10.7	360 A A	
245/50RF18	100H	RFT	7.0-(7.5)-8.5	27.7	10.0	10.7	360 A A	
255/55RF18	109V	XL, RFT	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
Ø 17								
205/45RF17	88V	XL, RFT	6.5-(7.0)-7.5	24.3	8.1	10.7	360 A A	
205/50RF17	93V	XL, RFT	5.5-(6.5)-7.5	25.1	8.4	10.7	360 A A	
205/55RF17	95V	XL, RFT	5.5-(6.5)-7.5	25.9	8.4	10.7	360 A A	
225/45RF17	91H	RFT	7.0-(7.5)-8.5	25.0	8.9	10.7	360 A A	
225/50RF17	98V	XL, RFT	6.0-(7.0)-8.0	25.9	9.2	10.7	360 A A	
225/55RF17	101V	XL, RFT	6.0-(7.0)-8.0	26.8	9.2	10.7	360 A A	
225/60RF17	99H	RFT	6.0-(6.5)-8.0	27.6	9.0	10.7	360 A A	
Ø 16								
195/55RF16	91V	XL, RFT	5.5-(6.0)-7.0	24.4	7.9	10.7	360 A A	
205/55RF16	94V	XL, RFT	5.5-(6.5)-7.5	24.9	8.4	10.7	360 A A	
205/60RF16	96V	XL, RFT	5.5-(6.0)-7.5	25.7	8.2	10.7	360 A A	

SIZE	LI/S.R.	L.R.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	------	--------------	----------	----------	-------------	------	--------

**DIMAX WINTER SPORT**

ALPINE

Ø 21								
295/35R21	107V	XL	10.0-(10.5)-11.5	29.1	11.9	10.7	360 A A	
Ø 20								
255/45R20	105V	XL	8.0-(8.5)-9.5	29.1	10.0	10.7	360 A A	
255/50R20	109V	XL	7.0-(8.0)-9.0	30.1	10.4	10.7	360 A A	
Ø 19								
235/35R19	91V	XL	8.0-(8.5)-9.5	25.5	9.4	10.7	360 A A	
235/55R19	105V	XL	6.5-(7.5)-8.5	29.2	9.4	10.7	360 A A	
255/40R19	100V	XL	8.5-(9.0)-10.0	27.0	10.4	10.7	360 A A	
255/50R19	107V	XL	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
255/55R19	111V	XL	7.0-(8.0)-9.0	30.0	10.4	10.7	360 A A	
Ø 18								
215/55R18	99H	XL	6.0-(7.0)-7.5	27.3	8.7	10.7	360 A A	
225/40R18	92V	XL	7.5-(8.0)-9.0	25.1	9.1	10.7	360 A A	
225/45R18	95W	XL	7.0-(7.5)-8.5	26.0	9.1	10.7	360 A A	
225/55R18	102H	XL	6.0-(7.0)-8.0	27.7	9.1	10.7	360 A A	
225/60R18	104V	XL	6.0-(6.5)-8.0	28.6	9.1	10.7	360 A A	
235/50R18	101V	XL	6.5-(7.5)-8.5	27.3	9.6	10.7	360 A A	
235/55R18	104H	XL	6.5-(7.5)-8.5	28.1	9.6	10.7	360 A A	
235/60R18	107V	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
245/40R18	97V	XL	8.0-(8.5)-9.5	25.7	9.6	10.7	360 A A	
245/45R18	100V	XL	7.5-(8.0)-9.0	26.7	9.6	10.7	360 A A	
245/50R18	104V	XL	7.0-(7.5)-8.5	27.7	10.0	10.7	360 A A	
255/55R18	109V	XL	7.0-(8.0)-9.0	29.0	10.4	10.7	360 A A	
Ø 17								
205/45R17	88V	XL	6.5-(7.0)-7.5	24.3	8.1	10.7	360 A A	
205/50R17	93V	XL	5.5-(6.5)-7.5	25.1	8.4	10.7	360 A A	
205/55R17	95V	XL	5.5-(6.5)-7.5	25.9	8.4	10.7	360 A A	
215/45R17	91V	XL	(7.0)-8.0	24.6	8.4	10.7	360 A A	
215/50R17	95V	XL	6.0-(7.0)-7.5	25.5	8.5	10.7	360 A A	
215/55R17	98V	XL	6.0-(7.0)-7.5	26.3	8.9	10.7	360 A A	
215/60R17	100H	XL	6.0-(6.5)-7.5	27.2	8.7	10.7	360 A A	
215/65R17	103H	XL	6.0-(6.5)-7.5	28.0	8.7	10.7	360 A A	
225/45R17	94V	XL	7.0-(7.5)-8.5	25.0	8.9	10.7	360 A A	
225/50R17	98V	XL	6.0-(7.0)-8.0	25.9	9.2	10.7	360 A A	
225/55R17	101V	XL	6.0-(7.0)-8.0	26.8	9.2	10.7	360 A A	
225/60R17	103H	XL	6.0-(6.5)-8.0	27.6	9.0	10.7	360 A A	
225/65R17	106H	XL	6.0-(6.5)-8.0	28.5	9.0	10.7	360 A A	
235/45R17	97V	XL	7.5-(8.0)-9.0	25.4	9.3	10.7	360 A A	
235/55R17	103H	XL	6.5-(7.5)-8.5	27.2	9.6	10.7	360 A A	
235/65R17	108H	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	360 A A	
Ø 16								
195/55R16	91H	XL	5.5-(6.0)-7.0	24.4	7.9	10.7	360 A A	
205/55R16	91H	-	5.5-(6.5)-7.5	24.9	8.4	10.7	360 A A	



SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX WINTER SPORT (CONT.)**

ALPINE

Ø 16								
205/55R16	94V	XL	5.5-(6.5)-7.5	24.9	8.4	10.7	360 A A	
205/60R16	96H	XL	5.5-(6.0)-7.5	25.7	8.2	10.7	360 A A	
215/55R16	97V	XL	6.0-(7.0)-7.5	25.3	8.9	10.7	360 A A	
215/60R16	99H	XL	6.0-(6.5)-7.5	26.1	8.7	10.7	360 A A	
215/65R16	102H	XL	6.0-(6.5)-7.5	27.0	8.7	10.7	360 A A	
215/70R16	100H	-	5.5-(6.5)-7.0	27.9	8.7	10.7	360 A A	
225/55R16	99H	XL	6.0-(7.0)-8.0	25.7	9.2	10.7	360 A A	
225/70R16	107H	XL	6.0-(6.5)-7.5	28.4	9.0	11.3	360 A A	
235/60R16	100H	-	6.5-(7.0)-8.5	27.1	9.4	11.3	360 A A	
235/70R16	106H	-	6.0-(7.0)-8.0	29.0	9.4	11.3	360 A A	

Ø 15								
175/65R15	88H	XL	(5.0)-6.0	24.0	7.0	10.5	360 A A	
185/55R15	86V	XL	5.0-(6.0)-6.5	23.0	7.6	10.7	360 A A	
185/65R15	92V	XL	5.0-(5.5)-6.5	24.4	7.4	10.7	360 A A	
195/50R15	86V	XL	5.5-(6.0)-7.0	22.7	7.9	10.7	360 A A	
195/60R15	88V	-	5.5-(6.0)-7.0	24.2	7.9	10.7	360 A A	

Ø 14								
165/65R14	79H	-	4.5-(5.0)-6.0	22.4	6.7	10.5	360 A A	
165/70R14	81H	-	4.0-(5.0)-5.5	23.1	6.7	10.5	360 A A	
175/65R14	82H	-	(5.0)-6.0	23.0	7.0	10.5	360 A A	
175/70R14	88H	XL	4.5-(5.0)-6.0	23.7	7.0	10.5	360 A A	
185/60R14	82H	-	5.0-(5.5)-6.5	22.8	7.4	10.7	360 A A	

**VAN**

**ARGONITE ALPINE**

ALPINE VAN

Ø 17								
215/60R17C	109/107T	-	6.0-(6.5)-7.5	27.2	8.7	13.0	-	
225/55R17C	109/107T	-	6.0-(7.0)-8.0	26.8	9.2	13.0	-	
235/60R17C	117/115R	-	6.5-(7.0)-8.5	28.1	9.4	13.0	-	

Ø 16								
185/75R16C	104/102R	-	4.5-(5.5)-6.0	26.9	7.2	13.0	-	
195/65R16C	104/102T	-	5.5-(6.0)-7.0	26.0	7.9	13.0	-	
195/75R16C	110/108R	-	5.0-(5.5)-6.5	27.5	7.7	13.0	-	
205/65R16C	107/105T	-	5.5-(6.0)-7.5	26.5	8.2	13.0	-	
215/65R16C	109/107R	-	6.0-(6.5)-7.5	27.0	8.7	13.0	-	
235/65R16C	115/113R	-	6.5-(7.0)-8.5	28.0	9.4	13.0	-	
235/65R16C	121/119R	-	6.5-(7.0)-8.5	28.0	9.4	13.0	-	

SIZE	LI/S.R.	LR.	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	---------	-----	--------------	----------	----------	-------------	------	--------

**DIMAX ICE**

NORDIC

Ø 19								
235/35R19	91T	XL	8.0-(8.5)-9.5	25.5	9.5	10.7	-	
235/55R19	105T	XL	6.5-(7.5)-8.5	29.2	9.6	10.7	-	

Ø 18								
225/40R18	92T	XL	7.5-(8.0)-9.0	25.1	9.1	10.7	-	
225/45R18	95T	XL	7.0-(7.5)-8.5	25.9	8.9	10.7	-	
225/55R18	102T	XL	6.0-(7.0)-8.0	27.8	9.2	10.7	-	
235/50R18	101T	XL	6.5-(7.5)-8.5	27.3	9.6	10.7	-	
235/55R18	104T	XL	6.5-(7.5)-8.5	28.1	9.6	10.7	-	
235/60R18	107T	XL	6.5-(7.0)-8.5	29.1	9.4	10.7	-	

Ø 17								
215/50R17	95T	XL	6.0-(7.0)-7.5	25.5	8.9	10.7	-	
215/55R17	98T	XL	6.0-(7.0)-7.5	26.3	8.9	10.7	-	
215/60R17	100T	XL	6.0-(6.5)-7.5	27.2	8.7	10.7	-	
225/45R17	94T	XL	7.0-(7.5)-8.5	25.0	8.9	10.7	-	
225/50R17	98T	XL	6.0-(7.0)-8.0	25.9	9.2	10.7	-	
225/55R17	101T	XL	6.0-(7.0)-8.0	26.8	9.2	10.7	-	
225/60R17	103T	XL	6.0-(6.5)-8.0	27.6	9.0	10.7	-	
225/65R17	106T	XL	6.0-(6.5)-8.0	28.5	9.0	10.7	-	
235/55R17	103T	XL	6.5-(7.5)-8.5	27.2	9.6	10.7	-	

Ø 16								
205/55R16	94T	XL	5.5-(6.5)-7.5	24.9	8.4	10.7	-	
205/60R16	96T	XL	5.5-(6.0)-7.5	25.7	8.2	10.7	-	
215/55R16	97T	XL	6.0-(7.0)-7.5	25.3	8.9	10.7	-	
215/60R16	99T	XL	6.0-(6.5)-7.5	26.1	8.7	10.7	-	
215/65R16	102T	XL	6.0-(6.5)-7.5	27.0	8.7	10.7	-	

Ø 15								
195/65R15	95T	XL	5.5-(6.0)-7.0	25.0	7.9	11.0	-	

**DIMAX ICE LOCK**

NORDIC STUDDED

Ø 19								
235/35R19	91T	XL	8.0-(8.5)-9.5	25.5	9.5	12.0	-	

Ø 18								
225/40R18	92T	XL	7.5-(8.0)-9.0	25.1	9.1	12.0	-	

Ø 17								
225/45R17	94T	XL	7.0-(7.5)-8.5	25.0	8.9	12.0	-	
225/65R17	106T	XL	6.0-(6.5)-8.0	28.5	9.0	13.2	-	

Ø 16								
205/55R16	94T	XL	5.5-(6.5)-7.5	24.9	8.4	12.0	-	

Ø 15								
195/65R15	95T	XL	5.5-(6.0)-7.0	25.0	7.9	12.0	-	

TOURING



DIMAX CLASSIC

SIZE	LI./S.R.	L.R.	SIDEWALL	APPROVED RIM	O.D.(in)	O.W.(in)	T.D.(1/32")	UTQG	AVAIL.
------	----------	------	----------	--------------	----------	----------	-------------	------	--------

**DIMAX CLASSIC**

TOURING

Ø 16									
185R16	93H	-	-	5.0-(5.5)-6.0	27.6	7.3	10.7	-	-
Ø 15									
125R15	68S	-	-	3.0-(3.5)-4.0	22.9	5.0	8.2	-	-
125R15	68S	-	WSW	3.0-(3.5)-4.0	22.9	5.0	8.2	-	-
155R15	82S	-	-	4.0-(4.5)-5.0	24.8	6.2	8.8	-	-
155R15	82S	-	WSW	4.0-(4.5)-5.0	24.8	6.2	8.8	-	-
165R15	86H	-	-	4.0-(4.5)-5.5	25.4	6.6	9.4	-	-
165R15	86H	-	WSW	4.0-(4.5)-5.5	25.4	6.6	9.4	-	-
175/70R15	86H	-	-	4.5-(5.0)-5.5	24.7	7.0	9.4	-	-
185/70R15	89V	-	-	4.5-(5.5)-6.0	25.2	7.4	10.7	-	-
185/70R15	89V	-	WSW (N)	4.5-(5.5)-6.0	25.2	7.4	10.7	-	-
185/70R15	89W	-	-	4.5-(5.5)-6.0	25.2	7.4	10.7	-	-
185R15	93V	-	-	4.5-(5.0)-6.0	26.7	7.2	10.7	-	-
205/70R15	96V	-	-	5.0-(6.0)-7.0	26.3	8.2	10.7	-	-
205/70R15	96W	-	-	5.0-(6.0)-7.0	26.3	8.2	10.7	-	-
205R15	97V	-	-	5.5-(6.0)-6.5	27.9	8.2	11.3	-	-
215/60R15	94W	-	-	6.0-(6.5)-7.5	25.2	8.7	11.3	-	-
215/70R15	98W	-	-	5.5-(6.5)-7.0	26.9	8.7	11.3	-	-
215/70R15	98W	-	WSW (N)	5.5-(6.5)-7.0	26.9	8.7	11.3	-	-
235/70R15	101V	-	-	6.5-(7.0)-7.5	28.0	9.4	12.0	-	-
235/70R15	101V	-	WSW (N)	6.5-(7.0)-7.5	28.0	9.4	12.0	-	-
255/60R15	102W	-	-	7.0(7.5)-9.0	27.0	10.2	12.0	-	-
Ø 14									
165R14	84H	-	-	4.0-(4.5)-5.0	24.5	6.6	9.4	-	-
175R14	88H	-	-	4.5-(5.0)-5.5	25.0	7.0	9.4	-	-
185/70R14	88V	-	-	4.5-(5.5)-6.0	24.3	7.4	10.7	-	-
185/70R14	88V	-	WSW (N)	4.5-(5.5)-6.0	24.3	7.4	10.7	-	-
185R14	90H	-	-	5.0-(5.5)-6.0	25.6	7.4	10.7	-	-
185R14	90H	-	WSW	5.0-(5.5)-6.0	25.6	7.4	10.7	-	-
195/70R14	91V	-	-	5.0-(6.0)-6.5	24.8	7.8	10.7	-	-
205/70R14	95W	-	-	5.0-(6.0)-7.0	25.4	8.2	10.7	-	-
205R14	89W	-	-	5.5-(6.0)-6.5	27.0	8.2	11.3	-	-
215/70R14	92V	-	WSW (N)	5.5-(6.5)-7.0	25.9	8.6	11.3	-	-
215/70R14	92W	-	-	5.5-(6.5)-7.0	25.9	8.6	11.3	-	-
Ø 13									
145R13	75T	-	-	3.5-(4.0)-5.0	22.1	5.7	8.2	-	-
175/50R13	72V	-	-	5.0-(5.5)6.0	19.9	7.2	9.4	-	-
185/70R13	86V	-	-	4.5-(5.5)-6.0	23.2	7.4	10.7	-	-
185/70R13	86V	-	WSW (N)	4.5-(5.5)-6.0	23.2	7.4	10.7	-	-
205/60R13	86V	-	-	6.0-(6.5)	22.7	8.2	11.3	-	-
Ø 12									
125R12	62S	-	-	3.0-(3.5)-4.0	19.9	5.0	8.2	-	-
125R12	62S	-	WSW	3.0-(3.5)-4.0	19.9	5.0	8.2	-	-



OMNI UNITED USA

[www.omni-united.com](http://www.omni-united.com) | [info@omni-united.com](mailto:info@omni-united.com)